



Three-Way Decisions Community Detection Model Based on Weighted Graph Representation

Jie Chen¹, Yang Li¹, Shu Zhao¹(✉), Xiangyang Wang², and Yanping Zhang¹

¹ School of Computer Science and Technology, Anhui University,
Hefei 230601, Anhui, People's Republic of China
zhaoshuzs2002@hotmail.com

² Anhui Electrical Engineering Professional Technique College,
Hefei 230051, Anhui, People's Republic of China

Abstract. Community detection is of great significance to the study of complex networks. Community detection algorithm based on three-way decisions (TWD) forms a multi-layered community structure by hierarchical clustering and then selects a suitable layer as the community detection result. However, this layer usually contains overlapping communities. Based on the idea of TWD, we define the overlapping part in the communities as boundary region (BND), and the non-overlapping part as positive region (POS) or negative region (NEG). How to correctly divide the nodes in the BND into the POS or NEG is a challenge for three-way decisions community detection. The general methods to deal with boundary region are modularity increment and similarity calculation. But these methods only take advantage of the local features of the network, without considering the information of the divided communities and the similarity of the global structure. Therefore, in this paper, we propose a method for three-way decisions community detection based on weighted graph representation (WGR-TWD). The weighted graph representation (WGR) can well transform the global structure into vector representation and make the two nodes in the boundary region more similar by using frequency of appearing in the same community as the weight. Firstly, the multi-layered community structure is constructed by hierarchical clustering. The target layer is selected according to the extended modularity value of each layer. Secondly, all nodes are converted into vectors by WGR. Finally, the nodes in the BND are divided into the POS or NEG based on cosine similarity. Experiments on real-world networks demonstrate that WGR-TWD is effective for community detection in networks compared with the state-of-the-art algorithms.

Keywords: Community detection · Hierarchical clustering · Three-way decisions · Weighted graph representation

1 Introduction

Nowadays, there are all kinds of complex systems with specific functions in the real world such as online social systems, medical systems and computer systems. These systems can be abstracted into networks with complex internal structures, called complex networks. The research of complex networks has received more and more attention due to the development of the Internet. Community structure [6, 23] is a common feature of complex networks, which means that a network consists of several communities, the connections between communities are sparse and the connections within a community are dense [10]. Mining the community structure in the network is of great significance to understand the network structure, analyze the network characteristics and predict the network behavior. Thus, community detection has become one of the most important issues in the study of complex networks.

In recent years, a great deal of research is devoted to community detection in networks. Most community detection methods are used to identify non-overlapping communities (i.e., a node belongs to only one community). The main approaches include graph partitioning and clustering [9, 10, 13], modularity maximization [1, 20], information theory [12, 25] and non-negative matrix factorization [16, 27]. The Kernighan-Lin algorithm [13] is a heuristic graph partitioning method that detects communities by optimizing the edges within and between communities. GN algorithm [10] is a representative hierarchical clustering method, which can find communities by removing the links between communities. Blondel et al. proposed the Louvain algorithm [1], which is a well-known optimization method based on modularity. It is used to handle large-scale networks due to low time complexity. Liu et al. [16] put forward a community detection method by using non-negative matrix factorization. Zhao et al. [33] introduced the idea of granular computing into the community detection of network and proposed a community detection method based on clustering granulation.

The existing non-overlapping community detection algorithms have made great achievements, but these algorithms only use the traditional two-way decisions [29, 30] method (the acceptance or rejection decision) to deal with the overlapping nodes between communities. Compared with the two-way decisions method, the three-way decisions theory (TWD) [28] adds a non-commitment decision. The main idea of TWD is to divide an entity set into three disjoint regions, which are denoted as positive region (POS), negative region (NEG) and boundary region (BND) respectively. The POS adopts the acceptance decision, the NEG adopts the rejection decision, and the BND adopts the non-commitment decision (i.e., entities that cannot make a decision based on the current information are placed in the BND). For entities in the BND, we can further mine more information to realize their final partition. The introduction of non-commitment decision can effectively solve the decision-making errors caused by insufficient information, which is more flexible and closer to the actual situation.

How to deal with the boundary region has become a key issue for three-way decisions community detection. At present, the commonly used methods to

process the boundary region include modularity increment [20] and similarity calculation [2, 8]. But these methods only take advantage of the local features of the network, without considering the information of the divided communities and the similarity of the global structure. Therefore, how to tackle the boundary region effectively is a challenge.

In this paper, we propose a three-way decisions community detection model based on weighted graph representation (WGR-TWD). The graph representation can well transform the global structure of the network into vector representation and make the two nodes in the boundary region that appear in the same community more similar by using the weight. Firstly, the multi-layered community structure is constructed by hierarchical clustering. The target layer is selected according to the extended modularity value of each layer. Secondly, all nodes are converted into vectors by weighted graph representation. Finally, nodes in the boundary region are divided into positive or negative region based on cosine similarity. Thus, non-overlapping community detection is realized.

The key contributions of this paper can be summarized as follows:

- (1) We use weighted graph representation to obtain the global structure information of the network to guide the processing of the boundary region, which gets a better three-way decisions community detection method.
- (2) Based on the knowledge of the communities in the target layer, we make the two nodes connected by a direct edge in the boundary region more similar by using frequency of appearing in the same community as the weight. Then the walk sequences are constructed according to the weight of the edge. Finally, the Skip-Gram model is used to obtain the vector representation of nodes. Therefore, the weighted graph representation method is realized.
- (3) We evaluate the effectiveness the proposed model WGR-TWD on real-world networks compared with the baseline methods. The experimental results show the superior performance of our model.

The rest of this paper is organized as follows. We introduce related work in Sect. 2. We give the detailed description of our algorithm in Sect. 3. Experiments on real-world networks are reported in Sect. 4. Finally, we conclude the paper in Sect. 5.

2 Related Work

2.1 Community Detection of Hierarchical Clustering

Hierarchical clustering method has been widely used in community detection due to the hierarchical nature of the network structure. This approach can be divided into two forms: divisive method and agglomerative method. The divisive method removes the link with the lowest similarity index repeatedly, while the agglomerative method merges the pair of clusters with the highest similarity index repeatedly. These two methods eventually form a dendrogram, and communities are detected by cutting the tree.

The research of community detection based on hierarchical clustering has received widespread attention from scholars. Girvan and Newman proposed the GN algorithm [10], which is a typical divisive method. Clauset et al. [5] proposed a community detection algorithm based on data analysis, which is a representative agglomerative method. Fortunato et al. [9] presented an algorithm to find community structures based on node information centrality. Chen et al. proposed the LCV algorithm [4] which detects communities by finding local central nodes. Zhang et al. [32] introduced a hierarchical community detection algorithm based on partial matrix convergence using random walks.

Combining hierarchical clustering with granular computing, we introduce an agglomerative method based on variable granularity to build a dendrogram. Given an undirected and unweighted graph $G = (V, E)$, where V is the set of nodes, E denotes the set of edges. The set of neighbor nodes to a node v_i is denoted as $N(v_i) = \{v_j \in V | (v_i, v_j) \in E\}$, the set of initial granules is defined as $H^1 = \{C_1^1, C_2^1, \dots, C_p^1\}$. The formation process of the initial granules is as follows. First, we calculate the local importance of each node in the network. The local importance of a node v_i is defined as follows:

$$I(v_i) = \frac{|Z|}{|N(v_i)|}, \tag{1}$$

where $Z = \{v_j \in N(v_i) | d(v_j) \leq d(v_i)\}$, $d(v_i)$ is the degree of node v_i , and $|\cdot|$ denotes the number of elements in a set. Second, all important nodes are found according to the local importance of nodes. The node v_i is an important node if $I(v_i) > 0$. Finally, for any important node, an initial granule is composed of all neighbor nodes of the important node and the important node itself. After all the initial granules are obtained, the hierarchical clustering method based on variable granularity is described. The clustering coefficient between the two granules is defined as

$$f(C_i^m, C_j^m) = \frac{|C_i^m \cap C_j^m|}{\min\{|C_i^m|, |C_j^m|\}}, C_i^m, C_j^m \in H^m \tag{2}$$

where $|C_i^m \cap C_j^m|$ denotes the number of common nodes in granules C_i^m and C_j^m , $\min\{|C_i^m|, |C_j^m|\}$ is the smaller number of nodes in granules C_i^m and C_j^m , H^m is the granules set of the m th ($m = 1, 2, \dots$) layer. The collection of clustering thresholds is denoted as $\lambda = \{\lambda_m, m = 1, 2, \dots\}$, where λ_m is the clustering threshold of the m th layer. In order to automatically obtain the clustering threshold of each layer, λ_m is defined as

$$\lambda_m = \text{med}\{f(C_i^m, C_j^m) | \forall C_i^m, C_j^m \in H^m, C_i^m \cap C_j^m \neq \emptyset \wedge i \neq j\} \tag{3}$$

where $\text{med}\{\}$ is a median function. The clustering process is as follows. Firstly, for $\forall C_i^m, C_j^m \in H^m$, the clustering coefficient between them is calculated. Then the clustering threshold λ_m of the current layer is calculated. And the maximum clustering coefficient is found, which is denoted as $f(C_\alpha^m, C_\beta^m)$.

If $f(C_\alpha^m, C_\beta^m) \geq \lambda_m$, the two granules C_α^m and C_β^m are merged to form a new granule and the new granule is added to H^{m+1} . Otherwise, all the granules in H^m are added to H^{m+1} and H^m is set to empty. For each layer, repeat above clustering process until all nodes in the network are in a granule. Therefore, a dendrogram is built.

2.2 DeepWalk

Traditional network representation usually uses high-dimensional sparse vectors, which takes more running time and computational space in statistical learning. Network representation learning (NRL) is proposed to address the problem. NRL aims to learn the low-dimensional potential representations of nodes in networks. The learned representations can be used as features of the graph for various graph-based tasks, such as classification, clustering, link prediction, community detection, and visualization.

DeepWalk [24] is the first influential NRL model in recent years, which adopts the approach of natural language processing by using the Skip-Gram model [18, 19] to learn the representation of nodes in the network. The goal of Skip-Gram is to maximize the probability of co-occurrence among the words that appear within a window. DeepWalk first generates a large number of random walk sequences by sampling from the network. These walk sequences can be analogized to the sentences of the article, and the nodes are analogized to the words in the sentence. Then Skip-Gram can be applied to these walk sequences to acquire network embedding. DeepWalk can express the connection of the network well, and has high efficiency when the network is large.

3 The Proposed Algorithm

3.1 Weighted Graph Representation

To effectively deal with overlapping communities in the target layer, a weighted graph representation approach is proposed. At first, a weighted graph is constructed according to the community structure of the target layer. The weights of edges in an unweighted graph are defined as follows

$$W_{ij} = 1.0 + \sigma_{ij}/N_c \quad (4)$$

where σ_{ij} is the number of communities in which nodes v_i and v_j appear in a community at the same time, N_c is the total number of communities in the target layer. After that, an improved DeepWalk (IDW) model is used to acquire the vector representation of all nodes in the graph. Unlike DeepWalk, the IDW model constructs the walk sequences according to the weight of the edge. The greater the weight, the higher the walk probability. Assume that the current walk node is v_i , if $v_j \in N(v_i)$, then the walk probability from node v_i to node v_j is

$$P(v_i \rightarrow v_j) = \frac{W_{ij}}{\sum_{v_k \in N(v_i)} W_{ik}}. \quad (5)$$

After obtaining all the walk sequences, the Skip-Gram model is used to learn the vector representation of nodes from the walk sequences. The objective function of IDM is as follows

$$\min_R \sum_{-\omega \leq j \leq \omega, j \neq 0} -\log P(v_{i+j}|R(v_i)) \tag{6}$$

where $R(v_i)$ is the vector representation of node v_i , ω is the window size which is maximum distance between the current and predicted node within a walk sequence. Thus, the vector representation of all nodes in the network is obtained.

3.2 The WGR-TWD Algorithm

We will present the proposed WGR-TWD algorithm in this section. Figure 1 shows the overall framework of the proposed algorithm. Our algorithm consists of two parts: the construction of multi-layered community structure and boundary region processing.

The first part, we employ the hierarchical clustering method based on variable granularity to construct a multi-layered community structure according to Sect. 2.1. Some overlapping communities exist in the multi-layered community structure because of clustering mechanism, so we use the extended modularity (EQ) [26] to measure the partition quality of each layer. It is defined as follows

$$EQ = \frac{1}{2m} \sum_i \sum_{u \in C_i, v \in C_i} \frac{1}{O_u O_v} \left(A_{uv} - \frac{d_u d_v}{2m} \right) \tag{7}$$




Fig. 1. The framework of the proposed method.

where m is the number of edges in the network, C_i represents a community, O_u is the number of communities that node u belongs to, A_{uv} is the element of adjacent matrix, and d_u is the degree of node u . A larger EQ value means better performance for overlapping community division. Thus, we select the layer corresponding to the largest EQ value as the target layer.

Algorithm 1. WGR-TWD

Input: An undirected and unweighted graph $G = (V, E)$.

Output: Non-overlapping community structure $POS(G)$, $NEG(G)$.

- 1: construct the multi-layered community structure: $H = \{H^1, H^2, \dots, H^m\}$
 - 2: calculate EQ for each layer in H
 - 3: $H^t \leftarrow$ find the layer corresponding to the maximum EQ
 - 4: divide three regions according to H^t : $POS(G)$, $NEG(G)$, $BND(G)$
 - 5: get a weighted graph $G' = (V, E, W)$ according to Equation (4)
 - 6: $walks \leftarrow$ generate the walk sequences by W
 - 7: learn node representation from $walks$ by using Skip-Gram model
 - 8: **for** $\forall v \in BND(G)$ **do**
 - 9: $s(v, POS) \leftarrow$ calculate the similarity between node v and $POS(G)$
 - 10: $s(v, NEG) \leftarrow$ calculate the similarity between node v and $NEG(G)$
 - 11: **if** $s(v, POS) > s(v, NEG)$ **then**
 - 12: $POS(G) \leftarrow POS(G) + \{v\}$
 - 13: **else if** $s(v, POS) < s(v, NEG)$ **then**
 - 14: $NEG(G) \leftarrow NEG(G) + \{v\}$
 - 15: **end if**
 - 16: **end for**
 - 17: **return** $POS(G)$, $NEG(G)$
-

The second part introduces the method of dealing with overlapping communities in the target layer. Since there are overlapping communities in the target layer, we need to further divide the target layer to achieve non-overlapping community detection. Therefore, the three-way decisions theory (TWD) is introduced to handle overlapping communities. Based on the idea of TWD, we define the overlapping part in the communities as boundary region (BND), and the non-overlapping part as positive region (POS) or negative region (NEG). And our goal is to process nodes in the BND. First of all, we adopt the weighted graph representation method to learn the vector representation of all nodes in the network. After that, the nodes in the BND are divided into the POS or NEG by using cosine similarity. Suppose the vector of node u is $u = (x_1, x_2, \dots, x_n)$, node v is $v = (y_1, y_2, \dots, y_n)$, then the cosine similarity is defined as

$$S(u, v) = \frac{\sum_{i=1}^n x_i y_i}{\sqrt{\sum_{i=1}^n (x_i)^2} \cdot \sqrt{\sum_{i=1}^n (y_i)^2}}. \quad (8)$$

For arbitrary node v_i in the BND, find out all communities containing node v_i in the target layer, calculate the average value of cosine similarity between node v_i and non-overlapping nodes in each community as the similarity between node v_i and this community, then join node v_i into the community corresponding to the maximum similarity and update the community structure of the target layer. Repeat the above operation until all nodes in the BND are processed. The WGR-TWD algorithm is described in Algorithm 1.

4 Experiments

4.1 Datasets

We test the performance of our method on eight real-world datasets in which each dataset is described as follows, and the main information of those datasets are shown in Table 1.

Zachary’s karate club [31]. This is a social network of friendships between 34 members of a karate club at a US university in the 1970s.

Dolphin social network [17]. It is an undirected social network of frequent associations between 62 dolphins in a community living off Doubtful Sound, New Zealand.

Books about US politics [22]. A network of books about US politics published around the time of the 2004 presidential election and sold by the online bookseller Amazon.com. Edges between books represent frequent co-purchasing of books by the same buyers.

American college football [10]. A network of American football games between Division IA colleges in 2000.

Email communication network [21]. It is a complex network which indicates the email communications of a university. The network was composed by Alexandre Arenas.

Facebook [15]. The network was collected from survey participants using Facebook app.

Geom [11]. The authors collaboration network in computational geometry.

Collaboration [14]. The network is from the e-print arXiv and covers scientific collaborations between authors papers submitted to High Energy Physics Theory category.

4.2 Baseline Methods

In this paper, two representative algorithms are chosen to compare with the proposed WGR-TWD, as shown below:

- Modularity increment (MI) [3]. A hierarchical clustering method based on variable granularity, and the overlapping nodes between communities are divided according to modularity optimization.
- DeepWalk [24]. It is a network representation learning method. This approach is used to handle the overlapping communities in the target layer.

Table 1. Information of datasets.

Network	Nodes	Edges	Real clusters
Karate	34	78	2
Dolphin	62	159	2
Polbooks	105	441	3
Football	115	613	12
Email	1133	5451	Unknown
Facebook	4039	88234	Unknown
Geom	7343	11898	Unknown
Collaboration	9877	25998	Unknown

4.3 Evaluation Metrics

We employ two widely used criteria to evaluate the performance of community detection algorithms.

The first index is modularity (Q) [5], which is often used when the real community structure is not known. Q is defined as follows

$$Q = \frac{1}{2m} \sum_{i,j} \left[A_{ij} - \frac{d_i d_j}{2m} \right] \delta(c_i, c_j) \quad (9)$$

where m is the number of edges in the network, A is the adjacent matrix, d_i is the degree of node i , c_i represents the community to which node i belongs, and $\delta(c_i, c_j) = 1$ when $c_i = c_j$, else $\delta(c_i, c_j) = 0$. The higher the modularity value, the better the result of community detection.

Another index is normalized mutual information (NMI) [7], which is defined as follows

$$NMI = \frac{-2 \sum_{i=1}^{C_A} \sum_{j=1}^{C_B} C_{ij} \log \frac{C_{ij} n}{C_i \cdot C_j}}{\sum_{i=1}^{C_A} C_i \log \frac{C_i}{n} + \sum_{j=1}^{C_B} C_j \log \frac{C_j}{n}} \quad (10)$$

where C_A (C_B) denotes the number of communities in partition A (B), C_{ij} is the number of nodes shared by community i in partition A and by community j in partition B , C_i (C_j) represents the sum of elements of matrix C in row i (column j), and n is the number of nodes in the network. A higher value of NMI indicates the detected community structure is closer to the real community structure.

4.4 Experimental Results

In the networks with known real partition (the first four small networks), we use two indicators (Q and NMI) to evaluate our algorithm. Table 2 presents the community detection results of the proposed algorithm and the baseline algorithms on networks with known real partition. We can see that our method

Table 2. Experimental results on networks with known real partition (under EQ criterion).

Network	Index	MI	DeepWalk	WGR-TWD
Karate	Q	0.360	0.360	0.371
	NMI	0.837	0.837	1.000
Dolphin	Q	0.385	0.379	0.385
	NMI	0.814	0.889	0.830
Polbooks	Q	0.439	0.442	0.441
	NMI	0.469	0.448	0.453
Football	Q	0.480	0.545	0.558
	NMI	0.626	0.726	0.732

Table 3. Experimental results on networks with known real partition (under Q criterion).

Network	Index	MI	DeepWalk	WGR-TWD
Karate	Q	0.391	0.391	0.401
	NMI	0.606	0.620	0.700
Dolphin	Q	0.510	0.520	0.523
	NMI	0.619	0.613	0.618
Polbooks	Q	0.514	0.492	0.509
	NMI	0.501	0.463	0.489
Football	Q	0.582	0.596	0.596
	NMI	0.904	0.899	0.911

obtains best results on the Karate and Football datasets. On the Dolphin dataset, the Q value of our method is better and the NMI value is second to the DeepWalk method. On the Polbooks dataset, our method performs not well because the connections between nodes are sparse which is difficult to mine the structural information of the network.

To further verify the effectiveness of the proposed algorithm, the MI method is used to deal with each layer in the multi-layered community structure. And we select the layer corresponding to the maximum Q value as the target layer. The experimental results are shown in Table 3. Compared with Table 2, Table 3 can obtain higher Q value. Combined with Tables 2 and 3, our method can get better community detection results compared with the baseline methods.

We also conducted experiments on four large networks. On these networks, the real partition is unknown. Therefore, we only use modularity to evaluate the performance of different methods. Table 4 shows the community detection results of the proposed method and baseline methods. On the first three networks, we can see that our method obtains better results compared with the

Table 4. Modularity values on networks with unknown real partition.

Network	MI	DeepWalk	WGR-TWD
Email	0.537	0.538	0.542
Facebook	0.771	0.770	0.772
Geom	0.702	0.710	0.711
Collaboration	0.723	0.718	0.720

two baseline methods. On the Collaboration dataset, the MI method achieves the best performance which is a little bit higher than our method. The main reason is that the Collaboration network is very sparse which leads to poor vector representation of the nodes. In conclusion, the proposed method effectively addresses the problem of non-overlapping community detection in networks.

5 Conclusion

In this paper, we propose a method for three-way decisions community detection based on weighted graph representation. The target layer in multi-layered community structure is selected according to the extended modularity value of each layer. For the overlapping communities in the target layer, the weighted graph representation can well transform the global structure into vector representation and make the two nodes in the boundary region more similar by using frequency of appearing in the same community as the weight. Finally, the nodes in the boundary region are divided according to cosine similarity. Experiments on real-world networks demonstrate that the proposed method is effective for community detection in networks.

Acknowledgments. This work is supported by the National Natural Science Foundation of China (Grants Numbers 61876001) and the Major Program of the National Social Science Foundation of China (Grant No. 18ZDA032).

References

1. Blondel, V.D., Guillaume, J.L., Lambiotte, R., Lefebvre, E.: Fast unfolding of communities in large networks. *J. Stat. Mech: Theory Exp.* **2008**(10), P10008 (2008)
2. Chen, J., et al.: Three-way decision community detection algorithm based on local group information. In: Polkowski, L., et al. (eds.) *IJCRS 2017. LNCS (LNAI)*, vol. 10314, pp. 171–182. Springer, Cham (2017). https://doi.org/10.1007/978-3-319-60840-2_12
3. Chen, J., Li, Y., Yang, X., Zhao, S., Zhang, Y.: VGHC: a variable granularity hierarchical clustering for community detection. *Granular Comput.* **4**, 1–10 (2019)
4. Chen, Q., Wu, T.T.: A method for local community detection by finding maximal-degree nodes. In: *2010 International Conference on Machine Learning and Cybernetics*, vol. 1, pp. 8–13. IEEE (2010)

5. Clauset, A., Newman, M.E., Moore, C.: Finding community structure in very large networks. *Phys. Rev. E* **70**(6), 066111 (2004)
6. Cui, Y., Wang, X., Eustace, J.: Detecting community structure via the maximal sub-graphs and belonging degrees in complex networks. *Phys. A* **416**, 198–207 (2014)
7. Danon, L., Diaz-Guilera, A., Duch, J., Arenas, A.: Comparing community structure identification. *J. Stat. Mech: Theory Exp.* **2005**(09), P09008 (2005)
8. Fang, L., Zhang, Y., Chen, J., Wang, Q., Liu, F., Wang, G.: Three-way decision based on non-overlapping community division. *CAAI Trans. Intell. Syst.* **12**(3), 293–300 (2017)
9. Fortunato, S., Latora, V., Marchiori, M.: Method to find community structures based on information centrality. *Phys. Rev. E* **70**(5), 056104 (2004)
10. Girvan, M., Newman, M.E.: Community structure in social and biological networks. *Proc. Nat. Acad. Sci.* **99**(12), 7821–7826 (2002)
11. Gong, M., Cai, Q., Chen, X., Ma, L.: Complex network clustering by multiobjective discrete particle swarm optimization based on decomposition. *IEEE Trans. Evol. Comput.* **18**(1), 82–97 (2013)
12. Hajek, B., Wu, Y., Xu, J.: Information limits for recovering a hidden community. In: 2016 IEEE International Symposium on Information Theory (ISIT), pp. 1894–1898. IEEE (2016)
13. Kernighan, B.W., Lin, S.: An efficient heuristic procedure for partitioning graphs. *Bell Syst. Tech. J.* **49**(2), 291–307 (1970)
14. Leskovec, J., Kleinberg, J., Faloutsos, C.: Graph evolution: densification and shrinking diameters. *ACM Trans. Knowl. Discov. Data (TKDD)* **1**(1), 2 (2007)
15. Leskovec, J., McAuley, J.J.: Learning to discover social circles in ego networks. In: *Advances in Neural Information Processing Systems*, pp. 539–547 (2012)
16. Liu, X., Wang, W., He, D., Jiao, P., Jin, D., Cannistraci, C.V.: Semi-supervised community detection based on non-negative matrix factorization with node popularity. *Inf. Sci.* **381**, 304–321 (2017)
17. Lusseau, D.: The emergent properties of a dolphin social network. *Proc. R. Soc. Lond. Ser. B: Biol. Sci.* **270**(Suppl. 2), S186–S188 (2003)
18. Mikolov, T., Chen, K., Corrado, G., Dean, J.: Efficient estimation of word representations in vector space. *arXiv preprint [arXiv:1301.3781](https://arxiv.org/abs/1301.3781)* (2013)
19. Mikolov, T., Sutskever, I., Chen, K., Corrado, G.S., Dean, J.: Distributed representations of words and phrases and their compositionality. In: *Advances in Neural Information Processing Systems*, pp. 3111–3119 (2013)
20. Newman, M.E.: Fast algorithm for detecting community structure in networks. *Phys. Rev. E* **69**(6), 066133 (2004)
21. Newman, M.E.: Finding community structure in networks using the eigenvectors of matrices. *Phys. Rev. E* **74**(3), 036104 (2006)
22. Newman, M.E.: Modularity and community structure in networks. *Proc. Nat. Acad. Sci.* **103**(23), 8577–8582 (2006)
23. Newman, M.E., Girvan, M.: Finding and evaluating community structure in networks. *Phys. Rev. E* **69**(2), 026113 (2004)
24. Perozzi, B., Al-Rfou, R., Skiena, S.: Deepwalk: online learning of social representations. In: *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 701–710 (2014)
25. Rosvall, M., Bergstrom, C.T.: An information-theoretic framework for resolving community structure in complex networks. *Proc. Natl. Acad. Sci.* **104**(18), 7327–7331 (2007)

26. Shen, H., Cheng, X., Cai, K., Hu, M.B.: Detect overlapping and hierarchical community structure in networks. *Phys. A* **388**(8), 1706–1712 (2009)
27. Wu, W., Kwong, S., Zhou, Y., Jia, Y., Gao, W.: Nonnegative matrix factorization with mixed hypergraph regularization for community detection. *Inf. Sci.* **435**, 263–281 (2018)
28. Yao, Y.: Three-way decision: an interpretation of rules in rough set theory. In: Wen, P., Li, Y., Polkowski, L., Yao, Y., Tsumoto, S., Wang, G. (eds.) RSKT 2009. LNCS (LNAI), vol. 5589, pp. 642–649. Springer, Heidelberg (2009). https://doi.org/10.1007/978-3-642-02962-2_81
29. Yao, Y.: Three-way decisions with probabilistic rough sets. *Inf. Sci.* **180**(3), 341–353 (2010)
30. Yao, Y.: Two semantic issues in a probabilistic rough set model. *Fundam. Inform.* **108**(3–4), 249–265 (2011)
31. Zachary, W.W.: An information flow model for conflict and fission in small groups. *J. Anthropol. Res.* **33**(4), 452–473 (1977)
32. Zhang, W., Kong, F., Yang, L., Chen, Y., Zhang, M.: Hierarchical community detection based on partial matrix convergence using random walks. *Tsinghua Sci. Technol.* **23**(1), 35–46 (2018)
33. Zhao, S., Wang, K., Chen, J., Zhang, Y.: Community detection algorithm based on clustering granulation. *J. Comput. Appl.* **34**(10), 2812–2815 (2014)