

REVIEW

Open Access



Pharmaceuticals and personal care products in water and wastewater: a review of treatment processes and use of photocatalyst immobilized on functionalized carbon in AOP degradation

Adewumi Olufemi Oluwole, Elizabeth Oyinkansola Omotola and Olatunde Stephen Olatunji*

Abstract

The presence of emerging contaminants such as pharmaceutical and personal care products in many aqueous matrices have been reported. One of such matrix is streams of wastewater, including wastewater treatment plants inflows and outflows and wastewater flow by-passing wastewater treatment plants. Their persistence arises from their resistant to breakdown, hence they may remain in the environment over long time, with a potential to cause adverse effects including endocrine disruption, gene toxicity, the imposition of sex organs, antibiotic resistance and many others in some aquatic organisms exposed to arrays of residues of pharmaceutical and personal care products. Among the treatment techniques, advanced oxidation processes have been reported to be a better technique through which these PPCPs can be degraded in the WWTPs. Heterogeneous photocatalysis using various photocatalyst immobilized on solid support such as activated carbon, graphene and carbon nanotubes in AOPs have been shown to be a viable and efficient method of PPCPs degradation. This is because, the performance of most WWTPs is limited since they were not designed to degrade toxic and recalcitrant PPCPs. This review highlight the occurrence, concentration of PPCPs in wastewater and the removal efficiency of heterogeneous photocatalysis of TiO_2 immobilized on solid supports.

Keywords: Ppcps, Wastewater, WWTPs, AOPs, Heterogeneous photocatalysis, Photocatalyst immobilized, Activated carbon/graphene/carbon nanotubes solid support, PPCPs degradation, Removal efficiency

Introduction

The expansion in the world's population, economic development, the industrial revolution, and climate change has led to an increase in the quantity of waste generation as well as an increase in the introduction of specific categories of compounds referred to as emerging contaminants, into the environments. The U.S. Environmental Protection Agency (EPA) described "emerging contaminants" as chemicals or materials which were previously not listed

for routine monitoring, characterized by a perceived potential or real threat to human and environmental health, and lacks published health standard, environmental protection laws, and regulations [1]. According to the U.S. Geological Survey (USGS), emerging contaminants are "any synthetic or naturally occurring chemical or any microorganism that is not usually investigated in the environment but can find its way into the environment and cause known or suspected adverse ecological and/or human health effects". Hence, there is an urgent need to develop methods for the removal of these emerging contaminants from the environment.

*Correspondence: olatunji@ukzn.ac.za
School of Chemistry and Physics, University of KwaZulu-Natal, Westville,
Durban 4000, South Africa



© The Author(s) 2020. This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>. The Creative Commons Public Domain Dedication waiver (<http://creativecommons.org/publicdomain/zero/1.0/>) applies to the data made available in this article, unless otherwise stated in a credit line to the data.

Emerging contaminants can be classified into several groups, which include; perfluorinated compounds (PFCs), pharmaceuticals and personal care products (PPCPs), brominated flame retardants (BFRs), microplastics and toxins from harmful algal blooms, etc. [2, 3]. Concerns about the potentially adverse effects of these substances on human and ecosystem health are arising from their persistence, environmental accumulation tendency, exposure potential, bioaccumulation/biomagnification potential, and bioactivity. These contaminants may, therefore, be prioritized for regulation, depending on the information pool from monitoring data regarding their occurrence, their toxicity, potential health effects, and public perception.

A significant index factor of public and community health is access to good quality water, which is imperatively crucial for all life forms. The pollution of the water system may result in an outbreak of water-borne diseases, which can have acute or long-term health implications and even death. Humans and animals are susceptible to these diseases because polluted water is mostly the exposure pathway to infectious pathogens and carcinogenic organic and inorganic contaminants. For instance, while the dissolution of active pharmaceutical ingredients (APIs) in aqueous matrices is variable; they are primarily water-soluble and have such properties that allow them to permeate membranes and persist in the biological systems. The inherent properties of APIs, however, raise questions about their environmental risk, the potential for accumulation, and bioactivity within an aquatic environment [4]. As with administered dosages on target organisms, pharmaceuticals are capable of altering biochemical and physiological processes in many non-target organisms. Hence, their capacity to induced undesirable consequences on native and peripatetic species of organisms exposed to APIs contaminated environment.

Although the presence of PPCPs in the environment has been noticed for some years now, the full extent of their presence and the risk associated with their presence in the environment has not been fully established. Also, the removal of these contaminants in wastewater treatment (WWTPs), before their discharge into surface water has proven to be difficult due to their low occurrence concentrations, and the challenges arising from analyzing them [5]. Therefore, there is a need to modify and upgrade the existing WWTPs to be able to resolve or remove these contaminants. The conventional wastewater treatment methods which include; physical, chemical or combination of physicochemical process, involving the following: filtration, flocculation, coagulation process, sedimentation, biological processes, membrane filtration, chlorination, adsorption process via activated carbon (AC), carbon nanotubes (CNTs), graphene oxide

(GO), ozonation, photo-catalysis ultraviolet irradiation, ultra-sonication, and others. Unfortunately, these methods cannot adequately remove organic pollutants from wastewater. In addition to the processes being chemically and operationally intensive, they require large systems, infrastructure, and engineering expertise, which make them burdensome, ineffective, time-consuming, and costly [6, 7].

Moreover, the use of nano-adsorbents in the removal of PPCPs from water matrices has been associated with some challenges, among which are smaller particle size, generation of secondary pollutants, inability to reuse, or regenerate etc. Also, the use of semiconductors as catalysts in the degradation of PPCPs encounter the following drawbacks such as; requirement for high ultraviolet radiation for their activities due to wide bandgap energy within them; some are carcinogenic, e.g., TiO_2 ; there is also the challenge with electron-hole pair recombination after use [8, 9]. Hence, the need to design materials that are green, economically efficient and effective methods for pollution control and prevention are needed for environmental protection and effluent discharge to have minimal impacts on human health and the biosphere.

Consequently, the advanced oxidation process (AOP) has been reported to be one of the most promising methods that can be employed for mineralization of complex organic pollutants as an effective alternative technique that involves the in-situ generation of strong oxidation radicals sufficient enough to degrade and eliminate organic pollutants within environmental matrices.

AOP is efficient in the removal of hazardous pollutants and their mineralization into non-toxic inorganic aliphatic acid, CO_2 and water as compared to other decontamination techniques like; adsorption, coagulation, flocculation, sedimentation, bio-filtration, etc., as a result of the generation of active oxidizing agents such as hydroxyl radicals, superoxide, ozonide and photo-produced electron-hole pairs [10–12]. AOP can be achieved by direct ozonolysis, catalytic oxidation, homogenous/heterogeneous catalyzed oxidation, with the more recent advances in photocatalytic oxidation which is one of the green technologies that has attracted scientific interest as viable alternatives for the treatment of wastewater because of its low operating cost, nontoxicity, and effective reduction of contaminants [13, 14].

Over the years, efforts have been directed towards synthesizing various nanocomposites for photocatalysis purposes. This technique is one of the most preferred AOP because it offers the possibility of utilizing naturally available and renewable solar energy as a potential energy source containing visible light in the presence of a suitable photocatalyst prepared from metal oxides or semiconductors as catalyst immobilized on various solid

supports for the photodegradation of pharmaceuticals. Unfortunately, the photocatalytic performance of most semiconductor photocatalyst is still low due to lack of enough active sites, large band gap, utilization of photons from the sun, and limited fast photoinduced charge carrier recombination [12, 15]. Hence, the development of efficient and highly stable photocatalysts with increased light absorption in the visible spectrum, reduced band gap, and decreased rapid electron–hole pairs recombination rate is necessary for the photocatalytic degradation of organic pollutants under visible light.

Hence, the aim of this review is to discuss the occurrence of pharmaceuticals and personal care products in the environment, highlights the failure of the conventional methods in degrading pharmaceuticals and personal care products from the water matrices and why photocatalytic degradation processes of pharmaceuticals and personal care products via the use of various semiconductor photocatalyst immobilized either on other semiconductors, metal oxide or on different carbon sources such as activated carbon, carbon nanotubes, and graphene oxides has been able to degrade these organic pollutants to propose more alternative nanomaterial that is green, efficient, non-toxic, cheap and more effective with a short time for the photocatalytic degradation of different organic pollutants.

Pharmaceuticals and personal care products (PPCPs)

Pharmaceuticals and personal care products (PPCPs) consists of APIs, moisturizers, lipsticks, shampoos, hair colors, deodorants, toothpaste surfactant, and many household products that are mainly used for improving the quality of daily life [16] and their degradation products have been inadvertently present in the aquatic environment since the 1970s [17]. Their residues have been detected in all types of surface water, groundwater, and the oceanic environment in the last 20 years [18]. These compounds find their way into many aquatic environments receiving contaminated water from urban wastewater streams (domestic/industrial discharges, WWTPs effluents, etc.), which in turn get transferred into the water cycle, even reaching drinking water, as a result of their hydrophilic character and low removal efficiency of wastewater treatment plants (WWTPs).

Pharmaceuticals generally include prescription or over the counter (OTC) veterinary/human drugs and nutraceuticals administered for prophylaxis/therapeutic and health supplements purposes. They are classified as antibiotics, analgesics, blood lipid regulators, natural and synthetic hormones, β -blockers, anti-diabetics, anti-hypertensive, and many more products that are used for health purposes [19]. These substances are continuously

discharged into the aquatic environment from a point and non-point domestic and industrial sources.

Presence and occurrence of pharmaceuticals and personal care products in wastewater

A global survey has indicated the presence of several classes of PPCPs in most aquatic environments. Unfortunately, these data rely primarily on studies conducted in Europe, North America, Scandinavia, and a few other places. The availability of such data in those parts of the world is because research on PPCPs and many endocrine disruption contaminants/pollutants in African Countries and especially in the South Africa aquatic system is scanty [20, 21]. Despite the lack of data, the occurrence of some PPCPs at concentration levels that sometimes surpassed $\mu\text{g/L}$ level in WWTPs effluents and environmental waters have been reported [22–24]. Research studies on remediation of contaminated/polluted aqueous matrices and or the removal of these contaminants in drinking treatment plants and or during wastewater treatment before discharge to surface water is still far behind and probably lacking.

Commonly detected pharmaceuticals in different environmental matrices and their occurrence levels are as listed in Table 1 below.

Classification of pharmaceuticals and personal care products

Pharmaceuticals can be classified into different active organic groups of compounds [44, 45]. These include but not limited to; (i) antibiotics which comprise penicillin, tetracycline, sulfonamides, macrolides, fluoroquinolones, and β lactams; (ii) steroids hormones many of which have been implicated as endocrine-disrupting compounds such as estrogens, estrone, estriol, 17- β -estradiol, 17- α -ethinylestradiol, testosterone, etc. (iii) analgesic and non-steroidal anti-inflammatory drugs (NSAIDS) which are one of the most prescribed groups of pharmaceuticals that include acetaminophen, diclofenac, ibuprofen, and naproxen; (iv) antiepileptic drugs such as carbamazepine, used in reducing the frequency of epileptic seizures; (v) blood lipid regulators, e.g., bezafibrate, gemfibrozil, fenofibric acid and clofibrate; (vi) β -blockers such as salbutamol, atenolol, sotalol, theophylline and metoprolol used in treating hypertension and cardiac dysfunctions; (vii) antineoplastic such as cytostatic drugs used in cancer therapy; etc. Antimicrobial agents, fungicides, disinfectants, synthetic musks, some preservatives, some sunscreen UV filters, etc., may also be referred to as pharmaceuticals depending on the description of use.

Personal Care Products (PCPs) groups include; (i) pesticides/insect repellants, (ii) musk; widely used as fragrances of many personal care products such as;

Table 1 Commonly detected PPCPs in different environmental matrices and their occurrence levels around the world

PPCPs	Concentration ($\mu\text{g/L}$)	Country	Source	References
Sulfamethoxazole	0.33–0.61	Beijing	River and sewage water	[25]
	2.00	Australia	Surface water	[26]
	3.00	Australia	Wastewater treatment plant influent	[26]
	0.20	Australia	Wastewater treatment plant effluent	[26]
	34.50	Kwazulu-Natal, South Africa	Wastewater treatment plant influent	[24]
	3.68	Kwazulu-Natal, South Africa	Surface water	[22]
	0.049	Scaynes Hill, UK	Wastewater treatment plant influent	[27]
	0.023	Scaynes Hill, UK	Wastewater treatment plant effluent	[27]
Nalidixic acid	1.73–30.84	Kwazulu-Natal, South Africa	Surface water	[22]
	29.9	Kwazulu-Natal, South Africa	WWTW influent	[28]
	25.2	Kwazulu-Natal, South Africa	WWTW effluent	[28]
	0.20	Australia	WWTW influent	[26]
	0.45	Australia	WWTW effluent	[26]
	0.75	Australia	Hospital effluent; Wastewater treatment plant	[26]
Aspirin	0.664	South Wales, UK	Cilfynydd wastewater treatment influent	[29]
	0.027	South Wales, UK	Cilfynydd wastewater treatment effluent	[29]
	2.49	South Wales, UK	Coslech Wastewater treatment influent	[29]
	0.02	South Wales, UK	Coslech Wastewater treatment effluent	[29]
	2.566	Catalonia, Spain	Wastewater Influent	[30]
	0.034	Catalonia, Spain	Wastewater effluent	[30]
	0.012	Catalonia, Spain	Surface Water	[30]
	874	Canada	Influent sewage treatment plants	[31]
	59.6	Canada	Effluent sewage treatment plants	[31]
	118.00	Kwazulu-Natal, South Africa	Wastewater treatment plant influent	[28]
44.20	South Africa	Wastewater treatment plant effluent	[28]	
Naproxen	0.838	South Wales, UK	Cilfynydd wastewater treatment influent	[29]
	0.37	South Wales, UK	Cilfynydd wastewater treatment effluent	[29]
	1.173	South Wales, UK	Coslech wastewater treatment influent	[29]
	0.17	South Wales, UK	Coslech wastewater treatment effluent	[29]
	5.938	Korea	WWTP influent	[32]
	0.120	Korea	WWTP effluent	[32]
	52.30–55.00	Gauteng, South Africa	WWTP influent	[23]
	13.50–20.40	Gauteng, South Africa	WWTP effluent	[23]
Ibuprofen	1.68	South Wales, UK	Cilfynydd wastewater treatment influent	[29]
	0.26	South Wales, UK	Cilfynydd wastewater treatment effluent	[29]
	2.29	South Wales, UK	Coslech wastewater treatment influent	[29]
	0.14	South Wales, UK	Coslech wastewater treatment effluent	[29]
	5–8	Canada	Wastewater effluent	[33]
	62.82	Kwazulu-Natal, South Africa	WWTW influent	[24]
	58.71	Kwazulu-Natal, South Africa	WWTW effluent	[24]
	9.494	Korea	WWTP influent	[32]
	0.015	Korea	WWTP effluent	[32]

Table 1 (continued)

PPCPs	Concentration ($\mu\text{g/L}$)	Country	Source	References
Acetaminophen	211.38	South Wales, UK	Cilfynydd wastewater treatment influent	[29]
	11.73	South Wales, UK	Cilfynydd wastewater treatment effluent	[29]
	178.12	South Wales, UK	Coslech wastewater treatment influent	[29]
	0.35	South Wales, UK	Coslech wastewater treatment effluent	[29]
	11.3	France	WWTP influents	[34]
	5.76	Kwazulu-Natal, South Africa	WWTW influent	[24]
	74.552	Korea	WWTP influent	[32]
Carbamazepine	0.023	Korea	WWTP effluent	[32]
	1.69	South Wales, UK	Cilfynydd wastewater treatment influent	[29]
	2.49	South Wales, UK	Cilfynydd wastewater treatment effluent	[29]
	0.95	South Wales, UK	Coslech wastewater treatment influent	[29]
	0.83	South Wales, UK	Coslech wastewater treatment effluent	[29]
	1.9	Canada	Wastewater treatment influent	[31]
	2.3	Canada	Wastewater treatment influent	[31]
Diclofenac	0.42	Tainan, Taiwan	WWTP effluent	[35]
	22.3	Kwazulu-Natal, South Africa	Wastewater treatment plant influent	[28]
	12.4	Kwazulu-Natal, South Africa	Wastewater treatment plant effluent	[28]
	15.3–19.4	Germany	Wastewater treatment plant	[19]
	0.21–0.49	France	WWTP effluents	[34]
	0.397	Scaynes Hill, UK	Wastewater treatment plant influent	[27]
	0.119	Scaynes Hill, UK	Wastewater treatment plant effluent	[27]
Tetracyclines	0.251	Sapporo, Japan	Municipal wastewater treatment plant influent	[36]
	0.145	Sapporo, Japan	Municipal wastewater treatment plant effluent	[36]
	0.10	Australia	WWTW influent	[26]
	0.02	Australia	WWTW effluent	[26]
	0.6–5.7	Kwazulu-Natal, South Africa	Surface water	[22]
	0.003–0.008	Tianjin China	Municipal wastewaters influents	[37]
	Bisphenol A	1.52	Tianjin China	Municipal wastewaters influents
0.190–1.0789		Harbin city, China	Wastewater influents	[38]
0.0614–0.1755		Harbin city, China	Wastewater effluent	[38]
0.028		Pretoria and Cape Town, South Africa	Drinking water	[39]
0.002		Germany	Drinking water	[40]
0.047		Germany	Sewage Treatment effluents	[40]
0.014		Germany	River Water	[40]
Triclosan	78.40–127.70	Gauteng, South Africa	WWTP influent	[23]
Benzophenone	1.5–8.58	Nagpur city, India	Sewage treatment plant	[41]
	10.70–22.90	Gauteng, South Africa	WWTP effluent	[23]
Estrone	0.013–0.351	Kwazulu-Natal, South Africa	WWTW influent	[42]
	0.078–0.158	Tianjin China	Municipal wastewaters influents	[37]
	0.003–0.078	Kwazulu-Natal, South Africa	WWTW effluent	[42]
	0.0102–0.0349	Harbin city, China	Wastewater influents	[38]
	0.0083–0.014	Harbin city, China	Wastewater effluents	[38]

Table 1 (continued)

PPCPs	Concentration ($\mu\text{g/L}$)	Country	Source	References
17- β -Estradiol	0.02–0.199	Kwazulu-Natal, South Africa	WWTW influent	[42]
	0.004–0.107	Kwazulu-Natal, South Africa	WWTW effluent	[42]
	0.011–0.054	Tianjin China	Municipal wastewaters influents	[37]
	0.0466–0.093	Harbin city, China	Wastewater influents	[38]
	0.0087–0.0324	Harbin city, China	Wastewater effluents	[38]
	0.0041	California, USA	Municipal wastewater effluent	[43]
Estriol	0.003–0.009	Kwazulu-Natal, South Africa	WWTW influent	[42]
	0.042–0.162	Tianjin China	Municipal wastewaters influents	[37]
Progesterone	0.163–0.904	Kwazulu-Natal, South Africa	WWTW influent	[42]
	0.025	Kwazulu-Natal, South Africa	WWTW effluent	[42]
Testosterone	0.119–0.635	Kwazulu-Natal, South Africa	WWTW influent	[42]
	0.026	Kwazulu-Natal, South Africa	WWTW influent	[42]

perfume, body lotion, hair care products, shower bath products facial essence and numerous household products, (iii) soaps and detergents, (iv) sunscreen UV filters, which are chemicals that serve as absorbers and protection of the skin from different ultraviolet radiations from UV-induced damages, (v) triclosan; a lipid-soluble, broad-spectrum, antimicrobial agents which are used as preservatives in personal care products such as hand soap, shampoos, detergents, toothpaste, sunscreen, deodorants, and (vi) antiseptic which serves various purposes in medical devices, household items and as additives in packaging textiles and functional clothing [46–48]. Some of their structures are given in Fig. 1

Source of PPCPs in the environment

The global annual consumption of PPCPs in developed world and countries such as Brazil, Russia, India, China, and South Africa has been reported to have increased over the last decade, due to their medical use for prophylaxis/therapy, and economic use for viability sustenance of commercial aquaculture and livestock agriculture [49]. As a result, residues of compounds of PPCPs are continuously released into wastewater via wash-off, urine, and feces as parent compounds, derivative conjugates, or metabolites [50]. PPCPs can also enter the surface water through direct discharge from industries [51], hospitals, household's/domestic wastewater and through surface runoff (as result of the use of contaminated biosolids as manure spread on agricultural land), reaching water bodies and groundwater by leaching or bank filtration. Other means through which PPCPs enter into the aquatic environment include disposal of unused medicines into landfills, irrigation with wastewater, off-label emissions, and disposal of carcasses of treated animals [52], and sewage

or wastewater treatment plants [53, 54]. Brauschet al. [55] reported that the WWTPs are the main route through which PPCPs are discharged into the aquatic environment. They have been found in lakes, rivers, groundwater, marine, and coastal area waters and drinking water [45, 56, 57].

Aquatic sediments can also hold a substantial amount of PPCPs because of their affinity binding/sorption capacity [58]. Thus, excess PPCPs do not remain in the water for long, as they partition between water, sediment, and other components of the aquatic ecosystem, via diffusion, seeding, silting out of suspended particle bonded-PPCPs and other physical/chemical processes. Aside from the application of contaminated biosolids on farmland soils, several PPCPs reach the soil and different terrestrial domain through the deposition (air/wet) of short and long-range atmospheric transferred aerodynamic sized PPCPs particulates [59]. A schematic diagram showing potential sources and pathways of pharmaceuticals is shown in Fig. 2.

Transformation of PPCPs and their metabolites

The soluble characteristics and bioactive nature of many pharmaceuticals and some personal care products may facilitate their biotransformation and depuration in biological features. However, this is not the case with most PPCPs in the environment, where they do not readily degrade. Many pharmaceuticals are discharged from the human and animal bodies in a mixture of their parent compound and conjugate metabolites [61, 62]. The extent of body metabolism and pharmacokinetics index is a function of the ratio between the parent compound (un-metabolized) and the conjugate metabolites concentrations measured in urine or feces [63, 64]. They may also




Fig. 1 Structures of some pharmaceuticals and personal care products

undergo environmental transformation under certain conditions (enviro-kinetic).

Monitoring metabolites of pharmaceuticals in the environment is, however, limited by the lack of

reference standards of environment bound pharmaceutical metabolites, resulting in the scanty information on the occurrence levels, behavior, and half-life of conjugates metabolites in the environment. For instance,




Fig. 2 Schematic diagram showing potential sources, pathways, and receptors of pharmaceutical pollution in the environment (adapted with modification from [60])

Kasprzyk-Hordern et al. [29] and Huerta-Fontela et al. [65] reported a concentration range of between 880 and 4026 ng/L for carbamazepine epoxide (a carbamazepine metabolite) in influents wastewater, while the concentration of its parent compounds (carbamazepine) range between <1.5 and 113 ng/L. There is, therefore, a need to understand environmental transformation/metabolism, transformation products (metabolites), and analysis of pharmaceutical metabolites. This action is essential because of the expected time-bound decrease in the environmental concentration of parent compounds, with a corresponding increase in metabolites' level, as well as the potential of the metabolites, eliciting probably greater than parent compound adverse effects in the environment.

Toxicity of pharmaceuticals and personal care products

The benefits of the intended use of pharmaceuticals and many personal care products are enormous. The consumption of drugs evokes specific biological responses in the host, after which 10–90% of excess unused doses and some conjugates metabolites are ultimately excreted and passed into the environment [66, 67]. Their leak and presence in different environmental matrices could cause a risk on non-target organisms, mainly because of their weak degradation, persistence, and biological activities. Organisms within the aquatic and terrestrial environments have the potential to be most affected. Recent reports indicated that drinking water sources, especially those receiving water input from contaminated sources,

contain residues of PPCPs, and thus may need further treatment to remove the pollutants before consumers supply [68].

There has been a growing concern about the environmental impact of pharmaceuticals and personal care products (PPCPs) in the aquatic environment [69] as a result of the fact that they can potentially elicit health and ecological impacts [55]. Furthermore, PPCPs may exist as mixtures with other contaminants in the environment and, therefore, can cause synergistic detrimental effects to both aquatic and terrestrial organisms even at low concentrations [70]. Antibiotics usage is common in animal husbandry for prevention, treatment, and growth purposes, making their over-use result in the genetic selection of more harmful bacteria [71]. Continuous exposure to antibiotics was noted as a probable cause of induced drug resistance in many pathogenic organisms, including bacteria.

Steroid hormones use as sex steroids, contraceptives, and birth control pills can interfere with the endocrine systems, or act as anti-androgenic ligands [72, 73]. Endocrine disruption leading to adverse effects such as sterilization, the imposition of sex organs (imposex), and feminization of some vertebrate, e.g., fish, mollusks, and other aquatic species have been reported [5, 74]. For instance, Solé et al. [75] reported that the presence of the hormone estrogen and progestogens at concentrations as low as approximately 1.0 µg/L caused endocrine-disrupting manifesting in fish feminization and decrease infertility. The accumulation of diclofenac on *rainbow trout* even at a low concentration of 5 µg/L had detrimental endocrine effects. In contrast, exposure to a mixture of acetaminophen, carbamazepine, gemfibrozil, and venlafaxine at concentrations between 0.5 and 10 µg/L was noted to cause effects such as tissue degeneration, a decline in embryo production and increase in embryo mortalities in *zebrafish* [76, 77]. Exposure to endocrine-disrupting contaminants in the aquatic environment was also reported to lead to the modulation of hypothalamus–pituitary–gonad (HPG), hypothalamus–pituitary–thyroid (HPT) and hypothalamus–pituitary–adrenal (HPA), and resulting in the tampering of the activities and functions of various physiological traits in some non-target vertebrate aquatic organisms [78].

Drugs such as carbamazepine, levetiracetam, lamotrigine, and valproate used as antiepilepsy which have been detected in drinking water supply in South Africa was fingered to have the capacity to cause a number of several reproductive endocrine system side-effects in certain fish species as well as in humans [77, 79, 80]. NSAIDs like Naproxen and Ibuprofen that are often not resolved in WWTPs may also induce an adverse effect on the endocrine systems of non-target vertebrate organisms

of WWTPs effluent receiving waters. For example, Japanese Medaka fish (*Oryzias latipes*) exposed to 0.1 µg/L concentration of Ibuprofen manifested delayed hatching while concentration reaching 1 mg/L in humans, can lead to an increase in blood plasma levels.

Remediation, treatment, and removal of PPCPS from contaminated matrices

Extraneous levels of widely distributed potentially toxic PPCPs and EDCs have been reported in many aqueous matrices worldwide. A large percentage of South Africa waters and aquatic ecosystem receives PPCPs contaminants via human excretions and improper discharge of pharmaceuticals into the sewage system [42, 81, 82]. Consequently, many non-target marine organisms have magnified drug residues to a varying extent in different organs of their bodies. PPCPs such as acetaminophen, caffeine, 1,7-dimethylxanthine, dehydronifedipine, tetracycline, oxytetracycline, sulfonamides, macrolides, and ormetoprim have been reported to be found in fruits, vegetables, fish, meat and even milk and dairy products as a result of uptake or exposure to PPCPs contaminated environment [83–85]. Thus, there is a need for the implementation of appropriate and effective environmental remediation to secure the health and safety of biological features, as well as environmental health and safety.

Several water treatment procedures and technologies have been developed and used for resolving contaminants in the environment, especially water and wastewater. The removal can be achieved through several processes, including; physical, biological, and chemical methods. The physical process may involve filtration where contaminants' removal is achieved by transforming one phase to another, leading to the production of highly concentrated sludge that could be toxic and more difficult to dispose of [86]. The biological process in water treatment revolves around aerobic and anaerobic degradation/digestion of nutrients and organics, while the chemical process is based on oxidative decomposition. However, many of these stepwise treatment techniques are insufficient, in that they are not able to remove or even degrade residues of PPCPs due to their deficient environmental concentrations, and because they were not initially factored in their design for such purposes [87]. Daughton and Ternes [44] reported that PPCPs are not entirely removed during wastewater treatment because the WWTPs are only designed to remove suspended solids, pathogens, and nutrients from wastewater using a serial link of processes to eliminate impurities, reduce nutrients and organic load and improve oxygen demand levels.

Petrović et al. [88], in a report, noted that the majority of the existing WWTPs are not designed to either treat or

remove these contaminants and their metabolites. Ineffective treatment of wastewater has been listed as a significant source of PPCPs in many receiving fresh surface water systems and other aquatic environments, especially those freshwater systems used as domestic water sources. There is, therefore, a need for the development of more advanced, efficient, and powerful water and wastewater treatment technologies for the treatment of PPCPs contaminated water, wastewater/effluent from municipal and industrial wastewater discharge streams [89]. This measure is critical and very important in eliminating the potential toxicity and health implication that may arise as a result of exposure of aquatic organisms and possibly humans to these metabolites. The development of facile, cheap, and green methods that can be employed in the treatment of pollutants has been a significant area of research in the field of environmental science and technology. It is important to note that the ability of certain PPCPs to sorb onto bio-solids and siliceous solids, suspended solids confers the need for remediation of contaminated sediment as well as contaminated soil, where they may be ultimately sunk into, or be discharged onto via the application of bio-solids as manure on land.

Water treatment and removal efficiency of PPCPs in WWTPs

Over 80% of PPCPs are released into the environment from the human body in the parent form un-metabolized, i.e., without transformation [90]. These are fed through into the wastewater treatment plants for removal or decomposition during the water treatment process. Many WWTPs are, however, unable to wholly eliminate most PPCPs, hormones and their metabolites, resulting in their presence as residues in wastewaters, surface waters, sediments, and sludge. This inefficiency of WWTPs could be attributed to their conventional integrated treatment uses for biological treatment and microbial decomposition as a process for the breakdown of complex organics, nutrients, and activated sludge for the removal method of contaminants in water/wastewater. Unfortunately, residues of PPCPs, hormones, and their metabolites are not fully removed as the removal efficiency of most WWTPs ranged between 50 and 90% [91, 92]. The removal efficiency of different PPCPs differs greatly, and varies with the physical and chemical properties of the parent compounds as well as the environmental conditions such as the configuration of biological reactors and operational parameters such as hydraulic retention time and sludge retention time [93, 94].

For example, carbamazepine, one of the contaminants that are most often detected in effluents, is known to be resistant to biodegradation, making it nearly impossible for efficient mineralization and removal in conventional

biological treatment [20]. Wu et al. [95] reported that 23% removal efficiency for carbamazepine after treatment of wastewater effluent in the conventional treatment process. The removal efficiency of other PPCPs such as ibuprofen, naproxen, ketoprofen, diclofenac, bezafibrate, sulfamethoxazole, and trimethoprim ranges from 60 to 100% [96–99]. The differences in the removal efficiency may be due to a number of factors, including the characteristic of the activated sludge, the concentration of the contaminants, the optimal operational condition of the WWTPs, and the water composition. Thus, the biological treatment process seems to be economically feasible and widely applicable but not effective in degrading many organic pollutants.

Most WWTPs utilizes various method in the conventional treatment systems for the removal of PPCPs such as coagulation, flocculation, and sedimentation of raw sewage, activated sludge, membrane bioreactor, sequential batch reactor up-flow anaerobic sludge blanket processes [100, 101]. Some treatment methods are, however, more efficient and effective in removing pharmaceuticals compounds of interest, compared to another. This might be as a result of the physicochemical properties, the hydrophobicity, and biodegradability of target pharmaceuticals and process operating parameters in the WWTPs [102]. For instance, Berset et al. [103] reported that using the conventional methods involving dioxychlorination and sand filtration processes, cocaine and benzoylecgonine were poorly removed, while they were removed entirely when ozonation process was used. Non-steroidal anti-inflammatory drug removal in WWTPs are achieved to a different extent. Upon treatment with a mixture of dioxychlorination and sand filtration, diclofenac (over 99%) was almost completely removed; naproxen was moderately removed (48%), while ibuprofen was poorly removed (14%). When ozonation process was used as a treatment process, more than 40% ibuprofen, naproxen, and diclofenac were removed by less than 20%, while dioxychlorination and sand filtration process remove sulfonamides and macrolides efficiently [104]. Thermal destruction of pollutants at high temperatures is also a suggested elimination procedure. However, this technique may lead to undesirable emissions and damage to useful microbes and aquatic life forms, while it is not economically feasible.

Biosorptive method for the removal of PPCPs from contaminated water

Wastewater treatment plants (WWTPs) rely on biodegradation and adsorption methods using conventional adsorbents such as activated sludge for removal of contaminating substances in aqueous matrices, but their use is limited. This limitation is because their removal

efficiency changes significantly, and varies with the physicochemical properties of the compounds as well as the environmental conditions and operational parameters [58, 105]. The biological, chemical, and physical processes have been studied for the removal of PPCPs from contaminated matrices [106]. Among these techniques, biosorptive method is seen as one of the environmentally friendly techniques used in the removal of PPCPs from aqueous solutions. Bioadsorptive immobilization have been reported to show promising results for the removal of some organic contaminants in laboratory pilot-scale experiments while biodegradation was proven to be inefficient for the removal of PPCPs due to poor degradability and low environmental concentration [107, 108].

Biosorptive processes have the advantages of effectiveness, simplicity, low cost, and sustainability [58]. Despite these advantages, the efficiency of bio-adsorption varies depending on the characteristics, polarity, the activity of the sorbent materials, the chemical properties and behaviours of the adsorbate material, thus suggesting incomplete pollutant removal and thereby passing them out in WWTP effluent. The cost of WWTP operation due to high energy requirements and low output is also a limitation [89]. There is also a tendency of the transformation of some non-biodegradable contaminants into toxic contaminants that can exert toxicity to micro-organisms under the treatment conditions [109].

Commercial activated carbon as adsorbents is one of the most widely studied materials for the removal of organic pollutants. Still, its drawback is in the high manufacturing cost and the deficiency of regeneration. Hence the preparation of economical adsorbents from agricultural waste, clay materials, biomass, non-living algae, and seafood-processing waste products, which are cheap, have been employed as biosorptive material for the removal of numerous organic pollutants from different water matrices [110]. Li et al. [111] reported the high removal efficiencies of diclofenac and trimethoprim via the use of agro-waste materials such as biochar, macroalgae, and wood chipping. These biosorptive materials indicated possible high removal at low concentrations, thereby offering a clean, sustainable, and practical water treatment solution for purifying water.

Alkaline-modified biomass employed for the removal of tramadol achieved a 91% removal at pH of 7, biosorbent dose of 0.5 g/L, and 50 mg/L contaminant concentration load of tramadol within 45 min. The removal efficiency of the sorbent was possible because of the hydrophilic interaction between amino and carbonyl groups within the pharmaceuticals moieties, and the hydroxyl and carbonyl functional groups generated on the surface of the modified algal biomass [110]. Moreover, different biosorbents such as graphene oxide and carbon nanotubes have

been used in the removal of various pharmaceuticals and personal care products [112–114]. Solution pH, temperature, interfering substances, ionic strengths of the matrix are among the environmental factors that play an essential role during biosorptive process for the removal of PPCP. However, their inability to be able to remove a large number of pharmaceuticals from wastewater treatment plants efficiently calls for the development of an efficient technology with acceptable cost and effective for mineralization of pharmaceuticals from the wastewater treatment plants.

Chemical oxidation methods for the dissipation and mineralization of PPCPs in water

Chemical oxidation method offers a better technology in that the challenges associated with the use of conventional wastewater treatment plants, which include incomplete degradation of organic pollutants, sludge formation, the formation of secondary pollutants, and high cost, are eliminated. Chemical oxidation generally overcomes the limitations of other treatment processes, although it may not result in the complete mineralization of the organic pollutants [115]. Chemical oxidation, often referred to as an AOP, involves the use of oxidants like ozone, hydrogen peroxide, and chlorine.

Chemical treatment method involving advanced oxidation processes such as ozonation, peroxidation, ultraviolet light aided ozonation (O_3/UV), ultraviolet light aided peroxidation (UV/H_2O_2), Fenton and Fenton-like oxidation, gamma radiolysis, sonolysis as well as electrochemical oxidation process have been reported to be sufficient for the degradation of toxic pollutants in the aqueous matrices [116]. However, the advanced oxidation process methods have been associated with the disadvantage of high energy demand for various critical devices such as ozonizers, UV lamps, and ultrasonicators, and this leads to high operation costs [117].

Basically, advanced oxidation processes rely on in situ generation of highly potent chemical oxidants in the presence of ozone (O_3) or hydrogen peroxide (H_2O_2) and the presence of a catalyst such as the Fenton's reagent or UV light [118]. AOPs uses reactive species such as the hydroxyl radicals $OH\cdot$ generated in sufficient quantity for water purification, in which both organic and inorganic pollutants are removed through O_3 aided oxidation or H_2O_2 supported oxidation, in the presence of catalysts such as TiO_2 , ZnO , BiO_2 , CuO etc., and UV light as an energy source at ambient temperature and pressure [119]. AOPs are classified into two based on photon-driven reactions;

- a. Photochemical processes such as UV oxidation, UV/H_2O_2 , UV/O_3 , $UV/H_2O_2/O_3$, $UV/Ultrasound$, Photo-




Fenton, photocatalysis, sonophotocatalysis, vacuum UV, microwave, and,

- b. Non-photochemical processes such as ozonation, ultrasound, US/H₂O₂, US/O₃, US/Fenton, electrochemical oxidation, supercritical water oxidation, ionization radiation, electron-beam irradiation, wet-air oxidation [120].

AOPs excel overall biological and chemical processes in that they are environmentally friendly as they are known not to transfer pollutants from one phase to the other, as seen during chemical precipitation, adsorption, and volatilization [120]. Moreover, they do not produce a large quantity of poisonous sludge during activated sludge processes as with other treatment methods. Popular advanced oxidation processes used for the removal of contaminants include TiO₂ and photo-fenton processes. Generally, photocatalyzed AOP is environmentally benign, biocompatible, highly stable with low-cost metal oxide photocatalyst (such as TiO₂), and can efficiently be used to remove different organic pollutants from water matrices [121, 122]. The photocatalytic degradation of organic pollutants within the water matrices are very efficient and effective due to the following factors; (i) good operating conditions at ambient temperature and pressure, (ii) complete mineralization of substrate and intermediate into CO₂ and H₂O, (iii) no problem with disposing of solid waste, (iv) utilization of sunlight, near UV-light or visible light for irradiation, (v) formation of non-toxic by-products and (vi) low cost [12, 123].

TiO₂ photocatalysis, however, offers better activity during the removal of organic pollutants because of their heterogeneous nature, hence, the possibility of catalyst reuse and their operation at a wide pH range when compared to photo-fenton process. Although different AOPs method has been employed in the degradation of PPCPs, however, this review intends to emphasize on the catalytic activity of semiconducting photocatalyst doped on solid supports such as activated carbon, carbon nanotubes, and graphene oxides and their application in the degradation of PPCPs. One of such semiconducting photocatalyst is TiO₂, or TiO₂ immobilized on other solid materials used in AOPs processes. Photocatalysis occurs upon the absorption of ultraviolet, visible, or infrared radiation by the photocatalyst in such a way that results in a change in the rate of the chemical reaction. The use of catalysts such as TiO₂ or TiO₂ immobilized on a support material was reported to lead to improved oxidation under solar irradiation, while the radiation also serves as a more sustained and energy-efficient solution for degradation of organic contaminants in the aqueous environment [124, 125].

Photocatalysis can either be a homogenous or heterogeneous photocatalyst. Homogenous photocatalysis occurs when both the photocatalyst and the organic pollutants are soluble and exist in the same phase during the photocatalytic process. An example of homogenous photocatalyzed AOP is the photo-Fenton process, which involves the iron salt catalyzed H₂O₂ reaction in the presence of UV-visible radiation as an energy source used for the generation of hydroxyl radicals as shown in the reaction below [126].



This process is used in the degradation of pharmaceuticals as a result of its simplicity and easy reactor design. Photo-Fenton processes have been applied for the degradation of organics pollutants in different environmental matrices. de Luna et al. [127] reported the degradation of acetaminophen by Fenton oxidation in a fluidized-bed reactor where the effect of operating parameters such as pH, temperature, the concentration of H₂O₂ and Fe²⁺ were monitored for the pseudo-second-order kinetic degradation 99.6% of the organic substrate. The Fenton process has also been proven to be a viable catalyst for photo-degradation of pharmaceuticals such as hydrocortisone, estradiol, and verapamil. The reaction mixture containing ferric ions as catalyst showed 100% degradation of the three pharmaceuticals in less than 1 h, compared to the use of TiO₂ in a heterogeneous photocatalyzed process which shows a more favorable level of mineralization which in turn prevent the danger involved in the accumulation of harmful organic pollutants in the water body [128].

The drawbacks in the use of this process include the use of reagents, strict pH control due to the process's pH dependence, and the formation of sludge. To overcome these challenges, the development of heterogeneous catalysts for the oxidation degradation processes was crucial, due to their potential role in facilitating the degradation and complete mineralization of organic contaminants, especially PPCPs. Current heterogeneous catalyst development studies are directed towards improving the synthesis, and functionality of various sizes and shapes of metal nanoparticles semiconducting photocatalyst, aimed at improving the performance and utilization of nanoparticles in multiple applications, including advanced oxidation processes (AOPs). In general, the use

of ozonolysis and photocatalytic oxidation has proven to be promising as pre-treatment/treatment techniques for the mineralization of organic pollutants when compared with other chemical oxidation processes.

Ozonolysis processes

The ozonolysis process is an advanced oxidation process that is based on the synergistic interaction between an oxidant such as ozone or abundant oxygen. Ozonolysis may be supported by catalyst or radiation or a combination of both resulting in the generation of hydroxyl radicals (HO·), which is a short-lived oxidizing species that reacts with both organic and inorganic pollutants within the water matrices in a non-selective manner [129]. Due to AOPs ability for selective degradation of recalcitrant organic pollutants, they may function as a pretreatment process prior to biological treatment techniques, thus suggesting integrated treatment as a more efficient and effective means for the removal of organic pollutants from highly contaminated wastewater [130, 131].

The preference for the use of ozonolysis in the removal of pollutants is because they do not cause a significant increase in salt concentration. It leaves no presence of chemical residue after usage, as observed with waste activated sludge, where bio-recalcitrant components and low soluble volatile organic compounds, are partially oxidized and solubilized to produce a biodegradable product [132, 133]. However, this method is expensive and requires a high operating cost, thereby making its application for pollutants removal limited. The technique is also associated with the generation of intermediates, which could be challenging to eliminate.

AOP using heterogeneous photocatalysts

This process is made up of purely chemical and physical reaction routes in which the photocatalyst is generated and its activity maintained by the absorption of radiant energy [134]. Heterogeneous photocatalysis occurs when the activity of semiconducting photocatalyst, which in most cases is insoluble in the solution that contains the organic substrates, and dependent on the pH of the solution, is initiated by the absorption of radiant energy. The generated photon with energy band gap level equal to or greater than the band gap energy of the photocatalyst which is the difference between the energy of the valence band full of electrons and that of the conduction band that is empty. Then, mobile electrons can access the conduction band, leaving positive holes in the valence band [131, 135]. Hence the catalyst and the substrates exist in different phases. The heterogeneous nature of the oxidative reaction makes for easy and cheap recovery catalyst from the solution after use.

The conventional semiconducting nanoparticles used in AOPs for the treatment of organic pollutants in water matrices include TiO₂ in homogeneously catalyzed process, while those use as heterogeneous catalysts; ZnO, SnO₂, Al₂O₃, In₂O₃, ZnS, Fe₂O₃, CeO₂, ZrO₂, SiO₂, CuO, MnO₂ and CdS which function as sensitizers for light-induced redox processes. The TiO₂ photocatalytic process leverage via direct photolysis of photon energy from UV and photocatalysis by producing hydroxyl radicals where TiO₂ is photo-activated to generate hydroxyl radicals on the surface of the crystal before reaction with a wide range of organic pollutants which in turn lead to mineralization of the pollutants to CO₂ and H₂O UV radiation [125, 136]. The continuous design and development of various photocatalyst by researchers around the world affirmed that heterogeneous photocatalysis presents the best technological opportunities for the degradation of organic pollutants within the environment.

Nanomaterial as photocatalyst in the degradation of PPCPs in WWTPs

Nanoparticle photocatalytic reactions can be described as the interaction of light energy with a metallic nanoparticle. This process is used in wastewater treatment as a result of their broad and high photocatalytic activities on the decomposition of various organic pollutants [137]. Nano-photocatalysts consist of nano-size order metal oxides, with semiconducting properties and strong ability to degrade large varieties of persistent organic pollutants such as dyes, detergents, pesticides, and volatile organic compound that WWTPs cannot remove [138, 139]. Quite several semiconductors such as ZnO, SrTiO₃, Fe₂O₃, SnO₂, CuO₂, WO₃, and Fe₃O₄ have been used for the decomposition of organic pollutants from different environmental matrices [139–141]. They can also be used for degrading halogenated and non-halogenated organic compounds, PPCPs, and heavy metals in some specific situations [7].

Photocatalyst and photocatalytic method in advance oxidation procedures

The photocatalytic method is a promising technology used in the treatment of contaminants as a result of the ability of the catalyst to use sunlight as the energy source to initiate and facilitate the degradation of organic pollutants [142]. However, some of the challenges encountered with the use of photosensitive semiconductors as catalysts are low quantum efficiency, rapid recombination of photogenerated carriers, narrow optical response, and a slow transfer rate of electrons to oxygen which hinder their applications in the treatment of organic pollutants [143]. These limitations could be eliminated by employing strategies such as the modification of the textural

properties, heterojunction construction, elemental doping, and morphology control to improve their photocatalytic performance [141].

The modification of photocatalysts that are highly active via visible light enhances the central part of the solar spectrum to be used. Therefore, to exploit the visible light during the photocatalytic process, there is a need for the usage of narrow band gap semiconductors like Cu_2O , WO_3 , CdS , BiVO_4 etc., for the degradation of different organic pollutants. Cheng et al. [144] reported the photocatalytic activity of Cu_2O - Cu composites irradiated under visible light at 420 nm for the degradation of methylene blue, where 52% removal was achieved after 60 min. The intensity degraded after irradiation at 664 nm as observed by the disappearance of its peak after 60 min. Li et al. [145] synthesized Z-scheme heterostructure nanocomposites by loading mesoporous $\gamma\text{-Fe}_2\text{O}_3$ nanosphere on $g\text{-C}_3\text{N}_4$ nanosheet, the synthesized Z-scheme $\gamma\text{-Fe}_2\text{O}_3/g\text{-C}_3\text{N}_4$ heterostructure exhibits mesoporous features with the improved specific surface area providing reactive mass sites for tetracycline; also the constructed heterostructure which existed between $\gamma\text{-Fe}_2\text{O}_3$ and $g\text{-C}_3\text{N}_4$ efficiently extends the response range which leads to the quick transfer and separation of photoinduced charge carrier which enhances its photocatalytic activity for mineralization of tetracycline hydrochloride under visible light irradiation.

The working mechanisms behind the photo-catalyzed advanced oxidation process are based on the photoexcitation of electron in the catalyst. For instance, if photocatalyst, such as TiO_2 , is irradiated with UV light, it causes a generation of holes (h^+) and exits electron (e^-) in the conduction band. In aqueous media, there is an entrapment of water molecules (H_2O) onto the holes (h^+), leading to the generation of hydroxyl radicals ($\cdot\text{OH}$). These hydroxyl radicals are indiscriminate, highly reactive, non-selective, and powerful oxidizing agents, which in turn, oxidize organic pollutants into water and gaseous degradation products [137].

TiO_2 photodegradation process

TiO_2 stands out as an excellent photocatalyst amongst the semiconductors that can be used for the degradation of PPCPs, due to its optical and electronic features, photosensitivity, physical and chemical stability, cost-effectiveness, resistance to light corrosion, non-toxicity and their high accessibility [146, 147]. Polymorphs of TiO_2 include anatase, rutile, and brookite [148], of which anatase TiO_2 have been shown to exhibit the highest photocatalytic activity as a result of the extended lifetime of the photoexcited electrons, and the fast migration of photogenerated electrons [149].

Literature reports indicated that the photocatalytic degradation of PPCPs using TiO_2 as catalysts could result in mineralization reaching close to 99% within 1 to 3 h under various parameters. For example, the photocatalytic degradation of ofloxacin and atenolol irradiated under a UV lamp was almost complete after 240 min [60, 150]. Furthermore, photocatalytic mineralization of tetracyclines, paracetamol, caffeine, and atenolol as single/lone pollutants and in mixtures was achieved via TiO_2 irradiated under UV and simulated solar irradiation, where the removal of tetracyclines reaches 90% after 35 min and that of paracetamol, caffeine, and atenolol were between 80 and 90% after 6 h, while the degradation of the mixture of these pharmaceuticals was achieved at 60% after 6 h under the same conditions [151]. He et al. [152] reported that 100%, 100%, 76%, and 74% photocatalytic degradation of propranolol, diclofenac, carbamazepine, and ibuprofen, respectively, was achieved after 96 h via the immobilization of TiO_2 on the sand. The degradations were made possible as a result of the photo-oxidation of substrates from the single oxygen generated in the reaction mixture [153].

Considerable removal performance can be achieved in the presence of simulated solar light. Irradiated TiO_2 was also applied for the mineralization of organic molecules such as acetylene in the gas phase. Acetylene mineralization/degradation in the gas phase follows a first-order kinetic in which no organic intermediate was detectable, suggesting that no pollutants or any intermediate species interfere in the photocatalytic mineralization [154]. However, the usage of TiO_2 as a photocatalyst has critical limitations such as its wide intrinsic band gap that is 3.0 eV and 3.3 eV for rutile and anatase, respectively, and this results in achieving an activation at ultraviolet radiation at $\lambda < 380$ nm. This wide band gap can be reduced via doping of TiO_2 , in order to cause a shift in absorption in the visible light region of $\lambda > 400$ nm [116, 155]. Another challenge of TiO_2 as a conventional powdered catalyst for photodegradation is the difficulty of their separation from the slurry of the reactor systems after photocatalysis, and this leads to low efficiency in photocatalytic activities over a range of application [125, 156].

Due to surface limitations and inadequate adsorption capacity of TiO_2 resulting from non-porous nature, current studies are directed towards incorporating photocatalysts on porous supports in order to facilitate the efficient absorption of target environmental pollutants prior to subsequent oxidation aided by the photocatalyst. To achieve a more rapid and efficient removal of PPCPs in WWTPs, there is a need to modify the photocatalytic process through immobilization of TiO_2 onto a suitable solid support such as activated carbon, molecular sieve, graphene, and minerals as a result of their ability to

enrich the pollutants and improves their photocatalytic degradation rate due to its stability, mechanical resistance, high surface area and appropriate porosity [157, 158].

ZnO photodegradation process

ZnO, with strong oxidation ability and a tremendous photocatalytic property, has also been used in the degradation of various organic pollutants due to its direct and broad band-gap energy close to UV spectral region, hence their thermal stability and considerable free-excitation binding energy. It is also relatively cheap when compared to TiO₂, which is said to be non-economical for the treatment of water on a large scale [159, 160]. ZnO nanoparticles have been reported to be more catalytically active compared to TiO₂ for degradation of pharmaceuticals, where the photocatalytic degradation of 14 pharmaceuticals was studied using ZnO and TiO₂ nanoparticles [161]. Study results showed that 95% removal was achieved after 40 min under UVA irradiation via ZnO nanoparticles catalyzed process, whereas only 40% removal was achieved for TiO₂ catalyzed process under the same condition. The photocatalytic activities of different types of ZnO were studied for the degradation of methylene blue, where the reaction was monitored at pH 7.5 for 60 min under UV irradiation of 664 nm. ZnO nanofibers were noted to be the best among the fabricated ZnO, as photo-degradation reaches almost 100% for methylene blue removal [160]. The photocatalytic efficiency of ZnO/g-C₃N₄ composites was investigated by Ismael [162] for the degradation of methyl orange and 4-chlorophenol under visible light radiation. Its photocatalytic performance was due to the synergistic effects between ZnO and g-C₃N₄, resulting in the interfacial transfer of photogenerated electrons and holes hence its effective charge separation resulting in their ability to be able to degrade methyl orange and 4-chlorophenol.

WO₃ photodegradation process

Another semiconductor which has been used in the photocatalytic degradation of organic pollutants is WO₃. WO₃ is an n-type semiconductor with high stability and a wide tunable band gap of around 2.6 eV, hence their application in the photocatalytic degradation of various organic pollutants. For instance, complete degradation of rhodamine B was achieved when WO₃ nanoplatelet was employed, with the intensity peak of Rhb disappearing after 350 min, when the catalyst reacted with the organic pollutants to form an unstable intermediate under UV light irradiated at 554 nm [163]. Chen et al. [164] reported the fabrication of WO₃/g-C₃N₄ nanocomposites by a simple direct precipitation method, and the Z-scheme photocatalyst WO₃/g-C₃N₄ was

designed and prepared by dispersing WO₃ nanosheets on g-C₃N₄ nanosheets. The as-prepared WO₃/g-C₃N₄ showed enhanced photocatalytic activity toward degrading methyl orange. The improved photocatalytic performance of WO₃ nanosheet doped on g-C₃N₄ was due to the coupling of effect of g-C₃N₄ on WO₃ resulting in a slight shifts to lower binding energy, which hints the strong interaction between WO₃ and g-C₃N₄.

Ag/AgCl/AC photodegradation process

Photocatalytic degradation involving tetracyclines reaches 97.3% in 60 min under visible light radiation through the use of Ag/AgCl/AC composites. The reactive species that aided the degradation are electron holes and superoxide radicals, while the exposed activated carbon surface in the composites photocatalyst enhances the tetracyclines adsorption onto its surface, thereby increasing the contact sites between tetracycline and photocatalyst which lead to a better and efficient photodegradation rate [165].

Carbon-solid supports in photocatalytic degradation

The photocatalytic performance of various photocatalysts has been mostly enhanced for the degradation of organic pollutants by combining them with carbonaceous materials. These carbonaceous materials, when compared to single semiconductors, give additional advantages such as chemical stability, thermal stability, high surface area, pore structure, good conductivity, excellent electronic properties, better photocatalytic activity, activity under solar irradiation and easy separation [106]. Activated carbon (AC), carbon nanotubes CNTs) and graphene are among the best solid materials for use as catalyst support for photocatalytic purposes, especially those use for the degradation of PPCPs in water and wastewater, due to properties such as; large specific surface areas and high charge carrier mobility [166, 167]. Activated carbon is porous and amorphous solid carbon material that can be derived from coal or plants through carbonization at a temperature between 400 and 600 °C, with an activation process by use of steam or CO₂ [168]. Activated carbon is non-photocatalytic in nature but can serve as a means to enhance the photocatalytic reaction between catalyst, e.g., TiO₂ and the organic contaminants, by adsorption of pollutants on its surface to facilitate the degradation of organic contaminants [169].

The use of carbonaceous material in the degradation of PPCPs has been studied several times, and it has been proven that they can only adsorb pollutants, but cannot transform them, thus leading to the generation of hazardous products. In a situation where the adsorbents were not regenerated on-site, such adsorbents become

hazardous waste and must be disposed of carefully, coming with additional cost. The use of carbonaceous material can, therefore, be expensive [7]. The affinity of solid materials for PPCPs results from the presence of functional groups such as carboxyl, carbonyl, phenol, lactone and quinone, which confers on them surface-active species and specific surface areas that attract solid materials and concentrating them close to the semiconducting active site for improved photodegradation [170]. This makes the composites serve as effective adsorbent material due to one or more combinations of either hydrophobic interaction, π - π interaction, hydrogen bonding interactions, and electrostatic and dispersion interaction [171]. The clogging of the pore on adsorbent material is also a common challenge.

Activated carbon (AC) for photocatalytic degradation

Carbonaceous materials like activated carbon function as electron scavenger because of their enormous electron storage ability, which is known as Hoffman mechanism property [172]. They also act as a sensitizer-providing electron for semiconductor photocatalyst such as TiO_2 , $g\text{-C}_3\text{N}_4$, etc. The electrons are excited by photons of light energy, which produces the superoxide radicals from absorbed molecular oxygen. Moreover, the positively charged composite material attracts electron from semiconducting metal catalysts such as TiO_2 , to create a hole (h^+) which interact with adsorbed water to generate hydroxyl radicals, in the TiO_2 valence band. The presence of carbon-oxygen-titanium linkages within the composite materials leads to a reduction in the band gap and extends the absorption band into the lower energy visible range [116]. Moreover, the interest in the use of activated carbon as solid support for various photocatalyst semiconductor is as a result of its developed pore structures, very large surface area and high adsorption capacity, hence their usage as an adsorbent for both organic and inorganic pollutants [173].

Activated carbon in the TiO_2 immobilized on activated carbon photocatalyst, serves as a reaction medium through which organic molecules are absorbed before degradation [174]. The complete removal of pharmaceuticals such as amoxicillin, ampicillin, acetaminophen, and diclofenac was achieved using AC- TiO_2 composite material under sunlight irradiation for 180 min, and this cannot be achieved with bare TiO_2 [173]. This is a result of the transfer of sorbate from activated carbon to photoactive TiO_2 due to the presence of a common interface between them [167]. Another solid support that has been of great use owing to its high surface area, chemical and thermal stability is zeolite [175]. Their immobilization on TiO_2 has proven to be efficient in the removal of highly volatile organic contaminants due to their adsorptive

nature, and this can easily be supplied onto the TiO_2 photocatalyst surface [176]. Bare TiO_2 samples can rapidly deteriorate, while TiO_2 composites can maintain a high adsorption efficiency to remove organic contaminants over a long period [177].

Preparation of activated carbon and the fabrication of doped activated carbon

Khraisheh et al. [178] reported the preparation of activated carbon from coconut shell material, which is an inexpensive source of carbon. AC prepared from many other biomass materials including, plant remains, animal remains, agricultural wastes, decomposing materials, etc., have been reported [179–181]. Carbon sources for the preparation of activated carbon vary from chemical to biological/natural sources, while the method of preparation depends on the nature and characteristics of the carbon source. However, production using biological/natural material sources are relatively cheaper than chemical raw materials because the organic/natural sources are often waste materials, hence the need for the use of plant material as a source for activated carbon.

This technique is followed by the immobilization/doping of activated carbon with a metal oxide or nano metal oxides to form a composite catalyst. Different physical and chemical characteristics and attributes are achieved depending on how and which method is used for activated carbon preparation and how the metal oxide is doped/immobilized on the ACs. Arana et al. [182] reported that the reaction of TiO_2 with activated carbon at different proportions showed that activated carbon not only increase the surface area but there is a modification of the acid-base properties and the UV spectrum of TiO_2 . The following methods have been used in the preparation of AC as a carbon source for photocatalytic degradation of organic pollutants: sol-gel, chemical vapor deposition, impregnation, pyrolysis, precipitation, hydrothermal preparation, microwave-assisted synthesis and sonochemical treatment [183–185].

The mostly used among the above method is the sol-gel method because there is an ultimate mixing or chemical interaction between activated carbon and the corresponding semiconductor photocatalyst. Studies proved that doped/immobilized metal oxides composite material possess superior quality and has the highest removal efficiency under UVC intensity. In TiO_2 composite material, for example, the composite solid support doped with TiO_2 showed higher photocatalytic activity, adsorption capacity, electron scavenging, and sensitization ability and extended visible light adsorption when compared to bare TiO_2 [186]. The photocatalytic activity of prepared nanocomposite ZnO/AC where the activated carbon was prepared from biomass degrades more than

95% organic pollutants as a result of the addition of electrolyte, although this decreases the photoactivity of the catalyst [187].

Carbon nanotubes doped composites in photodegradation

Carbon nanotubes are made up of cylindrical graphene sheets and can be classified either as single-walled carbon nanotubes (SWCNTs) and multi-walled carbon nanotubes (MWCNTs) [13]. CNTs possess a high specific surface area to mass ratio ranging between 75 and 1020 m²/g coupled with an exceptional sorption capacity [11, 188, 189]. They exhibited hydrophobic interactions, van der Waals forces, and π - π stacking, leading to the formation of four different types of adsorption sites such as inner cavities, interstitial channels, external grooves, and outermost surfaces [190], making them a suitable solid material for photocatalytic degradation of PPCPs. CNTs have interesting properties such as large electron storage capacity, superior metallic conductivity, and light adsorption at a broad range wavelength, thereby making them a suitable solid material in the enhancement of the photocatalytic activity of TiO₂ [172]. As monitored on high-performance liquid chromatography, the photocatalytic degradation of oxytetracyclines reaches 88.7% within 60 min when MWCNT/BiVO₄ composites were utilized. The photocatalytic enhancement was made possible as a result of the synergistic effect that occurs between MWCNTs and BiVO₄, which increased the separation rate of photogenerated electron-hole pairs [191].

The usage of CNTs-TiO₂ for the photocatalytic degradation of caffeine was as a result of good contact between CNTs and TiO₂, thereby causing a better enhancement in their photocatalytic activity [6]. CNTs-TiO₂-N has shown to exhibit a high photocatalytic activity under visible light irradiation for the degradation of ibuprofen [192]. This feature can be attributed to the fact that CNTs can function as electron scavengers resulting in a good binding between CNTs, TiO₂, and N used. Modification of CNTs on g-C₃N₄/BiVO₄ was evaluated for the degradation of phenol in the presence of solar light irradiation. The synergistic interaction between the heterostructure was aided by H₂O₂ as the oxidizing agents for 80.6% removal of phenol after 2 h, where the BiVO₄ helps to promote a better optical absorption ability over the well-contacted structure within the heterojunction while the presence of CNTs in the heterostructure enhances a higher photocatalytic performance as a result of its ability as an electron bridge mediator which is responsible in facilitating the photogenerated charge carrier separation [193, 194].

The methods that are employed during its preparation are as follows; hydrothermal, hydrolysis, restrained hydrolysis, simple evaporation and drying, sol-gel,

surfactant wrapping sol-gel, chemical vapour deposition, physical vapour deposition, electrophoretic deposition, electrostatic attraction, solvothermal and impregnation [183, 192].

Graphene-based nanocomposites in photocatalysis

Graphene is made up of a two-dimensional sheet of carbon atoms that are connected by an sp² bond consisting of an aromatic π electron system [195]. Graphene possesses the following properties; high electron mobility, high mechanical strength, high thermal stability, and high specific surface area [196]. These unique properties made graphene have a higher density of potential adsorption sites, which are; open-up surface, a longitudinally-parallel external surface, and interstitial channels [197]. The relevance of graphene includes applications such as in sensors, energy conversion and storage, polymer composite, drug delivery systems, and environmental remediations [198–200]. There are different type of graphene that is available, which are; graphene oxide, reduced graphene oxide, fullerene, carbon nano-onion, and carbon nanotubes [201].

Graphene oxide (GO) and reduced graphene oxide (rGO) are the most commonly used graphene because they show a high efficiency during water treatment. These abilities to adsorb pollutants are due to the presence of several surface functional groups like hydroxyl, carboxyl, and epoxy that function as adsorption sites that aid the removal of contaminants from the water system [202, 203]. Graphene oxide (GO) is prepared via chemical functionalization of graphene through the following method; Brodie [204], Staudenmaier, Hoffman, and Hummer methods [205]. Graphene oxide (GO) is photocatalytically active and can function as an electric insulator as a result of the chemical disruption of the π network. Their electrical conductivity can be restored during the conversion of graphene oxide to reduced graphene oxide [206]. Reduced graphene oxide can be prepared using the chemical treatment [207], thermal mediation [208], and electrochemical treatment [209]. Both graphene oxide and reduced graphene oxide can be used for the photocatalytic degradation of PPCPs. GO-TiO₂ can be prepared via the following method; solution mixing, sol-gel, hydrothermal, electrostatic self-assembly, molecular grafting, chemical exfoliation, liquid phase deposition, and electrospinning [95, 210, 211].

The choice of the method to use will be based on which of them shows a stronger interaction between graphene and the corresponding semiconductor photocatalyst, which in turn will enhance their photocatalytic activity. The degradation of Rhodamine reached 97.2% when rGO/g-C₃N₄ composite was employed. The efficiency of the composites was as a result of the synergistic effect of

rGO/g-C₃N₄ heterostructure formed in the formation of coupled heterointerface and heterojunctions which efficiently and effectively aid in the transfer of photogenerated electron–holes pairs under the influence of visible light where photo-induced electrons can freely migrate along with the conductive network of rGO thereby preventing the recombination of the photogenerated carriers [212]. There is a presence of strong electronic and physical coupling when TiO₂ nanosheet-graphene of 2D–2D composite interact, causing an enhancement of electron transfer between them, thus making the photocatalyst superior when used in the removal of 2,4-dichlorophenol as compared to TiO₂. This is because of the availability of rich oxygen functional groups on the 2D surface of rGO, which enhances the ability of rGO to interact with other organic/inorganic compounds to form hybrid composites [213].

Shanavas et al. [213] reported that the advantage in the use of 2D/3D/2D heterojunction in the photocatalytic degradation of pharmaceuticals such as tetracyclines and ciprofloxacin is the reduction of photoexcited charge carrier migration distance for effective suppression of electron–holes pairs recombination, therefore, creating numerous high-speed photo-induced charge transfer nanochannels in rGO/Fe₂O₃/g-C₃N₄ nanocomposite by degrading tetracyclines and ciprofloxacin under visible light irradiation. Also, porous 3D rGO–TiO₂ aerogel has been reported to remove over 99% of carbamazepine. This was made possible because the macro-porous 3D structure of the aerogel has abundant surface sites, effective charge separation causing an improvement in the mass transportation of the contaminants, thereby leading to easy separation of the catalyst after degrading the contaminants [214].

The excellent outcome experienced during the degradation of carbamazepine, ibuprofen, and sulfamethoxazole, which is up to 80% during removal and high durability in 45 h operation, is as a result of the immobilization of rGO on TiO₂ on optical fibers [215]. However, since the photocatalytic activity of solid material immobilized on TiO₂ has proved to be efficient in the degradation of PPCPs, there is, therefore, a need to develop a standard method with a pilot-scale experiment to ascertain the cost on a large scale use. Due to the photocatalytic activity of graphene–TiO₂ composite, hence their usage in the degradation of PPCPs but their drawback in water treatment arises from the difficulty in separating and recovery of the catalyst after use.

Catalyst preparation methods

The preparation of different photocatalysts can be achieved through various chemical processes. The synthesis methods are usually tailored to suit the size and

morphology of the intended materials. Some simple synthetic techniques that have been used for the synthesis of functional photocatalyst materials are stated below.

Coprecipitation

The coprecipitation method is a very facile and convenient method used in the synthesis of various photocatalysts. This method involves the dissolution of the salt precursor of interest into an aqueous solution followed by precipitation by addition of a base such as NaOH, KOH. This procedure is usually followed by washing and drying, then calcination of the precipitate at a desirable temperature to obtain the intended products [216]. The particle size, morphology, and composition of the synthesized photocatalyst prepared through this method can be controlled by adjusting different experimental parameters, such as the starting material, their ratio, the surface ligand, the reaction temperature with time, and the pH. Moreover, the size distribution of the as-prepared photocatalyst can be improved by the addition of ligands, such as surfactants, inorganic molecules, and polymers into the reaction medium, however, size control is generally poor for this method [217].

Hydrothermal/solvothermal method

This method involves the chemical reaction where the precursors are dissolved in a solvent such as water, organic solvents, or KOH. The aqueous mixture will then be subjected to heat at a high temperature around 200 °C in a sealed stainless steel autoclave. Consequently, the pressure within the reaction autoclave is drastically increased above atmospheric pressure resulting in the generation of high crystalline materials without the need for further treatments [218]. The drawback of this method is its low yield of products when compared with the coprecipitation method.

Thermal decomposition method

Thermal decomposition is an innovative method to synthesize stable nanoparticles. This method involves the thermolysis of organometallic complex precursors in high-boiling-point organic solvents in the presence of surfactants to synthesize nanoparticles of various materials. It is faster, clearer, and economical when compared with other methods [219]. It is also one of the easiest and the most convenient method used to synthesize mono-dispersed metal nanoparticles. Furthermore, it answers the greatest challenge of obtaining a controlled nanometric size and shape in nanotechnology research, which is achieved by controlling the concentrations of the precursors and surfactants; the solvent; and the experimental parameters such as heating rate, heating temperature, and heating time are usually regulated [217]. However,

photocatalyst prepared by this method is usually coated with hydrophobic ligands, thereby making it insoluble in water. Therefore, a further surface modification step is required to render these nanoparticles water-soluble for efficient photocatalytic applications.

Sol–gel method

The sol–gel method for the synthesis of nanomaterials is a convenient and versatile reaction technique in the synthesis of numerous functional photocatalyst. The sol–gel process is based on hydrolysis and polycondensation reaction involving the addition of a complexing agent such as; a polymer, citric acid, or other suitable organic entities into a solution of a colloidal dispersion of the metal ions of the target material. These complexing agents function as cross-linkers between the ionic substances in solution followed by gradual removal of the solvent molecules from the mixture to form a thick gel. The gel is then dried and pre-calcined to obtain the as-prepared powder. The as-prepared powders are then annealed at higher temperatures to obtain the finished product. Metal oxides can also be used as starting materials in this method [220, 221].

Several parameters, such as type of precursor, type of solvent, water content, pH, the concentration of precursor and temperature, can influence the structure of the initial gel, which in turn influenced the properties of the resulting materials, including the crystal structure, particle size, shape and crystallinity [222, 223]. The sol–gel method possesses many advantages. For instance, it allows tailoring of both the bulk properties, including phase composition and surface characteristics such as the surface area, the total pore volume distribution, etc., of a material on a nanometer scale from the earliest stages of processing. The main drawbacks are in the possible high cost for the majority of alkoxide precursors, and processing steps are long.

The use of graphitic carbon nitride ($g\text{-C}_3\text{N}_4$) as an efficient catalyst for the degradation of pharmaceuticals

The large band gap energy of semiconductor photocatalysts such as TiO_2 (3.2 eV), ZnO_2 (3.37 eV), constitute a significant limitation to their photocatalytic usage under visible light spectrum due to its low utilization of solar energy. This limitation makes this method an expensive means for the photocatalytic process; hence the urgent need to research more on visible light semiconductor photocatalyst. $g\text{-C}_3\text{N}_4$ has emerged one of the next generation photocatalysts due to its cheap synthesis, fascinating electronic band structure, non-toxic, graphene-like two-dimensional structure coupled with good visible light adsorption ability and chemical stability for


removal of hazardous pollutants from the environment and clean energy production [224, 225]. They are made up of two main units to establish their allotropic nature which are; tri-s-triazine/heptazine (C_6N_7) and s-triazine (C_3N_3) rings (Fig. 3); where the tri-s-triazine based $g\text{-C}_3\text{N}_4$ is highly favoured and the most stable phase of $g\text{-C}_3\text{N}_4$ thermodynamically [226].

Since the discovery of $g\text{-C}_3\text{N}_4$ by Wang et al. [225] as a promising visible light photocatalyst for the evolution of H_2 , much effort has been directed towards its synthesis. $g\text{-C}_3\text{N}_4$ can be prepared by thermal polymerization using the following precursors based on different reaction conditions and differences in the material degrees of condensation; cyanamide, dicyandiamide, melamine, urea, thiourea and ammonium thiocyanate [227–229]. $g\text{-C}_3\text{N}_4$ has a low energy band gap between 2.7 and 2.8 eV as a result of the presence of sp^2 -hybridized carbon and nitrogen forming the π -conjugated electronic structure, possess excellent chemical stability, does not dissolve in acid, alkali or organic solvents making it to be environmentally friendly material [229, 230].

However, their application in environmental remediations are limited by several obstacles such as low specific surface area, the high recombination rate of charge carrier and low electrical conductivity, hence the need to develop a modified $g\text{-C}_3\text{N}_4$ -based heterojunction photocatalyst with improved physicochemical properties that can be applied in the degradation of organic pollutants in the environment [231, 232]. The modification can be achieved through exfoliation of bulk $g\text{-C}_3\text{N}_4$ into nanosheet, nanotubes and quantum dots, deposition of noble metal, doping with metal, coupling with other semiconductors such as TiO_2 , ZnO , Ag_2O , MoS_2 , incorporating with carbonaceous materials like; activated carbon, graphene oxides, reduced graphene oxide, carbon nanotubes, and many others to form nanocomposites [233–235].

Modification of $g\text{-C}_3\text{N}_4$

To overcome the drawback in $g\text{-C}_3\text{N}_4$ associated with their photocatalytic application, specific surface area, charge separation, and opticals for $g\text{-C}_3\text{N}_4$ have been improved. Numerous heterostructure based $g\text{-C}_3\text{N}_4$ photocatalyst has been prepared by many researchers with improved suitable band structures, shaped at the interfaces between $g\text{-C}_3\text{N}_4$ and metal particles, inorganic semiconductors or carbonaceous materials have shown to enhance their charge carrier separation leading to its improvement in their photodegradation activity [236–238]. Hence, the interest in the synthesis of heterostructure based $g\text{-C}_3\text{N}_4$ with suitable band position resulting in the suppression of the recombination rate of the photogenerated electron–hole pairs for improved



photocatalytic degradation of hazardous contaminants from the environments.

Fabrication of $g\text{-C}_3\text{N}_4$ based semiconductor photocatalyst is considered as one of the effective and more feasible strategies to enhance the photocatalytic activity of $g\text{-C}_3\text{N}_4$ where the formation of a heterojunction system improve the photo-generated electron-hole pairs

separation leading to the improvement in their photocatalytic activity as seen in the following $g\text{-C}_3\text{N}_4$ based photocatalyst $g\text{-C}_3\text{N}_4/\text{TiO}_2$, $g\text{-C}_3\text{N}_4/\text{WO}_3$, $g\text{-C}_3\text{N}_4/\text{CdS}$, $g\text{-C}_3\text{N}_4/\text{Cu}_2\text{O}$, $g\text{-C}_3\text{N}_4/\text{CdS}/\text{Cu}_2\text{O}$ for the degradation of numerous organic pollutants in the environment [239–241].

Chen et al. [242] synthesized a series of visible-light-driven $\text{MgIn}_2\text{S}_4/\text{g-C}_3\text{N}_4$ heterostructures for the degradation of 4-nitroaniline and methyl orange. The improvement in the photocatalytic activity of $\text{MgIn}_2\text{S}_4/\text{g-C}_3\text{N}_4$ can be attributed to the faster charge separation and transport that existed between the interfaces and band structures of MgIn_2S_4 nanoplates and $\text{g-C}_3\text{N}_4$ nanosheets making it an efficient visible-light-driven composite for the degradation of hazardous pollutants. The photocatalytic performance of Z-scheme $\text{g-C}_3\text{N}_4/\text{CdS}$ composites for the degradation of erythromycin and tetracycline was remarkably enhanced as compared to that of pure $\text{g-C}_3\text{N}_4$ and CdS owing to the perfect matching of the band gap, the interface of the close photocatalyst was lower than that of CdS which give rise to the formation of heterojunction with $\text{g-C}_3\text{N}_4$ which suppresses the photo corrosion of CdS [243].

Table 2 below shows how different heterostructure composites have been used for the degradation of various organic pollutants.

Mechanism of $\text{g-C}_3\text{N}_4$ photocatalyst

The absorption of photon energy by $\text{g-C}_3\text{N}_4$ photocatalyst, which is either equal or greater than the band energy of $\text{g-C}_3\text{N}_4$ leads to the generation of electrons (e^-) in the valence band (VB) to be excited before migrating to the conduction band (CB). The generated electron will be excited and leave the photo-generated holes (h^+) in the valence band. Both the photoexcited electron (e^-) and photogenerated holes (h^+) will be trapped at the surface of the catalyst where the h^+ react with absorbed H_2O to produce $\cdot\text{OH}$ radicals while e^- react with absorbed O_2 to produce $\cdot\text{O}_2^-$ radicals before reacting with organic pollutants and finally degrade them [254, 255]. The mechanism is summarized below;








Table 2 Different synthesized heterostructure composites for the degradation of various organic pollutants

Photocatalyst	Synthesis method	Pollutants	Removal efficiency (%)	Time	Light source	References
$\text{g-C}_3\text{N}_4$	Polycondensation	Ibuprofen	20	4 h	35 W Xenon lamp	[244]
		Aspirin	30			
		Ciprofloxacin	60			
		Tetracycline	86			
$\text{BaTiO}_3/\text{TiO}_2$	One-step calcination	Acetaminophen	95	4 h	500 W Xenon lamp	[245]
$\text{ZnO/g-C}_3\text{N}_4$	Thermal condensation	Tetracycline	78.4	50 min	300 W Xenon lamp	[246]
		Oxytetracycline	63.5			
$\text{Ag/g-C}_3\text{N}_4$	Photo-reduction	Sulfamethazole	99.5	60 min	300 W Xenon lamp	[247]
$\text{g-C}_3\text{N}_4/\text{TiO}_2/\text{Fe}_3\text{O}_4/\text{SiO}_2$	Sol-gel	Ibuprofen	92	3 h	330 Wm^{-2} compact fluorescent lamps	[248]
$\text{g-C}_3\text{N}_4/\text{MoS}_2$	Hydrothermal	Levofloxacin	75.81	140 min	Ultrasonic wave at 30 kHz	[234]
		Methylene Blue	98.43	14 min		
$\text{Ag}_3\text{PO}_4/\text{GO/g-C}_3\text{N}_4$	Chemical precipitation	Rhodamine B	94.8	50 min	150 W Xenon lamp	[249]
$\text{BiVO}_4/\text{TiO}_2/\text{RGO}$	Hydrothermal	Tetracycline	96.2	60 min	1000 W Xenon lamp	[250]
		Oxytetracycline	97.5			
		Chlortetracycline	98.7			
		Doxycycline	99.6			
$\text{Ag}_2\text{O/CeO}_2$	Thermal deposition	Enrofloxacin	87.11	120	300 W Xenon lamp	[251]
$\text{g-C}_3\text{N}_4/\text{CNT/BiVO}_4$	Wet impregnation	Phenol	80.6	120 min	Sunlight (illumination intensity; 500 W halogen lamp)	[192]
$\text{g-C}_3\text{N}_4/\text{AgBr/rGO}$	Hydrothermal reaction	Tetracycline	78.4	90 min	250 W Xenon lamp	[252]
		2,4-Dichlorophenol	68.2	6 h		
$\text{rGO/WS}_2/\text{Mg-doped ZnO}$	Electrostatic self-assembly and coprecipitation	Rhodamine B	95	14 min	UV lamp	[253]
			90	90 min	Solar light	



However, in the photocatalytic process for the degradation of organic pollutants, it is crucial to understand the transformation of the different intermediates involved in photocatalysis as it will provide information about the toxicity of the intermediates as well as risk assessment. A schematic representation of photocatalysis mechanism is shown in Fig. 4.

Although many works have been done in fabricating a $g\text{-C}_3\text{N}_4$ based photocatalyst for environmental remediation, however, much effort needs to be directed towards the construction of $g\text{-C}_3\text{N}_4$ -based heterostructure photocatalyst. This act would improve the separation of photogenerated electrons and inhibit the electron-hole pair recombination with an excellent possibility for an efficient and effective photocatalytic activity for the degradation of pharmaceuticals under visible light irradiation.

Conclusion

In conclusion, this review highlighted a detailed overview of the detection of organic pollutants such as pharmaceuticals and personal care products, endocrine-disrupting chemicals, organic dyes, and various industrial waste in environmental matrices. Additionally, it was revealed that most researches focus on the occurrence of the parent pharmaceutical compound while the transformation products which may even be more toxic than the parent drugs are ignored, hence more focus is needed on how the chronic exposure to these contaminants affect humans and other ecosystems, particularly the non-target organisms. The environmental impacts of these emerging contaminants led to the need for the development of a technology for its removal from the environment. This problem of pharmaceutical contamination of the environment could be attributed to the inability of the wastewater treatment plants to completely remove the contaminants, making them one of the common

sources through which these pharmaceuticals get into the environment. Even though various methods such as activated sludge, wetlands, adsorption, membrane processes have been developed for the removal of these pollutants, unfortunately, many research reports have proven that these methods are ineffective in removing these contaminants. Hence, the advanced oxidation process using a photocatalytic method becomes relevant. In this method, various semiconducting photocatalyst can be immobilized on carbonaceous materials, metal oxides, or another semiconductor as the best alternative for the degradation and mineralization of these organic pollutants into harmless products and at the same time, the catalyst can still be recovered and recycled.

Moreover, it should be noted that from the various reports reviewed, photocatalyst materials emerged as an efficient and effective technology for the degradation of various organic pollutants ranging from pharmaceutical and personal care products to different dyes. Furthermore, the engineering of metal-free carbon-based photocatalyst holds a great advantage as an efficient and effective means in degrading organic pollutants because of their tunable band gap, visible light responses, the formation of complex structures, excellent chemical stability, economical, reusability, and ease of fabrication. However, despite the significant progress made in the synthesis of photocatalyst for environmental remediation, their photocatalytic performance for degradation and mineralization of pharmaceutical and personal care products with their intermediates still need additional improvement for practical application. Also, their activities are limited by insufficient light absorption, rapid electron-hole pair's recombination rate, difficulty in the separation and recycle of photocatalysts, and photo-corrosion of some semiconductor photocatalysts. The process might be complicated at times, costly, and time-consuming, hence the need to develop a method that is more efficient, easy, affordable, and environmentally friendly for the removal of organic pollutants at the WWTPs. Thus, the need for the green synthetic routes for more novel based heterostructure photocatalyst. In




Fig. 4 Schematic representation of photocatalysis mechanism (adapted with modification from [256])

addition, the synergistic effects that existed within the heterostructure photocatalyst, which aid their photocatalytic activity, need more investigation. The mechanism of the degradation pathways, also, needs much attention to be able to verify the most active reactive species in photodegradation of organic pollutants. Finally, this review tends to serve as a great advantage for material scientists and nanotechnologists who are interested in seeking materials for environmental degradation of organic pollutants.

Abbreviations

AC: Activated carbon; AOPs: Advanced oxidation processes; CB: Conduction band; CNTs: Carbon nanotubes; COD: Chemical oxygen demand; DCF: Diclofenac; EPA: Environmental Protection Agency; eV: Band gap energy; GCMS: Gas chromatography mass spectrometry; GO: Graphene oxide; LCMS: Liquid chromatography mass spectrometry; LOD: Below limit of detection; LOQ: Below limit of quantification; NSAIDs: Non-steroidal anti-inflammatory drugs; PPCPs: Pharmaceuticals and personal care products; RGO: Reduced graphene oxide; UHPLC: Ultra-high-performance liquid chromatography; UV: Ultraviolet light; VB: Valence bond; WWTPs: Wastewater treatment plant.

Acknowledgements

Not applicable.

Authors' contributions

AO conducted desk study and collected and analyzed relevant review information/data, and prepared the first draft of the paper in conjunction with EOO and OSO. EOO analyzed review information/data and revised the initial draft of the paper. OO conceived the idea, contributed, wrote some sections, read and edited the manuscript. All authors read and approved the final manuscript.

Funding

No funding was received for this work.

Availability of data and materials

All the information and data cited in this review were generated from literature research and listed in the references. The information, datasets used and analyzed during the current study are available from the corresponding author on reasonable request. We have presented all data in the form of tables and figures.

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

The authors declare that they have no competing interests.

Received: 17 September 2019 Accepted: 8 October 2020

Published online: 22 October 2020

References

- Ternes T, Adriano J, Jörg O (2015) Occurrence, fate, removal and assessment of emerging contaminants in water in the water cycle (from wastewater to drinking water). *Water Res* 72:1–2
- Vandermeersch G, Lourenço HM, Alvarez-Muñoz D et al (2015) Environmental contaminants of emerging concern in seafood—European database on contaminant levels. *Environ Res* 143:29–45
- Alves RN, Maulvault AL, Barbosa VL et al (2017) Preliminary assessment on the bioaccessibility of contaminants of emerging concern in raw and cooked seafood. *Food Chem Toxicol* 104:69–78
- Valdés ME, Amé MV, de los Angeles Bistoni M et al (2014) Occurrence and bioaccumulation of pharmaceuticals in a fish species inhabiting the Suquia River basin (Córdoba, Argentina). *Sci Total Environ* 472:389–396
- Bolong N, Ismail A, Salim MR et al (2009) A review of the effects of emerging contaminants in wastewater and options for their removal. *Desalination* 239(1–3):229–246
- Yuan C, Hung C-H, Li H-W et al (2016) Photodegradation of ibuprofen by TiO₂ co-doping with urea and functionalized CNT irradiated with visible light—effect of doping content and pH. *Chemosphere* 155:471–478
- Adeleye AS, Conway JR, Garner K et al (2016) Engineered nanomaterials for water treatment and remediation: costs, benefits, and applicability. *Chem Eng* 286:640–662
- Ramgopal G, Vidya Y, Anantharaju K et al (2015) Bio-inspired synthesis of Y₂O₃:Eu³⁺ red nanophosphor for eco-friendly photocatalysis. *Spectrochimica Acta A* 141:149–160
- Tyagi I, Gupta V, Sadegh H et al (2017) Nanoparticles as adsorbent; a positive approach for removal of noxious metal ions: a review. *Sci Technol Dev* 34(3):195–214
- Prakash K, Kumar JV, Latha P et al (2019) Fruitful fabrication of CDs on GO/g-C₃N₄ sheets layers: a carbon amalgamation for the remediation of carcinogenic pollutants. *J Photochem Photobiol A Chem* 370:94–104
- Jung C, Son A, Her N et al (2015) Removal of endocrine disrupting compounds, pharmaceuticals, and personal care products in water using carbon nanotubes: a review. *J Ind Eng Chem* 27:1–11
- Anjali R, Shanthakumar S (2019) Insights on the current status of occurrence and removal of antibiotics in wastewater by advanced oxidation processes. *J Environ Manag* 246:51–62
- Czech B, Buda W (2016) Multicomponent nanocomposites for elimination of diclofenac in water based on an amorphous TiO₂ active in various light sources. *J Photochem Photobiol A Chem* 330:64–70
- Hou Y, Yuan G, Wang S et al (2020) Nitrofurazone degradation in the self-biased bio-photoelectrochemical system: g-C₃N₄/CdS photocathode characterization, degradation performance, mechanism and pathways. *J Hazard Mater* 384:121438
- Shao B, Liu X, Liu Z et al (2019) Synthesis and characterization of 2D/0D g-C₃N₄/CdS-nitrogen doped hollow carbon spheres (NHCS) composites with enhanced visible light photodegradation activity for antibiotic. *Chem Eng* 374:479–493
- Ebele AJ, Abdallah MA-E, Hammad S (2017) Pharmaceuticals and personal care products (PPCPs) in the freshwater aquatic environment. *Emerg Contam* 3(1):1–16
- Veach A, Bernot MJ, Mitchell JK (2012) The influence of six pharmaceuticals on freshwater sediment microbial growth incubated at different temperatures and UV exposures. *Biodegradation* 23(4):497–507
- Klosterhaus SL, Grace R, Hamilton MC et al (2013) Method validation and reconnaissance of pharmaceuticals, personal care products, and alkylphenols in surface waters, sediments, and mussels in an urban estuary. *Environ Int* 54:92–99
- Ternes TA, Joss A, Siegrist H (2004) Peer reviewed: scrutinizing pharmaceuticals and personal care products in wastewater treatment. ACS Publications, Washington, DC
- Blair B, Nikolaus A, Hedman C et al (2015) Evaluating the degradation, sorption, and negative mass balances of pharmaceuticals and personal care products during wastewater treatment. *Chemosphere* 134:395–401
- Petrie B, Barden R, Kasprzyk-Hordern B (2015) A review on emerging contaminants in wastewaters and the environment: current knowledge, understudied areas and recommendations for future monitoring. *Water Res* 72:3–27
- Agunbiade FO, Moodley B (2014) Pharmaceuticals as emerging organic contaminants in Umgeni River water system, KwaZulu-Natal, South Africa. *Environ Monit Assess* 186(11):7273–7291
- Amdany R, Chimuka L, Cukrowska E (2014) Determination of naproxen, ibuprofen and triclosan in wastewater using the polar organic chemical integrative sampler (POCIS): a laboratory calibration and field application. *Water SA* 40(3):407–414

24. Matongo S, Birungi G, Moodley B et al (2015) Pharmaceutical residues in water and sediment of Msunduzi River, kwazulu-natal, South Africa. *Chemosphere* 134:133–140
25. Li J-D, Cai Y-Q, Shi Y-L et al (2007) Determination of sulfonamide compounds in sewage and river by mixed hemimicelles solid-phase extraction prior to liquid chromatography–spectrophotometry. *J Chromatogr A* 1139:178–184
26. Watkinson A, Murby E, Kolpin DW, Costanzo S (2009) The occurrence of antibiotics in an urban watershed: from wastewater to drinking water. *Sci Total Environ* 407:2711–2723
27. Zhou J, Zhang Z, Banks E et al (2009) Pharmaceutical residues in wastewater treatment works effluents and their impact on receiving river water. *J Hazard Mater* 166:655–661
28. Agunbiade FO, Moodley B (2016) Occurrence and distribution pattern of acidic pharmaceuticals in surface water, wastewater, and sediment of the Msunduzi River, Kwazulu-Natal, South Africa. *Environ Toxicol* 35:36–46
29. Kasprzyk-Hordern B, Dinsdale RM, Guwy AJ (2008) The occurrence of pharmaceuticals, personal care products, endocrine disruptors and illicit drugs in surface water in South Wales, UK. *Water Res* 42:3498–3518
30. Gros M, Petrovic M, Barceló D (2009) Tracing pharmaceutical residues of different therapeutic classes in environmental waters by using liquid chromatography/quadrupole-linear ion trap mass spectrometry and automated library searching. *Anal Chem* 81:898–912
31. Metcalfe CD, Koenig BG, Bennie DT et al (2003) Occurrence of neutral and acidic drugs in the effluents of Canadian sewage treatment plants. *Environ Toxicol Chem* 22:2872–2880
32. Kim J, Yoon S, Lee S et al (2012) Occurrence and fate of PPCPs wastewater treatment plants in Korea. In: 2nd international conference on environment and industrial innovation, Singapore, pp 57–61
33. Brun GL, Bernier M, Losier R et al (2006) Pharmaceutically active compounds in Atlantic Canadian sewage treatment plant effluents and receiving waters, and potential for environmental effects as measured by acute and chronic aquatic toxicity. *Environ Toxicol Chem* 25:2163–2176
34. Rabiet M, Togola A, Brissaud F et al (2006) Consequences of treated water recycling as regards pharmaceuticals and drugs in surface and ground waters of a medium-sized Mediterranean catchment. *Environ Sci Technol* 40:5282–5288
35. Lin W-C, Chen H-C, Ding W-H (2005) Determination of pharmaceutical residues in waters by solid-phase extraction and large-volume on-line derivatization with gas chromatography–mass spectrometry. *J Chromatogr A* 1065:279–285
36. Kimura K, Hara H, Watanabe Y (2007) Elimination of selected acidic pharmaceuticals from municipal wastewater by an activated sludge system and membrane bioreactors. *Environ Sci Technol* 41:3708–3714
37. Wang Y, Wang X, Li M et al (2018) Removal of pharmaceutical and personal care products (PPCPs) from municipal waste water with integrated membrane systems, MBR-RO/NF. *Int J Environ Res Public Health* 15:269
38. Zhang Z, Feng Y, Gao P et al (2011) Occurrence and removal efficiencies of eight EDCs and estrogenicity in a STP. *J Environ Monit* 13:1366–1373
39. Van Zijl MC, Aneck-Hahn NH, Swart P et al (2017) Estrogenic activity, chemical levels and health risk assessment of municipal distribution point water from Pretoria and Cape Town, South Africa. *Chemosphere* 186:305–313
40. Kuch HM, Ballschmiter K (2001) Determination of endocrine-disrupting phenolic compounds and estrogens in surface and drinking water by HRGC–(NCl)–MS in the picogram per liter range. *Environ Sci Technol* 35:3201–3206
41. Archana G, Dhodapkar R, Kumar A (2016) Offline solid-phase extraction for preconcentration of pharmaceuticals and personal care products in environmental water and their simultaneous determination using the reversed phase high-performance liquid chromatography method. *Environ Monit Assess* 188:512
42. Manickum T, John W (2014) Occurrence, fate and environmental risk assessment of endocrine disrupting compounds at the wastewater treatment works in Pietermaritzburg (South Africa). *Sci Total Environ* 468:584–597
43. Huang CH, Sedlak DL (2001) Analysis of estrogenic hormones in municipal wastewater effluent and surface water using enzyme-linked immunosorbent assay and gas chromatography/tandem mass spectrometry. *Environ Toxicol Chem* 20:133–139
44. Daughton CG, Ternes TA (1999) Pharmaceuticals and personal care products in the environment: agents of subtle change? *Environ Health Perspect* 107(suppl 6):907–938
45. Yang Y, Ok YS, Kim K-H et al (2017) Occurrences and removal of pharmaceuticals and personal care products (PPCPs) in drinking water and water/sewage treatment plants: a review. *Sci Total Environ* 596:303–320
46. Tseng W-JS-W, Tsai (2019) Assessment of dermal exposures for synthetic musks from personal care products in Taiwan. *Sci Total Environ* 669:160–167
47. Juliano C, Magrini GA (2017) Cosmetic ingredients as emerging pollutants of environmental and health concern. A mini-review. *Cosmetics* 4(2):11
48. Dann AB, Hontela A (2011) Triclosan: environmental exposure, toxicity and mechanisms of action. *J Applied Toxicol* 31(4):285–311
49. Tijani JO, Fatoba OO, Babajide OO et al (2016) Pharmaceuticals, endocrine disruptors, personal care products, nanomaterials and perfluorinated pollutants: a review. *Environ Chem Lett* 14(1):27–49
50. Langford KH, Thomas KV (2009) Determination of pharmaceutical compounds in hospital effluents and their contribution to wastewater treatment works. *Environ Int* 35(5):766–770
51. Fick J, Söderström H, Lindberg RH et al (2009) Contamination of surface, ground, and drinking water from pharmaceutical production. *Environ Toxicol Chem* 28(12):2522–2527
52. Boxall AB, Rudd MA, Brooks BW et al (2012) Pharmaceuticals and personal care products in the environment: what are the big questions? *Environ Health Perspect* 120(9):1221–1229
53. Maletz S, Floehr T, Beier S et al (2013) In vitro characterization of the effectiveness of enhanced sewage treatment processes to eliminate endocrine activity of hospital effluents. *Water Res* 47(4):1545–1557
54. Al Aukidy M, Verlicchi P, Voulvoulis N (2014) A framework for the assessment of the environmental risk posed by pharmaceuticals originating from hospital effluents. *Sci Total Environ* 493:54–64
55. Brausch JM, Connors KA, Brooks BW et al (2012) Human pharmaceuticals in the aquatic environment: a review of recent toxicological studies and considerations for toxicity testing. In: *Reviews of environmental contamination and toxicology*, vol 218. Springer, Boston, pp 1–99
56. Sui Q, Cao X, Lu S et al (2015) Occurrence, sources and fate of pharmaceuticals and personal care products in the groundwater: a review. *Emerg Contam* 1(1):14–24
57. Del Rosario KL, Mitra S, Humphrey CP Jr et al (2014) Detection of pharmaceuticals and other personal care products in groundwater beneath and adjacent to onsite wastewater treatment systems in a coastal plain shallow aquifer. *Sci Total Environ* 487:216–223
58. Wang J, Wang S (2016) Removal of pharmaceuticals and personal care products (PPCPs) from wastewater: a review. *J Environ Manag* 182:620–640
59. Weigel S, Berger U, Jensen E et al (2004) Determination of selected pharmaceuticals and caffeine in sewage and seawater from Tromsø/Norway with emphasis on ibuprofen and its metabolites. *Chemosphere* 56(6):583–592
60. Awfa D, Ateia M, Fujii M et al (2018) Photodegradation of pharmaceuticals and personal care products in water treatment using carbonaceous-TiO₂ composites: a critical review of recent literature. *Water Res* 142:26–45
61. Fent K, Weston AA, Caminada D (2006) Ecotoxicology of human pharmaceuticals. *Aqua Toxicol* 76(2):122–159
62. Nikolaou A, MERIC S, Fatta D (2007) Occurrence patterns of pharmaceuticals in water and wastewater environments. *Anal Bioanal Chem* 387(4):1225–1234
63. Boreen AL, Arnold WA, McNeill K (2003) Photodegradation of pharmaceuticals in the aquatic environment: a review. *Aquat Sci* 65(4):320–341
64. Packer JL, Werner JJ, Latch DE et al (2003) Photochemical fate of pharmaceuticals in the environment: naproxen, diclofenac, clofibrac acid, and ibuprofen. *Aquat Sci* 65(4):342–351
65. Huerta-Fontela M, Galceran MT, Ventura F (2011) Occurrence and removal of pharmaceuticals and hormones through drinking water treatment. *Water Res* 45(3):1432–1442
66. Hirsch R, Ternes T, Haberer K et al (1999) Occurrence of antibiotics in the aquatic environment. *Sci Total Environ* 225(1–2):109–118

67. Kümmerer K (2009) Antibiotics in the aquatic environment—a review—part I. *Chemosphere* 75(4):417–434
68. Osunmakinde CS, Tshabalala OS, Dube S et al (2013) Verification and validation of analytical methods for testing the levels of PPCPs (pharmaceutical & personal health care products) in treated drinking water and sewage: report to the Water Research Commission. Water Research Commission Pretoria
69. Kosma CI, Lambropoulou DA, Albanis TA (2014) Investigation of PPCPs in wastewater treatment plants in Greece: occurrence, removal and environmental risk assessment. *Sci Total Environ* 466:421–438
70. Camacho-Muñoz D, Martín J, Santos JL et al (2010) Occurrence, temporal evolution and risk assessment of pharmaceutically active compounds in Doñana Park (Spain). *J Hazard Mater* 183(1–3):602–608
71. Petrović M, Hernando MD, Díaz-Cruz MS et al (2005) Liquid chromatography–tandem mass spectrometry for the analysis of pharmaceutical residues in environmental samples: a review. *J Chromatogr A* 1067(1–2):1–14
72. Liney KE, Hagger JA, Tyler CR et al (2006) Health effects in fish of long-term exposure to effluents from wastewater treatment works. *Environ Health Perspect* 114(Suppl 1):81–89
73. Jobling S, Burn RW, Thorpe K et al (2009) Statistical modeling suggests that antiandrogens in effluents from wastewater treatment works contribute to widespread sexual disruption in fish living in English rivers. *Environ Health Perspect* 117(5):797–802
74. Schriks M, Heringa MB, van der Kooij MM et al (2010) Toxicological relevance of emerging contaminants for drinking water quality. *Water Res* 44(2):461–476
75. Solé M, Raldua D, Piferrer F et al (2003) Feminization of wild carp, *Cyprinus carpio*, in a polluted environment: plasma steroid hormones, gonadal morphology and xenobiotic metabolizing system. *Comp Biochem Phys C* 136(2):145–156
76. Schwaiger J, Ferling H, Mallow U et al (2004) Toxic effects of the non-steroidal anti-inflammatory drug diclofenac: part I: histopathological alterations and bioaccumulation in rainbow trout. *Aquat Toxicol* 68(2):141–150
77. Galus M, Jeyaranjaan J, Smith E et al (2013) Chronic effects of exposure to a pharmaceutical mixture and municipal wastewater in zebrafish. *Aquat Toxicol* 132:212–222
78. Archer E, Petrie B, Kasprzyk-Hordern B et al (2017) The fate of pharmaceuticals and personal care products (PPCPs), endocrine disrupting contaminants (EDCs), metabolites and illicit drugs in a WWTW and environmental waters. *Chemosphere* 174:437–446
79. Harden CL, Nikolov BG, Kandula P et al (2010) Effect of levetiracetam on testosterone levels in male patients. *Epilepsia* 51(11):2348–2351
80. Svalheim S, Sveberg L, Mochol M et al (2015) Interactions between antiepileptic drugs and hormones. *Seizure* 28:12–17
81. Swart N, Pool E (2007) Rapid detection of selected steroid hormones from sewage effluents using an ELISA in the Kuils River water catchment area, South Africa. *J Immunoassay Immunochem* 28(4):395–408
82. Swart JC, Pool EJ, van Wyk JH (2011) The implementation of a battery of in vivo and in vitro bioassays to assess river water for estrogenic endocrine disrupting chemicals. *Ecotoxicol Environ Saf* 74(1):138–143
83. Baron PA, Love DC, Nachman KE (2014) Pharmaceuticals and personal care products in chicken meat and other food animal products: a market-basket pilot study. *Sci Total Environ* 490:296–300
84. Done HY, Halden RU (2015) Reconnaissance of 47 antibiotics and associated microbial risks in seafood sold in the United States. *J Hazard Mater* 282:10–17
85. Pan M, Wong CK, Chu L (2014) Distribution of antibiotics in wastewater-irrigated soils and their accumulation in vegetable crops in the Pearl River Delta, southern China. *J Agric Food Chem* 62(46):11062–11069
86. Çatalkaya EÇ, Bali U, Şengül F (2003) Photochemical degradation and mineralization of 4-chlorophenol. *Environ Sci Pollut Res* 10(2):113–120
87. Mirra R, Ribarov C, Valchev D et al (2020) Towards energy efficient onsite wastewater treatment. *J Civ Eng Manag* 6(7):1218–1226
88. Petrović M, Gonzalez S, Barceló D (2003) Analysis and removal of emerging contaminants in wastewater and drinking water. *Trac-Trend Anal Chem* 22(10):685–696
89. Ferroudj N, Nzimoto J, Davidson A et al (2013) Maghemite nanoparticles and maghemite/silica nanocomposite microspheres as magnetic Fenton catalysts for the removal of water pollutants. *Appl Catal* 136:9–18
90. Halling-Sørensen B, Nielsen SN, Lanzky P et al (1998) Occurrence, fate and effects of pharmaceutical substances in the environment—a review. *Chemosphere* 36(2):357–393
91. Ibáñez M, Gracia-Lor E, Bijlsma L et al (2013) Removal of emerging contaminants in sewage water subjected to advanced oxidation with ozone. *J Hazard Mater* 260:389–398
92. Zhang DQ, Gersberg RM, Hua T et al (2013) Fate of pharmaceutical compounds in hydroponic mesocosms planted with *Scirpus validus*. *Environ Pollut* 181:98–106
93. Li G, Nie X, Gao Y et al (2016) Can environmental pharmaceuticals be photocatalytically degraded and completely mineralized in water using g-C₃N₄/TiO₂ under visible light irradiation?—Implications of persistent toxic intermediates. *Appl Catal* 180:726–732
94. Roberts J, Kumar A, Du J et al (2016) Pharmaceuticals and personal care products (PPCPs) in Australia's largest inland sewage treatment plant, and its contribution to a major Australian river during high and low flow. *Sci Total Environ* 541:1625–1637
95. Wu H, Fan J, Yang Y et al (2015) Hydrothermal synthesis of graphene–TiO₂ nanowire with an enhanced photocatalytic activity. *Russ J Phys Chem A* 89(7):1189–1194
96. Carballa M, Omil F, Lema JM et al (2004) Behavior of pharmaceuticals, cosmetics and hormones in a sewage treatment plant. *Water Res* 38(12):2918–2926
97. Göbel A, Thomsen A, McArdell CS et al (2005) Occurrence and sorption behavior of sulfonamides, macrolides, and trimethoprim in activated sludge treatment. *Environ Sci Technol* 39(11):3981–3989
98. Kasprzyk-Hordern B, Dinsdale RM, Guwy AJ (2009) The removal of pharmaceuticals, personal care products, endocrine disruptors and illicit drugs during wastewater treatment and its impact on the quality of receiving waters. *Water Res* 43(2):363–380
99. Lindqvist N, Tuhkanen T, Kronberg L (2005) Occurrence of acidic pharmaceuticals in raw and treated sewages and in receiving waters. *Water Res* 39(11):2219–2228
100. Kaur H, Hippargi G, Pophali GR et al (2019) Treatment methods for removal of pharmaceuticals and personal care products from domestic wastewater. In: *Pharmaceuticals and personal care products: waste management and treatment technology*. Elsevier, Oxford
101. Gomes J, Domingues E, Gmurek M et al (2020) Advanced oxidation processes for recalcitrant compounds removal comparison with biofiltration by *Corbicula fluminea*. *Energy Rep* 6:666–671
102. Madikizela LM, Ncube S, Chimuka L (2020) Analysis, occurrence and removal of pharmaceuticals in African water resources: a current status. *J Manag* 253:109741
103. Berset J-D, Brenneisen R, Mathieu C (2010) Analysis of illicit and illicit drugs in waste, surface and lake water samples using large volume direct injection high performance liquid chromatography–electrospray tandem mass spectrometry (HPLC–MS/MS). *Chemosphere* 81(7):859–866
104. Bolea MR, Galceran MT, Ventura F (2011) Behavior of pharmaceuticals and drugs of abuse in a drinking water treatment plant (DWTP) using combined conventional and ultrafiltration and reverse osmosis (UF/RO) treatments. *Environ Pollut* 159(6):1584–1591
105. Alvarino T, Suarez S, Lema J et al (2018) Understanding the sorption and biotransformation of organic micropollutants in innovative biological wastewater treatment technologies. *Sci Total Environ* 615:297–306
106. Anjum M, Miandad R, Waqas M et al (2016) Remediation of wastewater using various nano-materials. *Arab J Chem* 12(8):4897–4919
107. Lagesson A, Fahlman J, Brodin T et al (2016) Bioaccumulation of five pharmaceuticals at multiple trophic levels in an aquatic food web—Insights from a field experiment. *Sci Total Environ* 568:208–215
108. Mirzaei A, Chen Z, Haghhighat F et al (2016) Removal of pharmaceuticals and endocrine disrupting compounds from water by zinc oxide-based photocatalytic degradation: a review. *Sustain Cities Soc* 27:407–418
109. Zelmanov G, Semiat R (2008) Phenol oxidation kinetics in water solution using iron (3)-oxide-based nano-catalysts. *Water Res* 42(14):3848–3856
110. Ali ME, El-Aty AMA, Badawy MI et al (2018) Removal of pharmaceutical pollutants from synthetic wastewater using chemically modified

- biomass of green alga *Scenedesmus obliquus*. *Ecotoxicol Environ Saf* 151:144–152
111. Li Y, Taggart MA, McKenzie C et al (2019) Utilizing low-cost natural waste for the removal of pharmaceuticals from water: mechanisms, isotherms and kinetics at low concentrations. *J Clean Prod* 227:88–97
 112. Lerman I, Chen Y, Xing B et al (2013) Adsorption of carbamazepine by carbon nanotubes: effects of DOM introduction and competition with phenanthrene and bisphenol A. *Environ Pollut* 182:169–176
 113. Cai N, Larese-Casanova P (2014) Sorption of carbamazepine by commercial graphene oxides: a comparative study with granular activated carbon and multiwalled carbon nanotubes. *J Colloid Interface Sci* 426:152–161
 114. Zhou Y, Apul OG, Karanfil T (2015) Adsorption of halogenated aliphatic contaminants by graphene nanomaterials. *Water Res* 79:57–67
 115. Kasprzyk-Hordern B, Ziólek M, Nawrocki J (2003) Catalytic ozonation and methods of enhancing molecular ozone reactions in water treatment. *Appl Catal* 46(4):639–669
 116. Wang Y, Zhang J, Liu X et al (2012) Synthesis and characterization of activated carbon-coated $\text{SiO}_2/\text{TiO}_2-x\text{C}_x$ nanoporous composites with high adsorption capability and visible light photocatalytic activity. *J Mater Chem* 135(2–3):579–586
 117. Cominellis C, Kapalka A, Malato S et al (2008) Advanced oxidation processes for water treatment: advances and trends for R&D. *J Chem Technol Biotechnol* 83(6):769–776
 118. Kanakaraju D, Glass BD, Oelgemöller M (2018) Advanced oxidation process-mediated removal of pharmaceuticals from water: a review. *J Environ Manag* 219:189–207
 119. Wang Y, Liu J, Kang D et al (2017) Removal of pharmaceuticals and personal care products from wastewater using algae-based technologies: a review. *Rev Environ Sci Bio/Technol* 16(4):717–735
 120. Gültekin I, Ince NH (2007) Synthetic endocrine disruptors in the environment and water remediation by advanced oxidation processes. *J Environ Manag* 85(4):816–832
 121. Nakata K, Fujishima A (2012) TiO_2 photocatalysis: design and applications. *J Photochem Photobiol C Photochem Rev* 13(3):169–189
 122. Byrne C, Subramanian G, Pillai SC (2018) Recent advances in photocatalysis for environmental applications. *J Environ Chem Eng* 6(3):3531–3555
 123. Zhao C, Li W, Liang Y et al (2016) Synthesis of BiOBr/carbon quantum dots microspheres with enhanced photoactivity and photostability under visible light irradiation. *Appl Catal A Gen* 527:127–136
 124. Spasiano D, Marotta R, Malato S et al (2015) Solar photocatalysis: materials, reactors, some commercial, and pre-industrialized applications. A comprehensive approach. *Appl Catal* 170:90–123
 125. Salaeh S, Perisic DJ, Biosic M et al (2016) Diclofenac removal by simulated solar assisted photocatalysis using TiO_2 -based zeolite catalyst; mechanisms, pathways and environmental aspects. *Chem Eng* 304:289–302
 126. Reina AC, Santos-Juanes L, Sánchez JG et al (2015) Modelling the photo-Fenton oxidation of the pharmaceutical paracetamol in water including the effect of photon absorption (VRPA). *Appl Catal* 166:295–301
 127. de Luna MDG, Briones RM, Su C-C et al (2013) Kinetics of acetaminophen degradation by Fenton oxidation in a fluidized-bed reactor. *Chemosphere* 90(4):1444–1448
 128. Klementova S, Kahoun D, Doubkova L et al (2017) Catalytic photo-degradation of pharmaceuticals—homogeneous and heterogeneous photocatalysis. *Photochem Photobiol Sci* 16(1):67–71
 129. Agustina TE, Ang HM, Vareek VK (2005) A review of synergistic effect of photocatalysis and ozonation on wastewater treatment. *J Photochem Photobiol C Photochem Rev* 6(4):264–273
 130. Xiao J, Xie Y, Cao H (2015) Organic pollutants removal in wastewater by heterogeneous photocatalytic ozonation. *Chemosphere* 121:1–17
 131. Mehrjouei M, Müller S, Möller D (2015) A review on photocatalytic ozonation used for the treatment of water and wastewater. *Chem Eng* 263:209–219
 132. Dobsław D, Schulz A, Helbich S et al (2017) VOC removal and odor abatement by a low-cost plasma enhanced biotrickling filter process. *J Environ Chem Eng* 5(6):5501–5511
 133. Oller I, Malato S, Sánchez-Pérez J (2011) Combination of advanced oxidation processes and biological treatments for wastewater decontamination—a review. *Sci Total Environ* 409(20):4141–4166
 134. Augugliaro V, Palmisano G, Palmisano L et al (2019) Heterogeneous photocatalysis and catalysis: an overview of their distinctive features. In: *Heterogeneous photocatalysis*. Elsevier, Amsterdam, pp 1–24
 135. Ortiz I, Rivero MJ, Margallo M (2019) Advanced oxidative and catalytic processes. In: *Sustainable water and wastewater processing*. Elsevier, Amsterdam, pp 161–201
 136. Eskandarian MR, Choi H, Fazli M et al (2016) Effect of UV-LED wavelengths on direct photolytic and TiO_2 photocatalytic degradation of emerging contaminants in water. *Chem Eng* 300:414–422
 137. Akhavan O (2009) Lasting antibacterial activities of $\text{Ag-TiO}_2/\text{Ag}/\alpha\text{-TiO}_2$ nanocomposite thin film photocatalysts under solar light irradiation. *J Colloid Interface Sci* 336(1):117–124
 138. Lin S-T, Thirumavalavan M, Jiang T-Y et al (2014) Synthesis of ZnO/Zn nano photocatalyst using modified polysaccharides for photodegradation of dyes. *Carbohydr Polym* 105:1–9
 139. Theingi M, Tun KT, Aung NN (2019) Preparation, characterization and optical property of LaFeO_3 nanoparticles via sol-gel combustion method. *SciMed J* 1(3):151–157
 140. Rehman GU, Tahir M, Goh P et al (2019) Facile synthesis of GO and $\text{g-C}_3\text{N}_4$ nanosheets encapsulated magnetite ternary nanocomposite for superior photocatalytic degradation of phenol. *Environ Pollut* 253:1066–1078
 141. Asadzadeh-Khaneghah S, Habibi-Yangjeh A, Yubuta K (2019) Novel $\text{g-C}_3\text{N}_4$ nanosheets/CDs/BiOCl photocatalysts with exceptional activity under visible light. *J Am Ceram Soc* 102(3):1435–1453
 142. Bahnemann D (2004) Photocatalytic water treatment: solar energy applications. *J Sol Energy* 77(5):445–459
 143. Qiu LF, Zhou ZW, Qiu XB et al (2018) Synthesis and photocatalytic degradation performance of $\text{g-C}_3\text{N}_4/\text{CQDs}/\text{SAPO-5}$ ternary composite. In: *Key engineering materials*. Trans Tech Publ, Pfaffikon
 144. Cheng Y, Lin Y, Xu J et al (2016) Surface plasmon resonance enhanced visible-light-driven photocatalytic activity in Cu nanoparticles covered Cu_2O microspheres for degrading organic pollutants. *Appl Surf Sci* 366:120–128
 145. Li C, Yu S, Che H et al (2018) Fabrication of Z-scheme heterojunction by anchoring mesoporous $\gamma\text{-Fe}_2\text{O}_3$ nanospheres on $\text{g-C}_3\text{N}_4$ for degrading tetracycline hydrochloride in water. *ACS Sustain Chem Eng* 6(12):16437–16447
 146. Saleh R, Djaja NF (2014) UV light photocatalytic degradation of organic dyes with Fe-doped ZnO nanoparticles. *Superlattice Microstruct* 74:217–233
 147. Ismail AA (2012) Facile synthesis of mesoporous Ag-loaded TiO_2 thin film and its photocatalytic properties. *Microporous Mesoporous Mater* 149(1):69–75
 148. Friedmann D, Mendive C, Bahnemann D (2010) TiO_2 for water treatment: parameters affecting the kinetics and mechanisms of photocatalysis. *Appl Catal* 99(3–4):398–406
 149. Zhang J, Zhou P, Liu J et al (2014) New understanding of the difference of photocatalytic activity among anatase, rutile and brookite TiO_2 . *Phys Chem Chem Phys* 16(38):20382–20386
 150. Awfa D, Ateia M, Fujii M et al (2019) Novel magnetic carbon nanotube- TiO_2 composites for solar light photocatalytic degradation of pharmaceuticals in the presence of natural organic matter. *J Water Process Eng* 31:100836
 151. Rimoldi L, Meroni D, Falletta E et al (2017) Emerging pollutant mixture mineralization by TiO_2 photocatalysts. The role of the water medium. *Photochem Photobiol Sci* 16(1):60–66
 152. He Y, Sutton NB, Rijnaarts HH et al (2016) Degradation of pharmaceuticals in wastewater using immobilized TiO_2 photocatalysis under simulated solar irradiation. *Appl Catal* 182:132–141
 153. Hapeshi E, Achilleos A, Vasquez MI et al (2010) Drugs degrading photocatalytically: kinetics and mechanisms of ofloxacin and atenolol removal on titania suspensions. *Water Res* 44(6):1737–1746
 154. Thevenet F, Guaitella O, Herrmann J et al (2005) Photocatalytic degradation of acetylene over various titanium dioxide-based photocatalysts. *Appl Catal* 61(1–2):58–68

155. Noorimotlagh Z, Kazeminezhad I, Jaafarzadeh N et al (2018) WITH-DRAWN: nonylphenol degradation using immobilized carbon-doped TiO₂ (Rutile/Anatase) under visible illumination: effect of operational parameters and degradation pathway. *Chem Eng J*. <https://doi.org/10.1016/j.cej.2018.02.077>
156. Dzinun H, Othman MHD, Ismail AF et al (2015) Photocatalytic degradation of nonylphenol by immobilized TiO₂ in dual layer hollow fibre membranes. *Chem Eng* 269:255–261
157. Wang X, Hu Z, Chen Y et al (2009) A novel approach towards high-performance composite photocatalyst of TiO₂ deposited on activated carbon. *Appl Surf Sci* 255(7):3953–3958
158. Dlugosz M, Kwiecień A, Żmudzki P et al (2015) A hybrid adsorbent/visible light photocatalyst for the abatement of microcystin-LR in water. *ChemComm* 51(36):7649–7652
159. Janotti A, Van de Walle CG (2009) Fundamentals of zinc oxide as a semiconductor. *Rep Prog Phys* 72(12):126501
160. Di Mauro A, Fragala ME, Privitera V et al (2017) ZnO for application in photocatalysis: from thin films to nanostructures. *Mater Sci Semicond Process* 69:44–51
161. Teixeira S, Gurke R, Eckert H et al (2016) Photocatalytic degradation of pharmaceuticals present in conventional treated wastewater by nanoparticle suspensions. *J Environ Chem Eng* 4(1):287–292
162. Ismael M (2020) The photocatalytic performance of the ZnO/g-C₃N₄ composite photocatalyst toward degradation of organic pollutants and its inactivity toward hydrogen evolution: the influence of light irradiation and charge transfer. *Chem Phys Lett* 739:136992
163. Dirany N, Arab M, Madigou V et al (2016) A facile one step route to synthesize WO₃ nanoplatelets for CO oxidation and photodegradation of RhB: microstructural, optical and electrical studies. *RSC Adv* 6(73):69615–69626
164. Chen G, Bian S, Guo C-Y et al (2019) Insight into the Z-scheme heterostructure WO₃/g-C₃N₄ for enhanced photocatalytic degradation of methyl orange. *Mater Lett* 236:596–599
165. Wang H, Yang X, Zi J et al (2016) High photocatalytic degradation of tetracycline under visible light with Ag/AgCl/activated carbon composite plasmonic photocatalyst. *J Ind Eng Chem* 35:83–92
166. Santhosh C, Velmurugan V, Jacob G et al (2016) Role of nanomaterials in water treatment applications: a review. *Chem Eng* 306:1116–1137
167. Leary R, Westwood A (2011) Carbonaceous nanomaterials for the enhancement of TiO₂ photocatalysis. *Carbon* 49(3):741–772
168. Puma GL, Bono A, Krishnaiah D et al (2008) Preparation of titanium dioxide photocatalyst loaded onto activated carbon support using chemical vapor deposition: a review paper. *J Hazard Mater* 157(2–3):209–219
169. Jamil TS, Ghaly MY, Fathy NA et al (2012) Enhancement of TiO₂ behavior on photocatalytic oxidation of MO dye using TiO₂/AC under visible irradiation and sunlight radiation. *Sep Purif Technol* 98:270–279
170. Bhatnagar A, Hogland W, Marques M et al (2013) An overview of the modification methods of activated carbon for its water treatment applications. *Chem Eng* 219:499–511
171. Ateia M, Apul OG, Shimizu Y et al (2017) Elucidating adsorptive fractions of natural organic matter on carbon nanotubes. *Environ Sci Technol* 51(12):7101–7110
172. Woan K, Pyrgiotakis G, Sigmund W (2009) Photocatalytic carbon-nanotube-TiO₂ composites. *J Adv Mater* 21(21):2233–2239
173. Alalm MG, Tawfik A, Ookawara S (2015) Combined solar advanced oxidation and PAC adsorption for removal of pesticides from industrial wastewater. *J Mater Environ Sci* 6(3):800–809
174. Salih HH, Sorial GA, Patterson CL et al (2012) Removal of trichloroethylene by activated carbon in the presence and absence of TiO₂ nanoparticles. *Water Air Soil Pollut* 223(5):2837–2847
175. Anis SF, Khalil A, Singaravel G et al (2016) A review on the fabrication of zeolite and mesoporous inorganic nanofibers formation for catalytic applications. *Microporous Mesoporous Mater* 236:176–192
176. Takeuchi M, Kimura T, Hidaka M et al (2007) Photocatalytic oxidation of acetaldehyde with oxygen on TiO₂/ZSM-5 photocatalysts: effect of hydrophobicity of zeolites. *J Catal* 246(2):235–240
177. Takeuchi M, Hidaka M, Anpo M (2012) Efficient removal of toluene and benzene in gas phase by the TiO₂/Y-zeolite hybrid photocatalyst. *J Hazard Mater* 237:133–139
178. Khraisheh M, Kim J, Campos L et al (2013) Removal of carbamazepine from water by a novel TiO₂-coconut shell powder/UV process: composite preparation and photocatalytic activity. *Environ Eng Sci* 30(9):515–526
179. Shaibu SE, Adekola FA, Adegoke HI et al (2014) A comparative study of the adsorption of methylene blue onto synthesized nanoscale zero-valent iron-bamboo and manganese-bamboo composites. *J Mater Sci* 7(6):4493–4507
180. Fagbayigbo BO, Opeolu BO, Fatoki OS et al (2017) Removal of PFOA and PFOS from aqueous solutions using activated carbon produced from *Vitis vinifera* leaf litter. *Environ Sci Pollut Res* 24(14):13107–13120
181. Omo-Okoro PN, Daso AP, Okonkwo JO (2018) A review of the application of agricultural wastes as precursor materials for the adsorption of per-and polyfluoroalkyl substances: a focus on current approaches and methodologies. *Environ Technol Innov* 9:100–114
182. Arana J, Dona-Rodríguez J, Rendón ET et al (2003) TiO₂ activation by using activated carbon as a support: Part I. Surface characterisation and decantability study. *Appl Catal* 44(2):161–172
183. Gopiraman M, Kim IS (2018) Carbon nanocomposites: preparation and its application in catalytic organic transformations. In: *Nanocomposites-recent evolutions*. IntechOpen, London
184. Orha C, Pode R, Manea F et al (2017) Titanium dioxide-modified activated carbon for advanced drinking water treatment. *Process Saf Environ* 108:26–33
185. Tan Q, Xu Y, Yang J et al (2013) Preparation and electrochemical properties of the ternary nanocomposite of polyaniline/activated carbon/TiO₂ nanowires for supercapacitors. *Electrochim Acta* 88:526–529
186. Vinayagam M, Ramachandran S, Ramya V et al (2018) Photocatalytic degradation of orange G dye using ZnO/biomass activated carbon nanocomposite. *J Environ Chem Eng* 6(3):3726–3734
187. Iijima S (1991) Helical microtubules of graphitic carbon. *Nature* 354(6348):56–58
188. Wei H, Deng S, Huang Q et al (2013) Regenerable granular carbon nanotubes/alumina hybrid adsorbents for diclofenac sodium and carbamazepine removal from aqueous solution. *Water Res* 47(12):4139–4147
189. Agnihotri S, Mota JP, Rostam-Abadi M et al (2006) Adsorption site analysis of impurity embedded single-walled carbon nanotube bundles. *Carbon* 44(12):2376–2383
190. Ye S, Zhou X, Xu Y et al (2019) Photocatalytic performance of multi-walled carbon nanotube/BiVO₄ synthesized by electro-spinning process and its degradation mechanisms on oxytetracycline. *Chem Eng* 373:880–890
191. Marques RR, Sampaio MJ, Carrapiço PM et al (2013) Photocatalytic degradation of caffeine: developing solutions for emerging pollutants. *Catal Today* 209:108–115
192. Samsudin MFR, Bacho N, Sufian S et al (2019) Photocatalytic degradation of phenol wastewater over Z-scheme g-C₃N₄/CNT/BiVO₄ heterostructure photocatalyst under solar light irradiation. *J Mol Liq* 277:977–988
193. Samsudin MFR, Mahmood A, Sufian S (2018) Enhanced photocatalytic degradation of wastewater over RGO-TiO₂/BiVO₄ photocatalyst under solar light irradiation. *J Mol Liq* 268:26–36
194. An G, Ma W, Sun Z et al (2007) Preparation of titania/carbon nanotube composites using supercritical ethanol and their photocatalytic activity for phenol degradation under visible light irradiation. *Carbon* 45(9):1795–1801
195. Hu C, Lu T, Chen F et al (2013) A brief review of graphene-metal oxide composites synthesis and applications in photocatalysis. *J Chin Adv Mater Soc* 1(1):21–39
196. Ersan G, Apul OG, Perreault F et al (2017) Adsorption of organic contaminants by graphene nanosheets: a review. *Water Res* 126:385–398
197. Wang Q, Arash B (2014) A review on applications of carbon nanotubes and graphenes as nano-resonator sensors. *Comput Mater Sci* 82:350–360
198. Bonaccorso F, Colombo L, Yu G et al (2015) Graphene, related two-dimensional crystals, and hybrid systems for energy conversion and storage. *J Sci* 347(6217):1246501
199. Mittal G, Dhand V, Rhee KY et al (2015) A review on carbon nanotubes and graphene as fillers in reinforced polymer nanocomposites. *J Ind Eng Chem* 21:11–25

200. Suárez-Iglesias O, Collado S, Oulego P et al (2017) Graphene-family nanomaterials in wastewater treatment plants. *Chem Eng* 313:121–135
201. Fei P, Wang Q, Zhong M et al (2016) Preparation and adsorption properties of enhanced magnetic zinc ferrite-reduced graphene oxide nanocomposites via a facile one-pot solvothermal method. *J Alloys Compd* 685:411–417
202. Shen J, Ma G, Zhang J et al (2015) Facile fabrication of magnetic reduced graphene oxide-ZnFe₂O₄ composites with enhanced adsorption and photocatalytic activity. *Appl Surf Sci* 359:455–468
203. Brodie BC (1859) XIII. On the atomic weight of graphite. *Philos Trans R Soc B* 149:249–259
204. Poh HL, Šaněk F, Ambrosi A et al (2012) Graphenes prepared by Staudenmaier, Hofmann and Hummers methods with consequent thermal exfoliation exhibit very different electrochemical properties. *Nanoscale* 4(11):3515–3522
205. Stankovich S, Dikin DA, Piner RD et al (2007) Synthesis of graphene-based nanosheets via chemical reduction of exfoliated graphite oxide. *Carbon* 45(7):1558–1565
206. Ma L, Chen A, Zhang Z et al (2012) In-situ fabrication of CNT/TiO₂ interpenetrating network film on nickel substrate by chemical vapour deposition and application in photoassisted water electrolysis. *Catal Commun* 21:27–31
207. Lin Z, Yao Y, Li Z et al (2010) Solvent-assisted thermal reduction of graphite oxide. *J Phys Chem* 114(35):14819–14825
208. Shao Y, Wang J, Engelhard M et al (2010) Facile and controllable electrochemical reduction of graphene oxide and its applications. *J Mater Chem* 20(4):743–748
209. Morales-Torres S, Pastrana-Martínez LM, Figueiredo JL et al (2013) Graphene oxide-P25 photocatalysts for degradation of diphenhydramine pharmaceutical and methyl orange dye. *Appl Surf Sci* 275:361–368
210. Gu Y, Yu Y, Zou J et al (2018) The ultra-rapid synthesis of rGO/g-C₃N₄ composite via microwave heating with enhanced photocatalytic performance. *Mater Lett* 232:107–109
211. Kim IY, Lee JM, Kim TW et al (2012) A strong electronic coupling between graphene nanosheets and layered titanate nanoplates: a soft-chemical route to highly porous nanocomposites with improved photocatalytic activity. *Small Methods* 8(7):1038–1048
212. Sun J, Zhang H, Guo L-H et al (2013) Two-dimensional interface engineering of a titania-graphene nanosheet composite for improved photocatalytic activity. *ACS Appl Mater Inter* 5(24):13035–13041
213. Shanavas S, Roopan SM, Priyadharsan A et al (2019) Computationally guided synthesis of (2D/3D/2D) rGO/Fe₂O₃/g-C₃N₄ nanostructure with improved charge separation and transportation efficiency for degradation of pharmaceutical molecules. *Appl Catal* 255:117758
214. Nawaz M, Miran W, Jang J et al (2017) One-step hydrothermal synthesis of porous 3D reduced graphene oxide/TiO₂ aerogel for carbamazepine photodegradation in aqueous solution. *Appl Catal* 203:85–95
215. Lin T, Yu S, Chen W (2016) Occurrence, removal and risk assessment of pharmaceutical and personal care products (PPCPs) in an advanced drinking water treatment plant (ADWTP) around Taihu Lake in China. *Chemosphere* 152:1–9
216. Mori M, Sammes NM, Tompsett GA (2000) Fabrication processing condition for dense sintered La_{0.6}Ae_{0.4}MnO₃ perovskites synthesized by the coprecipitation method (Ae=Ca and Sr). *J Power Sources* 86(1–2):395–400
217. Huang G, Lu C-H, Yang H-H (2019) Magnetic nanomaterials for magnetic bioanalysis. In: *Novel nanomaterials for biomedical, environmental and energy applications*. Elsevier, Amsterdam, pp 89–109
218. Feng S-H, Li G-H (2017) Hydrothermal and solvothermal syntheses. In: *Modern inorganic synthetic chemistry*. Elsevier, Amsterdam, pp 73–104
219. Salavati-Niasari M, Davar F, Mazaheri M (2008) Synthesis of Mn₃O₄ nanoparticles by thermal decomposition of a [bis(salicylidiminato)manganese(II)] complex. *Polyhedron* 27(17):3467–3471
220. Soni H, Kumar N, Patel K et al (2016) Photo catalytic efficiency and kinetic studies of ZnO nanoparticles for the removal of basic dye Rhodamine B. *Desalin Water Treat* 57(42):19857–19864
221. Zhang H, Fu X, Niu S et al (2008) Synthesis and photoluminescence properties of Eu³⁺-doped AZrO₃ (A=Ca, Sr, Ba) perovskite. *J Alloy Compd* 459(1–2):103–106
222. Wang B-L-L, Hu (2005) Effect of water content in sol on optical properties of hybrid sol-gel derived TiO₂/SiO₂/ormosil film. *Mater Chem Phys* 89(2–3):417–422
223. Marugán J, Christensen P, Egerton T et al (2009) Synthesis, characterization and activity of photocatalytic sol-gel TiO₂ powders and electrodes. *Appl Catal* 89(1–2):273–283
224. Lin X, Liu C, Wang J et al (2019) Graphitic carbon nitride quantum dots and nitrogen-doped carbon quantum dots co-decorated with BiVO₄ microspheres: a ternary heterostructure photocatalyst for water purification. *Sep Purif Technol* 226:117–127
225. Wang X, Maeda K, Thomas A et al (2009) A metal-free polymeric photocatalyst for hydrogen production from water under visible light. *Nat Mater* 8(1):76–80
226. Ong W-J, Tan L-L, Ng YH et al (2016) Graphitic carbon nitride (g-C₃N₄)-based photocatalysts for artificial photosynthesis and environmental remediation: are we a step closer to achieving sustainability? *Chem Rev* 116(12):7159–7329
227. Rono N, Kibet JK, Martincing BS et al (2020) A review of the current status of graphitic carbon nitride. *Crit Rev Solid State Mater Sci*. <https://doi.org/10.1080/10408436.2019.1709414>
228. Liu J, Wang H, Chen ZP et al (2015) Microcontact-printing-assisted access of graphitic carbon nitride films with favorable textures toward photoelectrochemical application. *J Adv Mater* 27(4):712–718
229. Yang P, Wang J, Yue G et al (2020) Constructing mesoporous g-C₃N₄/ZnO nanosheets catalyst for enhanced visible-light driven photocatalytic activity. *J Photochem Photobiol A Chem* 388:112169
230. Maeda K, Wang X, Nishihara Y et al (2009) Photocatalytic activities of graphitic carbon nitride powder for water reduction and oxidation under visible light. *J Phys Chem* 113(12):4940–4947
231. Kang S, Zhang L, He M et al (2018) "Alternated cooling and heating" strategy enables rapid fabrication of highly-crystalline g-C₃N₄ nanosheets for efficient photocatalytic water purification under visible light irradiation. *Carbon* 137:19–30
232. Zhong Q, Lan H, Zhang M et al (2020) Preparation of heterostructure g-C₃N₄/ZnO nanorods for high photocatalytic activity on different pollutants (MB, RhB, Cr (VI) and eosin). *Ceram Int*. <https://doi.org/10.1016/j.ceramint.2020.01.265>
233. Liang S, Zhang D, Pu X et al (2019) A novel Ag₂O/g-C₃N₄ pn heterojunction photocatalysts with enhanced visible and near-infrared light activity. *Sep Purif Technol* 210:786–797
234. He Y, Ma Z, Junior LB (2020) Distinctive binary g-C₃N₄/MoS₂ heterojunctions with highly efficient ultrasonic catalytic degradation for levofloxacin and methylene blue. *Ceram Int*. <https://doi.org/10.1016/j.ceramint.2020.01.287>
235. Liu G, Liao M, Zhang Z et al (2020) Enhanced photodegradation performance of Rhodamine B with g-C₃N₄ modified by carbon nanotubes. *Sep Purif Technol* 244:116618
236. Zhang S, Hu C, Ji H et al (2019) Facile synthesis of nitrogen-deficient mesoporous graphitic carbon nitride for highly efficient photocatalytic performance. *Appl Surf Sci* 478:304–312
237. Li J, Liu E, Ma Y et al (2016) Synthesis of MoS₂/g-C₃N₄ nanosheets as 2D heterojunction photocatalysts with enhanced visible light activity. *Appl Surf Sci* 364:694–702
238. Xue W, Hu X, Liu E et al (2018) Novel reduced graphene oxide-supported Cd_{0.5}Zn_{0.5}/g-C₃N₄ Z-scheme heterojunction photocatalyst for enhanced hydrogen evolution. *Appl Surf Sci* 447:783–794
239. Sridharan K, Jang E, Park TJ (2013) Novel visible light active graphitic C₃N₄-TiO₂ composite photocatalyst: synergistic synthesis, growth and photocatalytic treatment of hazardous pollutants. *Appl Catal* 142:718–728
240. Singh J, Arora A, Basu S (2019) Synthesis of coral like WO₃/g-C₃N₄ nanocomposites for the removal of hazardous dyes under visible light. *J Alloy Compd* 808:151734
241. Nekouei F, Nekouei S, Pouzesh M et al (2020) Porous-CdS/Cu₂O/graphitic-C₃N₄ dual pn junctions as highly efficient photocatalysts for degrading ciprofloxacin and generating hydrogen using solar energy. *Chem Eng* 385:123710
242. Chen W, Hua Y-X, Wang Y et al (2017) Two-dimensional mesoporous g-C₃N₄ nanosheet-supported MgIn₂S₄ nanoplates as visible-light-active heterostructures for enhanced photocatalytic activity. *J Catal* 349:8–18

243. Li G, Wang B, Zhang J et al (2019) Rational construction of a direct Z-scheme g-C₃N₄/CdS photocatalyst with enhanced visible light photocatalytic activity and degradation of erythromycin and tetracycline. *Appl Surf Sci* 478:1056–1064
244. Hernández-Uresti D, Vázquez A, Sanchez-Martinez D, Obregón S (2016) Performance of the polymeric g-C₃N₄ photocatalyst through the degradation of pharmaceutical pollutants under UV–vis irradiation. *J Photochem Photobiol A Chem* 324:47–52
245. Kurniawan TA, Yanyan L, Ouyang T et al (2018) BaTiO₃/TiO₂ composite-assisted photocatalytic degradation for removal of acetaminophen from synthetic wastewater under UV–vis irradiation. *Mater Sci Semicond Process* 73:42–50
246. Jingyu H, Ran Y, Zhaohui L et al (2019) In-situ growth of ZnO globular on g-C₃N₄ to fabrication binary heterojunctions and their photocatalytic degradation activity on tetracyclines. *Solid State Sci* 92:60–67
247. Song Y, Qi J, Tian J et al (2018) Construction of Ag/g-C₃N₄ photocatalysts with visible-light photocatalytic activity for sulfamethoxazole degradation. *Chem Eng J* 341:547–555
248. Kumar A, Khan M, Zeng X, Lo IM (2018) Development of g-C₃N₄/TiO₂/Fe₃O₄@ SiO₂ heterojunction via sol-gel route: a magnetically recyclable direct contact Z-scheme nanophotocatalyst for enhanced photocatalytic removal of ibuprofen from real sewage effluent under visible light. *Chem Eng J* 353:645–656
249. Yan J, Song Z, Wang X et al (2019) Enhanced photocatalytic activity of ternary Ag₃PO₄/GO/g-C₃N₄ photocatalysts for Rhodamine B degradation under visible light radiation. *Appl Surf Sci* 466:70–77
250. Wang W, Han Q, Zhu Z et al (2019) Enhanced photocatalytic degradation performance of organic contaminants by heterojunction photocatalyst BiVO₄/TiO₂/RGO and its compatibility on four different tetracycline antibiotics. *Adv Powder Technol* 30:1882–1896
251. Wen X-J, Niu C-G, Zhang L et al (2018) A novel Ag₂O/CeO₂ heterojunction photocatalysts for photocatalytic degradation of enrofloxacin: possible degradation pathways, mineralization activity and an in depth mechanism insight. *Appl Catal* 221:701–714
252. Zhou Y, Li J, Liu C et al (2018) Construction of 3D porous g-C₃N₄/AgBr/rGO composite for excellent visible light photocatalytic activity. *Appl Surf Sci* 458:586–596
253. YuChen WXA, Mei W et al (2017) Photocatalytic and electrochemical performance of three-dimensional reduced graphene oxide/WS₂/Mg-doped ZnO composites. *Appl Surf Sci* 400:129–138
254. Cui C, Xie J, Lin D et al (2019) Recent progress in carbon-based materials as catalysts for electrochemical and photocatalytic water splitting. In: *Carbon based nanomaterials for advanced thermal and electrochemical energy storage and conversion*. Elsevier, Amsterdam, pp 173–200
255. Samsudin MFR, Bacho N, Sufian S (2018) Recent development of graphitic carbon nitride-based photocatalyst for environmental pollution remediation. In: *Nanocatalysts*. IntechOpen, London
256. Ikram S (2016) Role of nanomaterials and their applications as photocatalyst and sensors: a review. *Nano Res* 2:10

Publisher's Note

Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Ready to submit your research? Choose BMC and benefit from:

- fast, convenient online submission
- thorough peer review by experienced researchers in your field
- rapid publication on acceptance
- support for research data, including large and complex data types
- gold Open Access which fosters wider collaboration and increased citations
- maximum visibility for your research: over 100M website views per year

At BMC, research is always in progress.

Learn more biomedcentral.com/submissions

