

RESEARCH ARTICLE

Car seat impact on driver's sitting behavior and perceived discomfort during prolonged real driving on varied road types


Pascaline Lantoine^{1,2}*, Mathieu Lecocq¹, Clément Bougard², Erick Dousset¹, Tanguy Marqueste¹, Christophe Bourdin¹, Jean-Marc Allègre²‡, Laurent Bauvineau²‡, Serge Mesure¹

1 Aix-Marseille Univ, CNRS, ISM, Marseille, France, **2** Stellantis, Centre Technique de Vélizy, Vélizy-Villacoublay, France

* These authors contributed equally to this work.

‡ J-MA and LB also contributed equally to this work.

* pascaline_lantoine@hotmail.com



OPEN ACCESS

Citation: Lantoine P, Lecocq M, Bougard C, Dousset E, Marqueste T, Bourdin C, et al. (2021) Car seat impact on driver's sitting behavior and perceived discomfort during prolonged real driving on varied road types. *PLoS ONE* 16(11): e0259934. <https://doi.org/10.1371/journal.pone.0259934>

Editor: YunJu Lee, National Tsing Hua University, TAIWAN

Received: March 30, 2021

Accepted: November 1, 2021

Published: November 16, 2021

Copyright: © 2021 Lantoine et al. This is an open access article distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Data Availability Statement: All relevant data are within the manuscript and its Supporting Information files.

Funding: This work was funded by the ANRT and Stellantis. The funder provided support in the form of salaries for authors Lantoine P., Bougard C., Bauvineau L. and Allègre J.-M., but did not have any additional role in the study design, data collection and analysis, decision to publish, or preparation of the manuscript. The specific roles of

Abstract

Prolonged driving under real conditions can entail discomfort linked to driving posture, seat design features, and road properties like whole-body vibrations (WBV). This study evaluated the effect of three different seats (S_1 = soft; S_2 = firm; S_3 = soft with suspension system) on driver's sitting behavior and perceived discomfort on different road types in real driving conditions. Twenty-one participants drove the same 195 km itinerary alternating highway, city, country, and mountain segments. Throughout the driving sessions, Contact Pressure (CP), Contact Surface (CS), Seat Pressure Distribution Percentage (SPD%) and Repositioning Movements (RM) were recorded via two pressure mats installed on seat cushion and backrest. Moreover every 20 minutes, participants rated their whole-body and local discomfort. While the same increase in whole-body discomfort with driving time was observed for all three seats, S_3 limited local perceived discomfort, especially in buttocks, thighs, neck, and upper back. The pressure profiles of the three seats were similar for CP, CS and RM on the backrest but differed on the seat cushion. The soft seats (S_1 & S_3) showed better pressure distribution, with lower SPD% than the firm seat (S_2). All three showed highest CP and CS under the thighs. Road type also affected both CP and CS of all three seats, with significant differences appearing between early city, highway and country segments. In the light of these results, automotive manufacturers could enhance seat design for reduced driver discomfort by combining a soft seat cushion to reduce pressure peaks, a firm backrest to support the trunk, and a suspension system to minimize vibrations.

Introduction

Transportation habits are evolving, with people driving more often and farther every year [1]. The French, for example, currently make an average of three car trips a day covering about 60 kilometres over 90 minutes [2]. The major risk is that prolonged driving exposes drivers to

these authors are articulated in the 'author contributions' section.

Competing interests: The authors have declared that no competing interests exist. This work was funded by the ANRT and Stellantis. The funder provided support in the form of salaries for authors Lantoine P., Bougard C., Bauvineau L. and Allegre J.-M., but did not have any additional role in the study design, data collection and analysis, decision to publish, or preparation of the manuscript. This commercial affiliation does not alter our adherence to PLOS ONE policies on sharing data and materials.

discomfort or fatigue [3–6]. The feeling of discomfort refers to physical symptoms and predicts the occurrence of pain, in particular in the back, neck, buttocks and thighs [7, 8]. Thus, one of the most important purchasing criteria for drivers is comfort, which is why an important design criterion for car manufacturers is minimizing discomfort, particularly on the seat.

Ebe & Griffin [9] determined two main types of factors, “static” and “dynamic”, which may influence perceived driver discomfort. Static factors include seat design characteristics such as seat shape, dimensions, or materials. These define the driving posture itself, with muscular, biomechanical, and vascular consequences. Sitting causes trunk flexion, which increases muscle stiffness as well as the mechanical load applied on the spine and the compression of tissues under buttocks, thighs, and back [10, 11]. In addition, driving is associated with postural fixity and isometric muscle contractions induced by the need to reach commands and pedals [12, 13]. Dynamic factors refer mainly to vibrations through the seat, which are directly dependent on the vehicle and road properties. In real conditions, the quality of the road is random and associated whole-body vibrations (WBV) can affect driver's posture, discomfort, and driving performance [14, 15]. The magnitude of lateral and longitudinal accelerations perceived by the driver depends on the road's linearity, the quality of the vehicle's suspension system, the speed, and the roughness of the road surface [16]. Mansfield et al. [17] further developed a multi-factorial model of vehicle seat discomfort incorporating these “static” and “dynamic” factors while adding the temporal effect of driving. The authors found that, as the magnitude of WBV or time increased, so did the feeling of perceived discomfort.

Because maintaining a driving posture for an extended period necessarily generates discomfort, drivers may try to reduce this discomfort or its frequency by moving on their seat, despite the restricted cockpit space. According to Baucher & Leborgne [10], the seat should encourage mobilization of trunk and limbs to relax muscles and relieve soft tissue and intervertebral disk compressions. Several authors reported an increase in repositioning movements (RM) with driving time, linked to changes in perceived discomfort [18–20]. Vergara & Page [21] identified two types of RM: macro-movements, referring to large postural changes and micro-movements, referring to oscillations around a “stable” posture. They found macro-movements to be the result of perceived discomfort. Of the various methods used to determine RM, pressure maps are among the most common, allowing sitting strategies at the seat-driver interface to be identified [22, 23]. Makhsous et al. [24] evaluated the influence of seat characteristics, particularly foam stiffness, on pressure parameters, using a soft cushion to induce a larger contact surface, for example. The composition of the foam appeared to be a major design criterion, affecting pressure distribution and the body's maintenance in an upright posture, and thus influenced feelings of discomfort. Moreover, pressure parameters depend on driving conditions. Seat cushion contact over time was reported to lead to sitting changes observable through a loss of pressure homogeneity and stabilization of contact pressure and surface as time increased [25–27].

For these reasons, seat designers need to take into account specific types of interaction between seat, driver, and road environment to optimize static and dynamic seat factors, in order to reduce discomfort and its related harmful physical consequences on drivers [28–30]. In the agricultural vehicle and truck contexts, one way to minimize transmission of vibrations in the vertical axis (*z*-axis) is to supplement the seat with a suspension system [30, 31]. This innovation can be used in a car to attenuate WBV and delay the onset of perceived discomfort, in particular in the back, by improving seat dynamic properties [17]. However, there is insufficient data on its performance under real driving conditions that induce varying WBV and different lateral and longitudinal solicitations. Moreover, the benefit from seat suspension systems in cars for personal use remains to be explored.

This study analyzed the evolution of the driver's sitting behavior by measuring pressure distribution and perceived discomfort under real prolonged driving conditions. Using real conditions enabled us to consider the effect of random road roughness due to surface asperity, which may induce vibrations varying in magnitude in z -axis. It also allowed us to take into account the effect of varying road types involving different levels of acceleration. Under these conditions, we investigated how (1) different seats (static factor) and (2) real driving (dynamic factor) affected pressure parameters (RM, pressure distribution, contact surface, and contact pressure) and subjective general and local discomfort. Three seats with different properties were tested: one soft (S_1), one firm (S_2), and one soft with a suspension system (S_3), on different road types. Based on previous research on agricultural vehicles we expected S_3 , with its better dynamic properties, to improve the prolonged driving experience by reducing perceived discomfort.

Materials & methods

The study was approved by automotive manufacturer Stellantis' "Comité d'hygiène, de sécurité et des conditions de travail" (Hygiene, Safety and Working Conditions Committee) and the research site was validated as biomedical research site n° 15–225 by the "Agence Régionale de Santé - Ile de France" (regional health agency Ile de France).

Participants

Twenty-one employees from Stellantis, a leading automotive manufacturer, were recruited through an email campaign and volunteered to participate in the experiment (16 men & 5 women; height: 1.74 ± 0.07 m; weight: 74.05 ± 13.75 kg). No participant had previous experience of a driving protocol, and all were naïve to the aim of comparing hardness of seats and road types in this experiment. The inclusion criteria were holding a driving license for a minimum of two years. Participants were excluded if they had suffered back pain or musculoskeletal disorders in the previous year, or if such symptoms had required medical follow-up and/or time off work. Subjects who had previously undergone back surgery were also excluded. Before each experimental session, participants completed a questionnaire about their driving habits (driving licence tenure: 25.1 ± 10.0 years; annual mileage: $13\,650 \pm 8777$ km; daily driving time: 78 ± 75.5 min) and gave their written informed consent (as outlined in PLOS consent form). Participants could stop the experiment at will and took responsibility for any violation of the Highway Code. Moreover, they were informed that experimenters would answer their questions about the aim of the study at the end of the driving sessions.

Experimental car

For this experiment, a 3008 vehicle (puretech 130, Peugeot, France) with an automatic gearbox was used. As a consequence, there was no clutch pedal and no gear switching. Technical adaptations were made to the car to allow each seat to be installed in the driver's place, and to collect data. Additional substructures were designed to fix seats to the car floor and to maintain the original cockpit configuration of the standard 3008 seat. Several electronic devices, in particular two cameras, one facing the driver and one oriented towards the road, a power station, and a computer, were installed in the car cockpit and trunk. The computer screen was fixed to the back of the front passenger seat facing the second experimenter, who used it to collect pressure and video data.

Experimental synopsis

All driving sessions covered the same 195 km itinerary lasting a minimum of 3 hours in real driving conditions. Driving sessions were scheduled at least one week apart and involved participants randomly assessing one seat among the three tested. Each experimental session started from the Technical Center of French car manufacturer PSA (Vélizy-Villacoublay, France) at the same time of the day (8:00 am) to avoid any effect from differences in circadian rhythms and traffic between sessions. Upon the participant's arrival, pressure mats were installed in the middle of the backrest and cushion. Then, participants were asked to put on a sports outfit provided by the experimenters, to avoid any effect from clothing type on perceived discomfort and any seam marking on pressure mats. They got into the cockpit and adjusted the seat to be as comfortable as possible. The participants could adjust the fore-aft position of the seat, the backrest inclination, the height of the seat, and the height of the steering wheel. Once adjusted, these settings subsequently remained unchanged throughout the driving session. Before the driving session, a calibration of two minutes in referential position (right foot on the throttle pedal, left foot on rest platform, left knee at an angle of 90°, and hands on the steering wheel at positions nine and three) was recorded by pressure system XSENSOR[®] and by two cameras. This calibration was defined as the baseline posture for the future normalization of pressure data representative of posture in an automatic car. After the calibration period, the participant started the vehicle and drove to the starting point. Then the two experimenters present throughout the driving session, one in the front passenger seat monitoring perceived discomfort measures and one at the rear handling recordings, gave the last instructions and launched pressure software and cameras as the driving task began. They explained that the vehicle was an automatic car and that consequently only the right foot could be used to activate gas and brake pedals. Moreover, drivers were allowed to move in their seat during the driving session if they felt uncomfortable, while still complying with the experimenter's instructions. The itinerary was displayed on a cellphone GPS and was composed of four types of road segments: city roads (Ci), country roads (Co), highways (Hi) and mountain roads (Mo). Each road type was repeated three times at least during the itinerary, yielding 15 road segments analyzed in the chronological order presented in Fig 1. Drivers had to respect French driving rules, which included keeping their hands on the steering wheel and not exceeding speed limits. After the entire itinerary had been followed to the finishing point, data recording ended.

Seats tested

Three different seats were tested, two already commercially available and the third a prototype based on a new technology. The three seats had the same metal frame and the same mechanical adjustments, but different covers, foam densities, and absorption properties. The first seat (S₁)




Fig 1. Chronological order of road segments. Participants drove on 15 segments of 4 road types: 4 City segments (Ci), 5 Highway segments (Hi), 3 Country segments (Co), and 3 Mountain segments (Mo).

<https://doi.org/10.1371/journal.pone.0259934.g001>




Fig 2. Design details of the seats. For each seat, main geometrical dimensions and values of bearing capacity and density for the seat cushion and backrest.

<https://doi.org/10.1371/journal.pone.0259934.g002>

is a Citroën seat considered soft, covered in a classic upholstery fabric. The second (S_2) is a firmer Peugeot seat with mixed fabric and leather upholstery. The third (S_3) is the softest seat and a prototype using a suspension-enhancement technology described below. Details of dimensions and foam densities are given in Fig 2. In addition, softness was defined according to a standard test of Force vs Displacement (FvsD) conducted at CTAG (Automotive Technology Center of Galicia, Spain), which records the maximum displacements of foam under force. FvsD under the backrest was similar for the three seats but the seat cushions' FvsD differed. All FvsD results are shown in Fig 3. S_3 incorporated a vibration absorber behind the backrest, a design innovation that allows better absorption of vibrations in z-axis, using hinged bars to




Fig 3. Force vs Displacement (FvsD) for the three seats tested. A test of foam hardness was conducted at CTAG and is illustrated in the pictures. The graph illustrates the FvsD for each seat cushion and each backrest. The force was applied by a rigid dummy. For the same force applied, cushion displacement was highest for S_3 , followed by S_1 and finally S_2 , thereby defining S_3 and S_1 as soft seats and S_2 as a firm seat.

<https://doi.org/10.1371/journal.pone.0259934.g003>

enhance the car's suspension. The aim is to reduce the resonance frequency experienced by the driver, which is between 4 and 8 Hz and can be a source of discomfort [32].

Measurements

Pressure and repositioning movements. Pressure parameters and RM were analysed via the pressure system XSENSOR[®] Technology Corporation (Xsensor, Inc., Calgary, Alberta, Canada). The system consisted of two sensor pressure mats (model X3 LX100) placed on the backrest (40 x 64 sensors, 50.8 cm x 81.2 cm sensing area, mat LX 100:40.64.02) and on the cushion (40 x 40 sensors, 50.8 cm x 50.8 cm sensing area, mat LX 100:40.40.02). Using the associated software (XSENSOR Pro V8), acquisition frequency was set at 1 Hz to ensure detection of postural changes, whose frequency range is known to be lower. This system afforded a measurement range of between 0.07 and 2.7 N/cm² and a measurement threshold of 0.07 N/cm². Moreover, it provided an accuracy of ± 10 mmHg and uncertainty was calculated at ± 5.9 mmHg.

The two webcams installed, one facing the driver and one facing the road, each had a sampling frequency of 30 frames per second. The aim of the video recording was to detect repositioning movements due to feelings of discomfort as distinguished from those simply inherent to the driving task.

Perceived discomfort. Throughout the driving sessions, participants were asked to evaluate their perceived discomfort, assessing it every twenty minutes from the beginning (t_{start} at 3 min) to the end (t_{end} at 183 min) of the itinerary. A total of ten assessments were collected on two different types of discomfort. The first, whole-body perceived discomfort, was evaluated using a Visual Analogue Scale (VAS). One side of the VAS was composed of a slider that drivers could move to score their whole-body discomfort, while the other side was graduated to allow the experimenter to numerically quantify the driver's discomfort score. The second evaluation, of local discomfort, required participants to verbally report their feeling of discomfort for each body area separately (neck, upper-back, lower-back, arms, buttocks, thighs, legs, and feet). For reasons of organization and security, these verbal assessments of local perceived discomfort were recorded and scored from 0 (no discomfort) to 100 (maximum level of discomfort imaginable). Local perceived discomfort was expressed as a percentage of the maximum value given by each participant during each driving session.


Data processing

Pressure analysis. All pressure data were analyzed via a MATLAB program (vR2017a, MathWorks Inc., Natick, USA), which calculated the contact pressure (CP) and the contact surface (CS) for both pressure mats. The seat pressure distribution percentage (SPD%), representing the homogeneity of pressure distribution [33], was calculated only for the cushion mat. The lower the SPD%, the more uniform and homogeneous the pressure distribution. The first step of the analysis consisted in importing the calibration into the program so as to include the driver's weight and contours applied at the interface with each seat.

After calculation of CP and CS for the full mats, spatial cutting was performed to divide each mat in such a way as to obtain CP and CS for six cushion areas: [Right/Left Bolsters (RBo/LBo), Right/Left Buttocks (RBU/LBU) and Right/Left Thighs (RTh/LTh)] and for four backrest areas [Right/Left Upper back (RUb/LUb) and Right/Left Lowerback (RLb/LLb)] (Fig 4).

A temporal division of all pressure parameters according to time segments was performed for all subjects and all seats. Moreover, all pressure parameters were normalized in terms of time spent in each road segment according to areas under the curve for each pressure

Backrest
(64 x 40 cells)



Cushion
(40 x 40 cells)




Fig 4. Representation of pressure mat areas. Spatial division of pressure mats to analyze 4 areas for the backrest (Right/Left Upper back and Lower back) and 6 areas for the cushion (Right/Left Buttocks, Thighs and Bolsters).

<https://doi.org/10.1371/journal.pone.0259934.g004>

parameter. This was calculated as follows: AUC of segment n / time spent in segment n (sec). However, pressure parameters were not normalized in terms of driver's bodyweight due to our within-subjects design. Pressure parameters were expressed as mean \pm standard error of the mean (SEM) for each normalized road segment.

Specifications for repositioning movements. A MatLab program was used to dynamically read backrest pressure and surface data and to calculate changes in trunk posture. Only macro-movements were considered as repositioning movements. Prior to RM identification, a calculation of the force applied (F) on the backrest was performed, combining CP and CS data. Then, a sliding one-minute average was continuously calculated all along the signal of F . A comparison between the F -value of each frame at t -moment and the corresponding moving-average at the same t -moment was used to determine whether the frame was an RM. If the value of F at this t -moment exceeded 3 standard deviations (STD) from the moving-average, then the frame was considered as an RM. If the value was below 3 STD from the moving-average, the RM was defined as a *forward repositioning movement* of the trunk (FRM) because the F value was suddenly lower than the moving-average. Conversely, if the value was above 3 STD from the moving-average, the RM was defined as a *backward repositioning movement* of the trunk (BRM) because the F value was suddenly higher than the moving-average. RM frequency per minute was used to analyze FRM and BRM.

Statistical analysis

The normality of all data was tested and validated with a Shapiro-Wilk test. Then, the homogeneity of variance was verified with a Levene test. For all statistical tests, one categorical independent variable (3 seats) was used. To analyze contact pressure (CP) and contact surface (CS) for both backrest and cushion, and SPD% for cushion alone, a one-way ANOVA (15 segments) was performed. Further data on evolution of CP and CS for each area of backrest and cushion were obtained through additional repeated measures ANOVA (15 segments \times 6 cushion areas; 15 segments \times 4 backrest areas), and the frequency of RM was also analyzed using repeated measures ANOVA (15 segments \times 2 types of RM).

In addition, to analyze discomfort scores, a one-way ANOVA (10 discomfort scores) was performed both on whole-body scores and on scores for each body part. Newman-Keuls post-hoc tests were performed if a significant main effect was found. Differences were considered significant at $p < 0.05$. All statistical analyses were conducted with Statistica (v13, TIBCO Software Inc., USA). All data are reported as mean \pm SEM.

Results

Cushion

Full cushion mat. For CP, a SEAT \times SEGMENT interaction effect was observed ($F_{(28,560)} = 1.84$; $p < 0.01$). For all three seats, there was no statistical difference between any two successive road segments, except between C_{i1} and H_{i1} (Fig 5A). The post-hoc test revealed a lower CP in H_{i1} compared to other highway segments for S_1 and S_3 ($p < 0.05$). For S_2 , CP was lower in the first six (C_{i1} , H_{i1} , C_{o1} , M_{o1} , H_{i2} and C_{i2}) than in the later segments of a given road type ($p < 0.05$).

Regarding CS and SPD%, a main SEGMENT effect was observed ($F_{(14,560)} = 6.55$; $p < 0.001$ and $F_{(14,560)} = 13.00$; $p < 0.001$, respectively) (Fig 5B). Whatever the seat, post-hoc testing




Fig 5. Pressure parameter evolution on full cushion mat for each road segment. A) Evolution of CP. B) Evolution of CS. * represents significant differences between segments for the same road type (*: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$). Colored * represents one seat, black * represents three seats. § represents significant differences between two successive segments (§: $p < 0.05$; §§: $p < 0.01$; §§§: $p < 0.001$).

<https://doi.org/10.1371/journal.pone.0259934.g005>

revealed significant differences between the three first successive segments with higher CS in Ci1 than in Hi1 and lower CS in Hi1 than in Co1 ($p < 0.05$). Whatever the seat, post-hoc tests revealed higher CS in Ci1 than in all subsequent city segments ($p < 0.01$) and lower CS in Hi1 than in all subsequent highway segments ($p < 0.01$). Post-hoc tests showed a higher SPD% in Ci1 than in subsequent city segments ($p < 0.01$), a higher SPD% in Co2 than in Co3 ($p < 0.001$), and a higher SPD% in Hi3 than in Hi4 ($p < 0.05$). In contrast, SPD% was lower in Hi2 than in all other highway segments ($p < 0.05$) (Fig 6).

Seat Pressure Distribution Percentage (SPD%)




Fig 6. Evolution of SPD%. Evolution of the uniformity or pressure distribution represents with SPD% score. * represents significant differences between segments for the same road type (*: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$).

<https://doi.org/10.1371/journal.pone.0259934.g006>

Distribution of Contact Pressure (CP)




Fig 7. CP profiles. Distribution of CP by area of backrest and cushion. Each shade of color represents a significant difference ($p < 0.05$).

<https://doi.org/10.1371/journal.pone.0259934.g007>

Areas of cushion mat. For CP, an AREAxSEAT interaction effect was found ($F_{(10,200)} = 2.52; p < 0.01$). Whatever the road segment, post-hoc tests revealed that both bolsters (RBo and LBo) of S_1 had a lower CP than the other seat cushion areas ($p < 0.001$). For S_2 and S_3 , CP in RBo and LBo were lower than in both thighs (RTh and LTh) and buttocks (RBU and LBU) ($p < 0.01$ with S_2 ; $p < 0.001$ with S_3). Moreover, both seats showed higher CP in RTh and LTh than in RBU and LBU ($p < 0.05$; see Fig 7 for detailed breakdown of CP and statistical differences for the three seats).

In addition, an AREAxSEGMENT interaction effect ($F_{(70,2800)} = 6.99; p < 0.001$) was also observed on CP. Post-hoc tests indicated that whatever the seat, CP for all seat areas was significantly lower in Hi_1 and Co_1 than in all subsequent highway segments (Hi_2, Hi_3, Hi_4, Hi_5) and country segments (Co_2, Co_3) ($p < 0.001$). In highway segments, CP for RBU and RTh increased with time, showing significantly higher values with successive highway segments ($Hi_1 < Hi_2 < Hi_3 < Hi_4 < Hi_5; p < 0.001$). Regarding the four other areas of the seat cushion (LBU, LTh, RBo, LBo), CP was lower in Hi_2 than in $Hi_3, Hi_4,$ and Hi_5 ($p < 0.001$). Except for RBo and RBU, all seat cushion areas showed lower CP in Mo_1 than in the subsequent mountain segments (Mo_2 and $Mo_3; p < 0.001$). CP values in Ci_1 were significantly lower than in all subsequent city segments (Ci_2, Ci_3, Ci_4) for RBo ($p < 0.001$) and lower than in Ci_3 for RTh ($p < 0.001$). In Ci_2 , CP values were also lower than in Ci_3 for LBU, RBo, and LBo ($p < 0.001$).

Regarding CS, seat cushion measurements indicated an AREAxSEAT interaction effect ($F_{(10,200)} = 5.75; p < 0.001$). Whatever the road segment, post-hoc tests showed lower CS in RBo for S_3 than for S_1 and S_2 ($p < 0.01$). In addition, S_3 had higher CS in RTh than S_1 and S_2 ($p < 0.05$), but lower CS in LTh than S_1 ($p < 0.05$). With S_1 , CS was higher in RTh than in all




Fig 8. CS profiles. Distribution of CS by area of backrest and cushion. Each shade of color represents a significant difference ($p < 0.05$).

<https://doi.org/10.1371/journal.pone.0259934.g008>

other areas ($p < 0.05$), and was also significantly higher in LTh than in RBu, LBU, RBo and LBo ($p < 0.01$). S_2 showed significantly higher CS in RTh and LTh than in other areas. S_3 showed lower CS in RBo and LBo than in thighs and buttocks ($p < 0.001$), significantly lower CS in RBu and LBU than in thighs ($p < 0.01$), and significantly higher CS in RTh than in LTh ($p < 0.001$; see Fig 8 for details of CS distribution and significant differences for the three seats).

CS values were also influenced by an AREAxSEGMENT interaction effect ($F_{(70,2800)} = 12.80$; $p < 0.001$). Post-hoc tests showed that whatever the seat, CS for all seat areas except bolsters was significantly higher in Ci_1 than in all subsequent city segments (Ci_2, Ci_3, Ci_4 , $p < 0.001$). In Hi_1 , CS in bolsters and thighs was lower than in Hi_3, Hi_4 , and Hi_5 ($p < 0.05$), and significantly lower in Hi_2 than in subsequent highway segments (Hi_3, Hi_4 , and Hi_5 ; $p < 0.01$). In Co_1 , CS for RBo alone was significantly lower than in Co_2 and Co_3 ($p < 0.001$). In Mo_1 , CS for LBo was lower than in other mountain segments (Mo_2 and Mo_3 , $p < 0.01$).

Backrest

Full backrest mat. A main SEGMENT effect was observed for CP ($F_{(14,560)} = 22.22$; $p < 0.001$) (Fig 9A). Whatever the seat, CP was higher in Ci_3 than in Ci_1 ($p < 0.05$) and Ci_2 ($p < 0.001$) but lower than in Ci_4 ($p < 0.001$). CP was significantly lower in Hi_1 than in all subsequent highway segments ($p < 0.05$). For country and mountain segments, CP significantly increased with time. CP was lower in Co_1 than in Co_2 ($p < 0.001$) and these two first country segments had lower CP than Co_3 ($p < 0.001$). CP was lower in Mo_1 than in Mo_2 ($p < 0.001$) and these two first mountain segments had lower CP than Mo_3 ($p < 0.001$).

Backrest measurements of CS indicated a SEATxSEGMENT interaction effect ($F_{(28,560)} = 1.75$; $p < 0.05$) (Fig 9B). Post-hoc tests revealed that S_1 showed significantly higher CS than S_2




Fig 9. Pressure parameter evolution on full backrest mat for each road segment. A) Evolution of CP. B) Evolution of CS. Symbol * represents significant differences between segments for the same road type (*: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$). Colored * represents one seat, black * represents three seats. § represents significant differences between two successive segments (§: $p < 0.05$; §§: $p < 0.01$; §§§: $p < 0.001$). □ represents significant differences between seats (□: $p < 0.05$; □□: $p < 0.01$; □□□: $p < 0.001$).

<https://doi.org/10.1371/journal.pone.0259934.g009>

and S₃ throughout the driving session ($p < 0.05$). When road segments were compared, S₁ showed lower CS in Ci₄ than in the preceding city segments (Ci₁, Ci₂ and Ci₃; $p < 0.05$). For S₃, CS was lower in the first segments (Hi₁, Co₁ and Mo₁) than, respectively, in the last highway (Hi₅; $p < 0.001$), last country (Co₃; $p < 0.001$) and last mountain segments (Mo₃, $p < 0.05$).

Areas of backrest. For the backrest, an AREAxSEGMENT interaction effect was observed for CP ($F_{(42,1680)} = 6.36$; $p < 0.001$). Post-hoc tests indicated that whatever the seat, the Right Upperback (RUB) showed lower CP than the other areas of the backrest (LUB, RLB & LLB; $p < 0.01$) (Fig 7). Comparing road segments, post-hoc tests showed that CP was higher in Co₃ than in the preceding country road segments ($p < 0.01$). Moreover, Mo₃ also showed higher CP than the preceding mountain segments for LUB, RUB and RLB ($p < 0.01$). In the last two highway segments (Hi₄ and Hi₅), CP for RUB was higher than in the preceding ones ($p < 0.01$). The LUB CP was also higher in Ci₃ than in Ci₁ and Ci₂ ($p < 0.01$). In contrast, the RLB CP was higher in Ci₁ than in Ci₂ and Ci₄ ($p < 0.001$), and higher in Ci₃ than in Ci₄ ($p < 0.05$).

An AREAxSEGMENT interaction effect was observed for CS ($F_{(42,1680)} = 9.31$; $p < 0.001$) (Fig 8). RUB showed lower CS than other backrest areas ($p < 0.05$). In highway segments, CS for RUB increased with time (Hi₁ < Hi₂ < Hi₃ < Hi₄ < Hi₅; $p < 0.05$). In mountain segments, CS for LUB and RUB increased with time (Mo₁ < Mo₂ < Mo₃; $p < 0.05$). In city segments, CS for LUB and RUB were higher in Ci₃ than in Ci₁ and Ci₂ ($p < 0.05$). In country segments, CS for LUB and RUB were lower in Co₁ than in Co₂ and Co₃ ($p < 0.05$). However, CS for RLB was higher in Ci₁ than in Ci₂, Ci₃ and Ci₄ ($p < 0.01$).

Repositioning movements. Concerning RM frequency, our results indicated an interaction effect from TYPE OF RMxSEGMENTxSEAT ($F_{(28,560)} = 2.42$; $p < 0.001$) (Fig 10).

Only a significant difference between seats was observed. S₂ showed higher frequency of BRM and FRM than S₁ and S₃ ($p < 0.001$). Moreover, S₃ frequency of FRM was higher in Ci₄ than in Ci₁ ($p < 0.05$) and also higher in Hi₂ than in all other highway segments ($p < 0.001$).

Discomfort

A main effect of TIME ($F_{(9,369)} = 69.09$; $p < 0.001$) was observed on whole-body discomfort scores. Post-hoc tests showed that, for all seats, the discomfort score at the first evaluation




Fig 10. Frequency of RM for each road segment. A) Backward RM. B) Forward RM. * represents significant differences between segments for the same road type (*: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$). Colored * represents one seat, black * represents three seats. § represents significant differences between two successive segments (§: $p < 0.05$; §§: $p < 0.01$; §§§: $p < 0.001$). □ represents significant differences between seats (□: $p < 0.05$; □□: $p < 0.01$; □□□: $p < 0.001$).

<https://doi.org/10.1371/journal.pone.0259934.g010>

(t_{start}) was significantly lower than at all subsequent discomfort assessments (from $t_{23 \text{ min}}$ to t_{end} ; $p < 0.001$) (Fig 11A).

A TIMExBODYPART interaction effect was observed on evolution of discomfort scores for each body part ($F_{(108,4428)} = 1.64$; $p < 0.001$). For all body parts and all seats, perceived discomfort increased throughout the driving session. However, the time when this increase began depended on the body part. Post-hoc tests revealed that discomfort appeared earlier for the neck, upperback, arms, and feet, with significant differences from t_{start} discomfort score appearing from t_4 (63 minutes) to the end of the driving session. Discomfort scores for the buttocks, right thigh, and legs began to differ from the t_{start} score at t_5 (83 minutes). Finally, the left thigh and lowerback were the last body parts where discomfort was perceived, their score beginning to differ from the t_{start} score at t_6 (103 minutes). The highest perceived discomfort scores were for both arms, neck, and lowerback (Fig 11B).

Discussion

The main objective of this study was to define drivers' sitting behavior and perceptions of discomfort when using different seats under real prolonged driving conditions on a variety of road types. Our results confirm previous findings of an effect from foam hardness on contact pressure and pressure distribution [34, 35]. The firmest of the seats tested here (S_2) led to higher CP and SPD% than the soft seat (S_1) and the seat with a suspension system (S_3). In terms of perceived discomfort, S_3 with its suspension system kept local discomfort to a minimum, although all three seats led to a similar general increase in discomfort.

Analysis of interface pressure between driver and car seat

Interface pressure recorded instantaneously can be used to describe the sitting of the driver with different seats [36, 37]. Pressure distribution, changes in pressure distribution and whole-body vibrations (WBV) are the main factors in sitting discomfort [28]. Using pressure measurements, we found that overall, the driver's sitting behavior depended on several factors such as seat characteristics, road dynamics, and driving time. Although all three seats' backrests showed the same CP and CS distribution profiles, with lower values for the right upper back (RUB), their distribution profiles differed for the seat cushion. Softness is known to induce a higher CS and to minimize pressure peaks under ischial tuberosities, including when there are vibrations [35, 38]. In our study, while no differences in cushion CS were observed

A. Whole - Body Discomfort



B. Local discomfort
Percentage of maximal score

Fig 11. Perceived discomfort. A) Mean scores for whole-body discomfort throughout driving session. Significant increases in discomfort compared to score at t_1 are represented by ***: $p < 0.001$. B) Visual representation of mean of local discomfort. A color scale shows scores as a percentage of maximum values for each body part.

<https://doi.org/10.1371/journal.pone.0259934.g011>

between the three seats, the S3 distribution profile showed differences between left and right thighs, and between buttocks and bolsters. The CP distribution profiles of S₂ and S₃ were similar, with CP highest under the thighs, as already observed by Zenk et al. [39]. However, S₁ showed uniform CP distribution between buttocks and thighs. S₂ showed higher CP and higher SPD% on the full cushion mat, which confirmed its firmness. Thus, S₂ could engender a higher risk of soreness and fatigue, particularly for buttocks and thighs, because of soft tissue compression at these locations [13, 40]. Moreover, Vink & Lips [41] indicated that the contact

area at the front of the seat cushion, corresponding to the lower thigh, is more sensitive and could induce additional pain in the legs and feet [28]. The compression caused by the contact constraints of prolonged driving was found to lead to static muscle contractions and a constriction of blood circulation in the lower limbs that can become painful [42]. A prolonged period of driving was reported to require initial adjustments to find a good posture combining physical and environmental constraints [43].

Our results reveal that the cushion CP of S_2 during the first four segments (C_{i1} , H_{i1} , Co_1 , Mo_1) differed from that of subsequent segments, becoming stable from the second highway segment (after approximately 1 hour of driving) to the end of the drive. On the other hand, for S_1 and S_3 , CP increased only in highway segments, where it was significantly lower in H_{i1} . Concerning CS, the same stabilization was observed after the first two road segments, whatever the seat. These results are consistent with previous studies demonstrating some sitting adjustments during the early phases of the drive [25, 44]. However, these initial adaptations to the seat cushion do not prevent postural fixity for long periods. Maintaining a prolonged driving posture reduces opportunities for movement due to the need to reach commands [12]. Moreover, a stable sitting posture increases contact points and contact surface while decreasing the degree of freedom for movements [10]. Previous studies demonstrated that an increase in repositioning movements (RM) with driving time is clearly associated with the onset of discomfort [19] and used to provide relief from static posture [11]. RM are unconscious, a means to relieve pressure under the soft tissues of the back, buttocks, and thighs, to continue minimizing intervertebral disc loading, and to induce changes in muscle contractions [20]. In our study, backrest pressure data allowed us to identify RM through variations that correspond to a dynamic behaviour, time-dependent and occurring from 30 minutes into the drive [18, 19, 37]. But our findings do not show an effect of the seat, nor of the road segment.

In addition, cushion hardness, composition, and the resulting contact area also have an impact on trunk support. Mergl et al. [45] recommended a firmer cushion to avoid back discomfort even if this meant higher CP under buttocks and thighs. Our findings show that the firmness of S_2 induced backrest CP similar to that of S_1 throughout the driving session but applied over a significantly smaller contact area, while S_3 presented the lowest backrest CP and CS. In a study by Carcone & Keir [46], participants, regardless of their stature, preferred backrests with low contact pressure. Using pressure parameters here helped to highlight the major impact of seat hardness over time, with both sitting behavior and perceived discomfort evolving throughout the driving session.

Postural discomfort of driver

Driver discomfort is a predictor of the onset of pain in the neck, back, buttocks, and thighs [47]. Mansfield et al. [29] demonstrated that WBV induced higher discomfort ratings than static conditions. Vibrations are transmitted to the driver through the seat, pedals, and steering wheel in real driving conditions [14]. These multiple sources of vibrations, added to postural fixity, foam composition, shape of seat, and individual driver characteristics, are factors that automotive companies need to take into account to optimize the static and dynamic characteristics of the seat [17]. As previously demonstrated [14, 19, 20], the level of whole-body discomfort increased with driving time in our study, whatever the seat. From the second assessment on (t_{23min}), discomfort scores became significantly higher than the first scores (t_{3min}). Under ideal road conditions and with high-quality vehicle suspension systems, the magnitude of the vibrations perceived through the seat can be low [13]. In our study, road quality was unpredictable, as in real driving conditions, with alternating smooth and rough segments that induced different levels of WBV. S_3 , incorporating a suspension system in the backrest to

optimize the dynamic seat characteristics and improve driver comfort, offered better absorption of vibrations in z -axis. Unexpectedly, however, S_3 did not minimize general perceived discomfort, engendering a level of whole-body discomfort similar to S_1 and S_2 at the end of the driving task, no doubt due to the muscular and biomechanical consequences of prolonged driving posture. While different types of seats generate different muscular adaptations, drivers may have difficulty differentiating between seats in terms of perceived discomfort. Gyi & Porter [48] reported that a minimum of two hours' driving is required to differentiate between seats. Lecocq et al. [49] therefore suggested that muscular adaptations linked to seat features are a better way to differentiate between seats than perceived discomfort. Nevertheless, significantly less local discomfort was found with S_3 here for all body parts except the lower back, no doubt because this prototype was designed for improved suspension and not back support. This seat therefore appears to be more effective in reducing local discomfort than S_1 and S_2 , but there is room for improvement to reduce general discomfort and avoid back pain.

Automotive design implications

Car seat designers are faced with making a compromise between producing seats that delay the onset of static discomfort while avoiding vibration discomfort by minimizing WBV [9]. This balance between static and dynamic factors can be achieved by taking into account the following: drivers' anthropometry, seat design, and driving environment [1, 8]. Currently, designing cockpits based on driver stature alone is not feasible because it would involve customization to each driver's characteristics. For example, height, body mass index, hip circumference, and even age or gender all have an impact on sitting posture, notably on pressure parameters [50, 51]. In addition, psychosocial factors like aesthetic or emotional reactions may affect the driver's perceived comfort [7]. However, manufacturers are trying to prevent the detrimental physical consequences of prolonged posture, like discomfort, fatigue, or pain. Romelfanger & Kolich [52] used big data analytics to underline the importance of considering thigh length in seat design. The hardness of foam was reported to contribute to biceps femoris support and consequently to the loading suffered in the lower back [39]. Lecocq et al. [49] found that firm foam (like that of S_2) offered better trunk support and delayed fatigue in the back muscles. Neuromuscular fatigue during driving is linked to peripheral and central mechanisms involved in maintaining posture and attention. Therefore, changes in road environment, particularly in visual demands and road curvatures, generate variations in the driver's attention and may cause central fatigue [53]. Greater stability and better support could be offered by reinforced bolsters [31], which might help to reduce this fatigue. Highways, being straight roads, were found to cause performance deterioration through making lower task demands than curved roads. Conversely, mountain roads led to greater engagement in the task but worse pressure distribution on the seat cushion, with higher SPD% [54]. Moreover, the backrest CP of the soft seats (S_1 & S_3) varied only for highway segments, whereas the firm seat (S_2) fulfilled its support function on all road types, with positioning adjustments only at the beginning of the driving session. Pressure parameters seem appropriate to our approach to testing the driver's response to the seats on different road types, since they reveal positioning adjustments. This worked particularly well in distinguishing between straight and curved roads, although the distinction between country and city roads was likely complicated by the fact that these road types necessitated more varied lateral and longitudinal accelerations.

Given all the above factors, it might be worth exploring an approach to car seat design that combines softness under the buttocks and thighs to avoid critical pressure points with firmness in the backrest and bolsters to support the trunk and the pelvis. This compromise between reducing contact pressure and providing support might well reduce perceived discomfort.

Seat S₃ combined these characteristics by offering a soft cushion and low CP and CS on the backrest, doubtless due to its suspension system. Although none of the seats attenuated whole-body discomfort over time, the suspension system had a positive effect on local discomfort by decreasing WBV in *z*-axis. Baucher & Leborgne [10] recommended respecting drivers' spinal curvatures and suggested that mobility should be encouraged by the seat design. The authors explained that alternating pressure constraints can minimize muscle fatigue and promote fidgeting movements. Fidgeting is recognized as beneficial, helping the driver to feel refreshed by relieving compression that can impede blood flow [19, 20]. Several dynamic solutions have been proposed to make drivers vary their position during driving. For example [11, 55], an integrated seat system with continuous variation of backrest or seat pan angle was shown to reduce perceived discomfort by fostering body movements. This kind of dynamic system, in combination with a seat design incorporating a suspension system for reduced discomfort, may enhance the prolonged driving experience.

Limitations of the study

The main limitation of this dynamic experiment comes from not recording accelerations. To determine and to highlight the magnitude of WBV, lateral, and longitudinal accelerations, the use of tri-axial accelerometers should be considered. First, this additional device placed on the driver might allow more accurate detection of RM in the three planes of motion [56]. Second, accelerometers placed on the seat and on the car floor could provide objective data to better characterize the different road types. Measuring three-dimensional accelerations from each road segment at different levels (car, seat, and driver) might provide more precise input on the influence of different road types on discomfort. Moreover, this on-board equipment would also allow the speed of the vehicle and its variations to be considered. Kim et al. [57] evaluated the effect of accelerations, decelerations, and curves on shear-forces at the seating interface, using a dummy with several sensors. The authors showed that as vehicle speed increased, so did the shear-forces. Variations in pressure parameters, especially the pressure distribution represented by SPD%, could therefore be partly attributed to variations in velocity and associated shear-forces.

The advantage of our experiment, conducted under real driving conditions, lies in exploiting dynamic conditions representative of the driving environment, rarely explored in the literature. However, by the same token, our experiment is exposed to certain disadvantages since stochastic conditions are more random than those in the laboratory. The differing lengths of time spent in the different road segments, the route-dependent sequencing of segments, and traffic conditions may all interfere with the interpretation of results regarding the four road types. In terms of arm discomfort, moreover, even though the experiment was conducted in real-world conditions, we required drivers to keep their hands on the wheel, which may have affected arm discomfort ratings. Most of the participants are used to driving with a manual transmission and maneuvering alternately with one or two hands, which would explain why this result was obtained for all 3 seats. Finally, the limited sample did not allow us to distinguish anthropometric sub-groups and to evaluate the effect of size or weight. Anthropometry, especially weight and skin surface, are predictors of contact surface [58]. For the above reasons, we believe that future studies taking into account anthropometry, accelerations, and interface parameters would provide even more accurate seat design guidelines for manufacturers [59].

Conclusion

The aim of this study was to contribute to current recommendations by elucidating the effects of foam hardness, absorption capacities, and road types on drivers' sitting behavior. We

observed a difference in these three seats' impact on pressure parameters under dynamic conditions. In real driving conditions, there was a difference between firm and soft seats S_1 and S_2 , with higher CS on the backrest for S_1 , likely due to drivers' sitting deeper in the seat and leaning more against the backrest. In addition, even though no difference in CP and CS was observed between the three seat cushions, the suspension system in S_3 reduced local discomfort, especially under buttocks and thighs. However, this seat still needs to be further optimized to mitigate the effect of a prolonged sitting posture, since general discomfort increased with driving time despite the suspension system. Future research should be directed toward supplementary features integrated into the seat to foster movement by drivers. In addition to suspension systems, better support on curved roads, and enhanced pressure distribution under buttocks and thighs could mitigate discomfort from prolonged driving, particularly in the lower back.

Acknowledgments

The present study was supported by the OpenLab "Automotive Motion Lab" which is a collaborative structure involving Aix-Marseille University, CNRS, and Groupe Stellantis. We would like to thank Serge Tribut, Julien Bonnet, John Masson, Antonio Gomes and Christophe Broquet from Groupe PSA for their work on the vehicle and on the seats. Our thanks to Issam Rosti (ALTRAN, Morocco) for his help with the Matlab analysis, and to Marjorie Sweetko for English language editing.

Author Contributions

Conceptualization: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Laurent Bauvineau, Serge Mesure.

Data curation: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Formal analysis: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Laurent Bauvineau, Serge Mesure.

Funding acquisition: Clément Bougard, Christophe Bourdin, Laurent Bauvineau, Serge Mesure.

Investigation: Pascaline Lantoine, Mathieu Lecocq, Jean-Marc Allègre, Laurent Bauvineau.

Methodology: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Project administration: Pascaline Lantoine, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Resources: Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Software: Pascaline Lantoine, Mathieu Lecocq, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Supervision: Clément Bougard, Laurent Bauvineau, Serge Mesure.

Validation: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Laurent Bauvineau, Serge Mesure.

Visualization: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Serge Mesure.

Writing – original draft: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Jean-Marc Allègre, Laurent Bauvineau, Serge Mesure.

Writing – review & editing: Pascaline Lantoine, Mathieu Lecocq, Clément Bougard, Erick Dousset, Tanguy Marqueste, Christophe Bourdin, Serge Mesure.

References

1. Hiemstra-van Mastrigt S, Groenesteijn L, Vink P, Kuijt-Evers LFM. Predicting passenger seat comfort and discomfort on the basis of human, context and seat characteristics: a literature review. *Ergonomics*. 2017 Jul 3; 60(7):889–911. <https://doi.org/10.1080/00140139.2016.1233356> PMID: 27633349
2. European Commission. Joint Research Centre. Institute for Energy and Transport. Driving and parking patterns of European car drivers: a mobility survey. [Internet]. LU: Publications Office; 2012. Available from: <https://data.europa.eu/doi/10.2790/7028>
3. Battié MC, Videman T, Gibbons LE, Manninen H, Gill K, Pope M, et al. Occupational driving and lumbar disc degeneration: a casecontrol study. *The Lancet*. 2002 Nov; 360(9343):1369–74. [https://doi.org/10.1016/S0140-6736\(02\)11399-7](https://doi.org/10.1016/S0140-6736(02)11399-7)
4. Dankaerts W, O'Sullivan P, Burnett A, Straker L. Altered patterns of superficial trunk muscle activation during sitting in nonspecific chronic low back pain patients: importance of subclassification. *Spine*. 2006 Aug; 31(17):2017–23. <https://doi.org/10.1097/01.brs.0000228728.11076.82> PMID: 16924221
5. Kyung G, Nussbaum MA, Babski-Reeves K. Driver sitting comfort and discomfort (part I): Use of subjective ratings in discriminating car seats and correspondence among ratings. *Int J Ind Ergon*. 2008 May; 38(5–6):516–25. <https://doi.org/10.1016/j.ergon.2007.08.010>
6. Lis AM, Black KM, Korn H, Nordin M. Association between sitting and occupational LBP. *Eur Spine J*. 2007 Feb; 16(2):283–98. <https://doi.org/10.1007/s00586-006-0143-7> PMID: 16736200
7. De Looze MP, Kuijt-Evers LFM, Van Dieën J. Sitting comfort and discomfort and the relationships with objective measures. *Ergonomics*. 2003 Aug; 46(10):985–97. <https://doi.org/10.1080/0014013031000121977> PMID: 12850935
8. Vink P, Hallbeck S. Editorial: Comfort and discomfort studies demonstrate the need for a new model. *Appl Ergon*. 2012 Mar; 43(2):271–6. <https://doi.org/https://doi.org/10.1016/j.apergo.2011.06.001>
9. Ebe K, Griffin MJ. Quantitative prediction of overall seat discomfort. *Ergonomics*. 2000 Jun; 43(6):791–806. <https://doi.org/10.1080/001401300404751> PMID: 10902888
10. Baucher J, Leborgne P. Application d'une approche transversale de l'appareil locomoteur au confort siège. *ITBM-RBM*. 2006 Jul; 27(3):133–40. <https://doi.org/10.1016/j.rbmet.2006.05.002> French.
11. Maradei F, Quintana L, Castellanos J. Influence of seat tilt motion on discomfort perception during a simulated driving activity. *Work*. 2017 Feb 6; 56(1):99–110. <https://doi.org/10.3233/WOR-162464> PMID: 28128777
12. Grieco A. Sitting posture: an old problem and a new one. *Ergonomics*. 1986 Mar; 29(3):345–62. <https://doi.org/10.1080/00140138608968270> PMID: 3698964
13. Kolich M, Taboun S. Ergonomics modelling and evaluation of automobile seat comfort. *Ergonomics*. 2004 Jun 22; 47(8):841–63. <https://doi.org/10.1080/0014013042000193273> PMID: 15204278
14. El Falou W, Duchêne J, Grabisch M, Hewson D, Langeron Y, Lino F. Evaluation of driver discomfort during long-duration car driving. *Appl Ergon*. 2003 May; 34(3):249–55. [https://doi.org/10.1016/S0003-6870\(03\)00011-5](https://doi.org/10.1016/S0003-6870(03)00011-5) PMID: 12737925
15. Philip P, Taillard J, Guilleminault C, Quera S, Bioulac B, Ohayon M. Long distance driving and self-induced sleep deprivation among automobile drivers. *Sleep*. 1999 Jun; 22(4):475–80. <https://doi.org/10.1093/sleep/22.4.475> PMID: 10389223
16. Bordignon M, Cutini M, Bisaglia C, Taboga P, Marcolin F, Antonutto G. Evaluation of Agricultural Tractor Seat Comfort with a New Protocol Based on Pressure Distribution Assessment. *J Agric Saf Health*. 2018; 24(1):13–26. <https://doi.org/10.13031/jash.12209> PMID: 29528603
17. Mansfield NJ, Mackrill J, Rimell AN, MacMull SJ. Combined Effects of Long-Term Sitting and Whole-Body Vibration on Discomfort Onset for Vehicle Occupants. *ISRN Automot Eng*. 2014 Jan 2; 2014:1–8. <http://dx.doi.org/10.1155/2014/852607>
18. Anne Fenety P, Putnam C, Walker JM. In-chair movement: validity, reliability and implications for measuring sitting discomfort. *Appl Ergon*. 2000 Aug; 31(4):383–93. [https://doi.org/10.1016/s0003-6870\(00\)0003-x](https://doi.org/10.1016/s0003-6870(00)0003-x) PMID: 10975665

19. Sammonds GM, Fray M, Mansfield NJ. Effect of long term driving on driver discomfort and its relationship with seat fidgets and movements (SFM). *Appl Ergon*. 2017 Jan; 58:119–27. <https://doi.org/10.1016/j.apergo.2016.05.009> PMID: 27633204
20. Varela M, Gyi D, Mansfield N, Picton R, Hirao A, Furuya T. Engineering movement into automotive seating: Does the driver feel more comfortable and refreshed? *Appl Ergon*. 2019 Jan; 74:214–20. <https://doi.org/10.1016/j.apergo.2018.08.024> PMID: 30487102
21. Vergara M, Page Á. Relationship between comfort and back posture and mobility in sitting-posture. *Appl Ergon*. 2002 Jan; 33(1):1–8. [https://doi.org/10.1016/s0003-6870\(01\)00056-4](https://doi.org/10.1016/s0003-6870(01)00056-4) PMID: 11827133
22. Andreoni G, Santambrogio GC, Rabuffetti M, Pedotti A. Method for the analysis of posture and interface pressure of car drivers. *Appl Ergon*. 2002 Nov; 33(6):511–22. [https://doi.org/10.1016/s0003-6870\(02\)00069-8](https://doi.org/10.1016/s0003-6870(02)00069-8) PMID: 12507335
23. Na S, Lim S, Choi H-S, Chung MK. Evaluation of driver's discomfort and postural change using dynamic body pressure distribution. *Int J Ind Ergon*. 2005 Dec; 35(12):1085–96. <https://doi.org/10.1016/j.ergon.2005.03.004>
24. Makhsous M, Lin F, Hanawalt D, Kruger SL, LaMantia A. The effect of chair designs on sitting pressure distribution and tissue perfusion. *Hum Factors J Hum Factors Ergon Soc*. 2012 Dec; 54(6):1066–74. <https://doi.org/10.1177/0018720812457681> PMID: 23397814
25. Adler S. The relation between long-term seating comfort and driver movement [dissertation]. Dipl.-Sportwiss: Friedrich-Schiller-Universität Jena; 2017.
26. Jagannath M, Balasubramanian V. Assessment of early onset of driver fatigue using multimodal fatigue measures in a static simulator. *Appl Ergon*. 2014 Jul; 45(4):1140–7. <https://doi.org/10.1016/j.apergo.2014.02.001> PMID: 24581559
27. Reed MP, Manary MA, Flannagan CAC, Schneider LW. A statistical method for predicting automobile driving posture. *Hum Factors J Hum Factors Ergon Soc*. 2002 Dec; 44(4):557–68. <https://doi.org/10.1518/0018720024496917> PMID: 12691365
28. Mandal M, Maity A, Prasad A. Automotive seat design: basic aspects. *Innov J*. 2015; 4(5):62–8. <http://dx.doi.org/10.15520/ajcem.2015.vol4.iss5.35.pp62-68>
29. Mansfield N, Sammonds G, Nguyen L. Driver discomfort in vehicle seats—Effect of changing road conditions and seat foam composition. *Appl Ergon*. 2015 Sep; 50:153–9. <https://doi.org/10.1016/j.apergo.2015.03.010> PMID: 25959330
30. Kim JH, Dennerlein JT, Johnson PW. The effect of a multi-axis suspension on whole body vibration exposures and physical stress in the neck and low back in agricultural tractor applications. *Appl Ergon*. 2018 Apr; 68:80–9. <https://doi.org/10.1016/j.apergo.2017.10.021> PMID: 29409658
31. Mehta CR, Tewari VK. Seating discomfort for tractor operators—a critical review. *Int J Ind Ergon*. 2000 Jul; 25(6):661–74. [https://doi.org/10.1016/S0169-8141\(99\)00054-2](https://doi.org/10.1016/S0169-8141(99)00054-2)
32. Liang C-C, Chiang C-F. Modeling of a seated human body exposed to vertical vibrations in various automotive postures. *Ind Health*. 2008; 13:125–37. <https://doi.org/10.2486/indhealth.46.125> PMID: 18413965
33. Ahmadian M, Seigler TM, Clapper D, Sprouse A. Alternative test methods for long term dynamic effects of vehicle seats. SAE Technical Paper Series. 2002–01–3082. Available from: <https://www.sae.org/content/2002-01-3082/>
34. Khamis NK, Tee NC, Tahir MFM, Sabri N. Pattern of pressure distribution on the car seat under static condition and its relationship with driving posture. *Int J Innov Technol Explor Eng*. 2019 Oct 10; 8(12):4189–94. <https://doi.org/10.35940/ijitee.L3668.1081219>
35. Kilincsoy U, Wagner A, Vink P, Bubbs H. Application of ideal pressure distribution in development process of automobile seats. Vink P, Bazley CM, Jacobs K, editors. *Work*. 2016 Sep 1; 54(4):895–904. <https://doi.org/10.3233/WOR-162350> PMID: 27447412
36. Daruis DDI, Deros BM, Nor MJM, Hosseini Fouladi M. Relationship between objective and subjective methods in evaluating static discomfort of car driver seat. *Adv Mater Res*. 2012 Jan; 433–440:4997–5003. <https://doi.org/10.4028/www.scientific.net/amr.433-440.4997>
37. Jackson C, Emck AJ, Hunston MJ, Jarvis PC. Pressure Measurements and Comfort of Foam Safety Cushions for Confined Seating. *Aviat Space Environ Med*. 2009 Jun 1; 80(6):565–9. <https://doi.org/10.3357/asem.2320.2009> PMID: 19522369
38. Wu X, Rakheja S, Boileau P-É. Distribution of human–seat interface pressure on a soft automotive seat under vertical vibration. *Int J Ind Ergon*. 1999 Sep; 24(5):545–57. [https://doi.org/10.1016/S0169-8141\(98\)00058-4](https://doi.org/10.1016/S0169-8141(98)00058-4)
39. Zenk R, Franz M, Bubbs H, Vink P. Technical note: Spine loading in automotive seating. *Appl Ergon*. 2012 Mar; 43(2):290–5. <https://doi.org/10.1016/j.apergo.2011.06.004> PMID: 21745653

40. Reenalda J, Van Geffen P, Nederhand M, Jannink M, IJzerman M, Rietman H. Analysis of healthy sitting behavior: Interface pressure distribution and subcutaneous tissue oxygenation. *J Rehabil Res Dev*. 2009; 46(5):577. <https://doi.org/10.1682/jrrd.2008.12.0164> PMID: 19882492
41. Vink P, Lips D. Sensitivity of the human back and buttocks: The missing link in comfort seat design. *Appl Ergon*. 2017 Jan; 58:287–92. <https://doi.org/10.1016/j.apergo.2016.07.004> PMID: 27633224
42. Kolich M, Taboun SM. Combining Psychophysical Measures of Discomfort and Electromyography for the Evaluation of a New Automotive Seating Concept. *Int J Occup Saf Ergon*. 2002 Jan; 8(4):483–96. <https://doi.org/10.1080/10803548.2002.11076549> PMID: 12427352
43. Reed M, Manary MA, Schneider LW. Methods for Measuring and Representing Automobile Occupant Posture. SAE Technical Paper Series. 1999–01–0959. Available from: <https://www.sae.org/content/1999-01-0959/>
44. Vink P. The sweetness of discomfort designing the journey. 2014. Available from: <http://resolver.tudelft.nl/uuid:517db1ea-9e10-4ba7-9bae-f012698eddb3>
45. Mergl C, Klendauer M, Mangen C, Bubb H. Predicting long term riding comfort in cars by contact forces between human and seat. SAE Technical Paper Series. 2005–01–2690. Available from: <https://www.sae.org/content/2005-01-2690/>
46. Carcone SM, Keir PJ. Effects of backrest design on biomechanics and comfort during seated work. *Appl Ergon*. 2007 Nov; 38(6):755–64. <https://doi.org/10.1016/j.apergo.2006.11.001> PMID: 17275776
47. Hamberg-van Reenen HH, van der Beek AJ, Blatter BM, van der Grinten MP, van Mechelen W, Bongers PM. Does musculoskeletal discomfort at work predict future musculoskeletal pain? *Ergonomics*. 2008 May; 51(5):637–48. <https://doi.org/10.1080/00140130701743433> PMID: 18432442
48. Gyi DE, Porter JM. Interface pressure and the prediction of car seat discomfort. *Appl Ergon*. 1999 Apr; 30(2):99–107. [https://doi.org/10.1016/s0003-6870\(98\)00018-0](https://doi.org/10.1016/s0003-6870(98)00018-0) PMID: 10098803
49. Lecocq M, Lantoine P, Bougard C, Allègre J-M, Bauvineau L, Bourdin C, et al. Neuromuscular fatigue profiles depends on seat feature during long duration driving on a static simulator. *Appl Ergon*. 2020 Sep; 87:103118. <https://doi.org/10.1016/j.apergo.2020.103118> PMID: 32501249
50. Kyung G, Nussbaum MA. Driver sitting comfort and discomfort (part II): Relationships with and prediction from interface pressure. *Int J Ind Ergon*. 2008 May; 38(5–6):526–38. <https://doi.org/10.1016/j.ergon.2007.08.011>
51. Kyung G, Nussbaum MA. Age-related difference in perceptual responses and interface pressure requirements for driver seat design. *Ergonomics*. 2013 Dec; 56(12):1795–805. <https://doi.org/10.1080/00140139.2013.840391> PMID: 24102548
52. Romelfanger M, Kolich M. Comfortable automotive seat design and big data analytics: A study in thigh support. *Appl Ergon*. 2019 Feb; 75:257–62. <https://doi.org/10.1016/j.apergo.2018.08.020> PMID: 30509534
53. Oron-Gilad T, Ronen A. Road characteristics and driver fatigue: a simulator study. *Traffic Inj Prev*. 2007 Aug 16; 8(3):281–9. <https://doi.org/10.1080/15389580701354318> PMID: 17710719
54. Ariën C, Jongen EMM, Brijs K, Brijs T, Daniels S, Wets G. A simulator study on the impact of traffic calming measures in urban areas on driving behavior and workload. *Accid Anal Prev*. 2013 Dec; 61:43–53. <https://doi.org/10.1016/j.aap.2012.12.044> PMID: 23477414
55. van Veen VS, Orlinskiy V, Franz M, Vink P. Investigating car passenger well-being related to a seat imposing continuous posture variation. *J Ergon*. 2015; 05(03). Available from: <http://www.omicsgroup.org/journals/investigating-car-passenger-wellbeing-related-to-a-seat-imposingcontinuous-posture-variation-2165-7556-1000140.php?aid=62373>
56. Wong WY, Wong MS. Detecting spinal posture change in sitting positions with tri-axial accelerometers. *Gait Posture*. 2008 Jan; 27(1):168–71. <https://doi.org/10.1016/j.gaitpost.2007.03.001> PMID: 17419060
57. Kim SG, Ko C-Y, Kim DH, Song YE, Kang TU, Ahn S, et al. Development of a shear force measurement dummy for seat comfort. Xu J, editor. *PLOS ONE*. 2017 Nov 29; 12(11):e0187918. <https://doi.org/10.1371/journal.pone.0187918> PMID: 29186136
58. Fojtlín M, Psikuta A, Toma R, Fišer J, Jícha M. Determination of car seat contact area for personalised thermal sensation modelling. Potter AW, editor. *PLOS ONE*. 2018 Dec 11; 13(12):e0208599. <https://doi.org/10.1371/journal.pone.0208599> PMID: 30533030
59. Kolich M. Predicting automobile seat comfort using a neural network. *Int J Ind Ergon*. 2004 Apr; 33(4):285–93. <https://doi.org/10.1016/j.apergo.2004.01.007> PMID: 15145290