



Article Enhanced OER Performances of Au@NiCo₂S₄ Core-Shell Heterostructure

Yuepeng Lv⁺, Sibin Duan⁺, Yuchen Zhu, Peng Yin and Rongming Wang^{*}

Beijing Advanced Innovation Center for Materials Genome Engineering, Beijing Key Laboratory for Magneto-Photoelectrical Composite and Interface Science, School of Mathematics and Physics, University of Science and Technology Beijing, Beijing 100083, China; b20150331@xs.ustb.edu.cn (Y.L.); sibinduan@ustb.edu.cn (S.D.); cy931122@live.com (Y.Z.); yinpeng0537@163.com (P.Y.)

* Correspondence: rmwang@ustb.edu.cn

+ These authors contributed equally to this work.

Received: 3 March 2020; Accepted: 23 March 2020; Published: 27 March 2020



Abstract: Transition metal sulfides have attracted a lot of attention as potential oxygen evolution reaction (OER) catalysts. Bimetallic sulfide possesses superior physicochemical properties due to the synergistic effect between bimetallic cations. By introducing a metal-semiconductor interface, the physicochemical properties of transition metal sulfide can be further improved. Using the solvothermal method, Au@NiCo₂S₄ core-shell heterostructure nanoparticles (NPs) and bare NiCo₂S₄ NPs were prepared. The measurement of the OER catalytic performance showed that the catalytic activity of Au@NiCo₂S₄ core-shell heterostructure was enhanced compared to bare NiCo₂S₄ NPs. At the current density of 10 mA cm⁻², the overpotential of Au@NiCo₂S₄ (299 mV) is lower than that of bare NiCo₂S₄ (49.1 mV dec⁻¹), indicating its faster reaction kinetics. Detailed analysis of its electronic structure, chemical state, and electrochemical impedance indicates that the enhanced OER catalytic performances of bare Au@NiCo₂S₄ core-shell NPs were a result of its increased proportion of high-valance Ni/Co cations, and its increased electronic conductivity. This work provides a feasible method to improve OER catalytic performance by constructing a metal-semiconductor core-shell heterostructure.

Keywords: metal-semiconductor; core-shell; bimetallic sulfide; OER; structure-property relationship

1. Introduction

Due to the limited supply and the threat to the environment of fossil fuels, renewable and clean energies need to be developed. Hydrogen is an ideal energy substitute, with high energy density and zero carbon emission. Electrochemical water splitting is an environmentally friendly and promising method for hydrogen production [1,2]. However, the working potential of electrochemical water splitting is much higher than 1.23 V—the theoretical potential [3,4]. Reducing the overpotential and enhancing the stability of catalytic materials are the main research goals of electrochemical water splitting. OER as the anode of the electrochemical water splitting reaction is a multi-step reaction that requires high energy to form O–O* bonds, leading to high overpotential and severely limiting hydrogen production efficiency [5]. Therefore, efficient catalysts are necessary to reduce the overpotential and enhance the OER reaction rate. IrO₂ and RuO₂ are recognized as the most effective OER catalysts, but the low supply and high price of these catalysts seriously limit their commercial applications [6–8].

Transition metals—with their nitrides, phosphides, oxides, hydroxides, sulfides, and selenides—are widely recognized as effective OER catalysts [4,9–14]. Transition metal sulfide is widely used in the field of OER catalysis due to its abundant supply, low price, superior catalytic

activity, and stable performance. Co/Ni sulfides have been considered as potential catalysts for their multivalent properties and tunable electronical structure [15]. Compared with monometallic sulfides, bimetallic sulfides exhibit outstanding OER activities because they have more active sites, higher conductivity, larger electrochemical surface area, and higher structural stability [13,16–27]. Among the bimetallic catalysts, bimetallic nickel cobalt sulfides have become one of the most studied bimetallic structure compounds, due to their advantages of high conductivity and the redox reaction in which Ni and Co elements are more abundant in multi-valence than monometallic sulfides [22,28,29]. For example, (Ni, Co)S₂ nanosheet has a lower overpotential of 270 mV, compared to CoS₂ nanosheet (350 mV), and NiS₂ nanosheet (410 mV) at 10 mA cm⁻², which is due to its good mass/electron transfer properties, more catalytic active sites and facilitated adsorption to O* [30].

To further enhance the OER catalytic properties and promote the application of bimetallic sulfides, designing heterostructures composed of bimetallic sulfide and metal is one of the most effective methods [31–35]. The enhanced physicochemical properties of metal-semiconductor heterostructures are mainly due to the interaction between metal and semiconductor [36,37]. Compared with yolk-shell and oligomer-like heterostructures, the core-shell heterostructure has the maximum contact interface, which can effectively enhance electron transmission along the interface, improve the electrical conductivity, and optimize the electronic structure [9,37,38]. For example, Au@NiS_x core-shell heterostructure has higher HER activity than Au-NiS_x yolk-shell and Au-NiS_x oligomer-like NPs. This is because the Au@NiS_x core-shell heterostructure has a larger contact interface, leading to promoted charge transfer and higher conductivity [39]. The OER activity of Au/Ni₁₂P₅ core-shell heterostructure has also been demonstrated to be improved by the electron interaction between Au and Ni₁₂P₅ [36].

Herein, Au@NiCo₂S₄ heterostructure and bare NiCo₂S₄ NPs were rationally designed and prepared through solvothermal methods. Using time-dependent experiments, the evolution mechanism of Au@NiCo₂S₄ NPs was studied. The measurements of the OER performance indicate that Au@NiCo₂S₄ core-shell heterostructure shows a high current density of 10 mA cm⁻², at a lower overpotential of 299 mV, and a lower Tafel slope of 44.5 mV dec⁻¹, compared with bare CoNi₂S₄ NPs.

2. Materials and Methods

2.1. Preparation of the Au@NiCo₂S₄ Core-Shell NPs

Au@NiCo₂S₄ core-shell heterostructure NPs were controllably synthesized using the seeded growth method. The synthesis method is shown in Figure 1. Typically, 0.05 g Ni(acac)₂ and 0.1 g Co(acac)₂ were dissolved in 16 mL oleylamine (OAm) in a three-necked flask. The solution was heated to 100 °C to form a clear solution. An amount of 3 ml toluene solution containing 0.03 g HAuCl₄·4H₂O was dropped into the solution afterwards. Au NPs were formed at 100 °C in the OAm by the reduction of the Au precursor, which were used as seeds during the subsequent growth of NiCo₂S₄ shells. The solution at 210 °C to serve as a sulfur source. The solution was then heated to 230 °C, and held at this temperature for 3 h. During this time, the NiCo₂S₄ shell formed and grew on the surface of the Au seeds. Finally, the solution was cooled to room temperature. The prepared sample was washed with a mixture of chloroform and acetone and collected by centrifugation. The solution was stirred during the whole reaction, and Ar gas was injected as the protective gas.



Figure 1. Diagram for the synthesis processes of Au@NiCo₂S₄ NPs. The core-shell structure was formed by the seeded growth of NiCo₂S₄ shells on Au NPs.

2.2. Preparation of the Bare $NiCo_2S_4$ NPs

The bare NiCo₂S₄ NPs were prepared by the typical solvothermal method. Amounts of 0.05 g Ni(acac)₂ and 0.1 g Co(acac)₂ were dissolved in 16 mL OAm in a three-necked flask. The solution was heated to 210 °C to form a clear solution. 0.123 g thiourea was added to the solution afterwards. The solution was then heated to 230 °C, and kept at this temperature for 3 h. After the solution was cooled to room temperature, the prepared sample was washed with a mixture of chloroform and acetone, and collected by centrifugation. The solution was stirred during the whole process, and Ar gas was injected as a protective gas.

2.3. Material Characterization

The crystal structures of the products were characterized by X-ray diffraction (XRD) using a Rigaku D/max 2200 PC diffractometer, with Cu K α radiation (λ = 0.15406 nm). An Oxford X-Max80T energy dispersive X-ray spectrograph was used to measure the elemental composition and distribution of the products. A JEOL JEM-2200FS field emission transmission electron microscope (TEM, Tokyo, Japan, JEOL) was used to investigate the morphology of the samples. The atomic arrangements and microstructure of the as-grown samples were examined on a Titan ETEM G2 aberration-corrected transmission electron microscope (AC-TEM). A ULVAC-PHI Phi5000 VersaProbe III X-ray photoelectron spectrograph (XPS, Chigasaki, Japan, ULVAC-PHI) was used to measure the electronic structure and valence of the elements.

2.4. OER Catalytic Measurements

A CHI 760E electrochemical workstation was used to measure the OER catalytic performance of the as-prepared samples. The measurements were performed in a 1 M KOH solution, using a three-electrodes system. To prepare the working electrodes, a 5 mg sample was dispersed into 1 mL ethanol and stirred magnetically for 20 min. Then, 5 mg carbon black was added to the solution and stirred for 20 min. 100 μ L 5 wt % Nafion was added to the solution, and the homogeneous ink was formed by stirred magnetically. 44 μ L ink was dropped onto the surface of a piece of carbon paper (1 cm²) and dried at room temperature to serve as the working electrode. About 0.2 mg of the sample was loaded onto the working electrode. The Hg/HgO and Pt plate were used as the reference electrode and counter electrode, respectively. Linear sweep voltammetry (LSV) was used to characterize OER catalytic performance, with a scan rate of 2 mV s⁻¹, and 95% iR compensation. The electrochemical

impedance spectroscopy (EIS) of the samples was carried out by AC impedance, with a frequency range from 100,000 to 0.1 Hz. The stability of the samples was characterized by a current-time curve.

3. Results and Discussion

Core-shell NPs with a single crystal structure are difficult to be prepare because of the big differences in crystal structures and physicochemical properties between metal and sulfide [35]. Understanding the growth mechanism is helpful for their preparation and controlling their electrocatalytic performance. The time-dependent experiments were conducted in combination with with TEM and EDS analyses. Samples were collected from 0 to 180 min after thiourea was added. Figure S1a–f shows the morphologies of the collected samples. During the formation of Au@NiCo₂S₄ core-shell NPs, the Au NPs kept a five-fold symmetric morphology, and the size of Au NPs was also maintained at 8~10 nm. The shells gradually formed and thickened to about 10 nm. Table S1 shows the atomic ratios of Au to Co gradually decrease from 1 to 0.21. From 10 to 30 min, the atomic ratios of Co to S changed from 0.49 to 0.42. From 30 to 180 min, the atomic ratios of Co to S barely changed. This indicates that the sulfuration process has been completed at 30 min. The above process indicates that the evolution mechanism of Au@NiCo₂S₄ NPs is a typical seeded growth of NiCo₂S₄ shells on the Au NPs.

Figure 2 shows the XRD spectra of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs, which confirms that the samples consist of cubic NiCo₂S₄ (JCPDS No. 43-1477) and cubic Au (JCPDS No. 99-0056). The impurity phase was not detected in the XRD patterns, indicating the high purity of the as-grown sample. Scherrer's equation ($d = 0.89\lambda/(\beta \cdot cos\theta_B)$, where λ is the X-ray wavelength, θ_B is the Bragg diffraction angle and β is the full width at half maxima of the peak) was used to estimate the crystal sizes of the products. The crystal size of NiCo₂S₄ was calculated to be about 11.8 nm, using the peak of NiCo₂S₄ (311) at about 31.5°, and that of the peak of Au was calculated to be about 8.8 nm, using the peak of Au (111) at about 38.2°.



Figure 2. XRD patterns of as-prepared Au@NiCo₂S₄, and bare NiCo₂S₄ NPs.

The chemical composition of the synthesized samples was confirmed by the EDS measurements. The EDS spectra of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs show that the products were composed of S, Co, Ni, and Au, as shown in Figure S2. The atomic ratio for S, Co, Ni, and Au for the Au@NiCo₂S₄ and bare NiCo₂S₄ NPs is also illustrated in Table S2. The TEM specimen holder may cause the additional signals of Si and Cu. The atomic percentages of Ni, Co, and S of the Au@NiCo₂S₄ heterostructure are 10.1%, 24.7%, and 59.9%, respectively. The atomic percentages of Ni, Co, and S of the bare NiCo₂S₄ NPs

are 11.4%, 25.5%, and 63.1%, respectively. Compared with the stoichiometric proportion, the contents of S are slightly higher, possibly due to the adsorption of additional S on the surface of the NPs.

The morphologies and microstructures of the Au@NiCo₂S₄ and the bare NiCo₂S₄ NPs were characterized by TEM. As shown in Figure 3a, the interface between the darker Au cores and the lighter NiCo₂S₄ of the NPs is clean and smooth, without impurity phases, pores, layers or amorphous structure. The bonding between the Au cores and $NiCo_2S_4$ shells was good along the interface because no additional diffraction contrast from the strain was detected. The diameter of the cores is 8.2 ± 1.5 nm. The shell with lighter contrast has a polyhedral structure, with dimensions of 21.9 ± 5.5 nm. The morphologies of these NPs are mainly truncated octahedrons. In Figure S3a-e, the core-shell heterostructure was further confirmed by rotating the TEM samples. Regardless of the viewing angle, the Au NPs were always located at the center of the particles, indicating that the prepared sample was core-shell structure rather than Au NPs supported on the surface of NiCo₂S₄ NPs [39]. The atomic arrangements in the Au@NiCo₂S₄ NPs were investigated using AC-TEM. An Au@NiCo₂S₄ NP with a typical truncated octahedron morphology is shown in Figure 3b. At the atomic scale, no amorphous layer or impurity phase is observed, and the crystal lattice fringe of the NiCo₂S₄ shell layer is clear, indicating that Au@NiCo₂S₄ NPs crystallize well. The diameter of the Au core is ~ 9 nm, and the thickness of the $NiCo_2S_4$ shell is ~ 9 nm. The FFT pattern (Figure 3c) indicates that the shell of the NP is a cubic phase NiCo₂S₄ single crystal. The lattice spacing is 0.285 nm, corresponding to the NiCo₂S₄ (311) planes. To confirm the element distribution of Au@NiCo₂S₄ NPs, EDS mapping spectra were collected. The spectra shown in Figure S4 indicate that the Au element is only distributed in the core, while the other three elements are distributed in the shell. The polyhedron NiCo₂S₄ NPs are exhibited in Figure 3d for comparison. The size of bare NiCo₂S₄ NPs is 10.8 ± 2.1 nm. Figure 3e shows a typical $NiCo_2S_4$ polyhedron NP with almost perfect facets. The crystal lattice of the bare $NiCo_2S_4$ NP is clear. The FFT analysis (Figure 3f) demonstrates that the bare $NiCo_2S_4$ NP is a cubic phase $NiCo_2S_4$ single crystal. The lattice spacing was measured to be 0.331 nm, corresponding to the NiCo₂S₄ (220) plane. All the above results confirm that Au@NiCo₂S₄ NPs is core-shell structured, with single crystal shells.



Figure 3. (a) Typical bright field TEM images of Au@NiCo₂S₄ NPs, (b) HRTEM images obtained by AC-TEM of an Au@NiCo₂S₄ NP, (c) FFT pattern of a Au@NiCo₂S₄ NP, (d) Typical bright field TEM images of NiCo₂S₄ NPs, (e) HRTEM images obtained by AC-TEM of a bare NiCo₂S₄ NP, (f) FFT pattern of a bare NiCo₂S₄ NP. In the FFT pattern, the diffraction spots of Au and NiCo₂S₄ are marked by yellow and purple circles, respectively.

The XPS spectra were used to characterize the chemical states and electronic structures of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs. The full survey scan XPS spectra are shown in Figure S5. By comparing the spectra, it can be confirmed that the full survey scan XPS spectrum of Au@NiCo₂S₄ is similar to that of bare $NiCo_2S_4$, except that the peak of Au 4f appears at 80–90 eV. Figure 4 and Figure S6 show high-resolution spectra of the Ni, Co, S, and Au of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs, respectively. The Ni 2p high-resolution spectra are shown in Figure 4a. The fitting peaks positioned at 853.12-853.22 eV and 870.42-870.52 eV are assigned to Ni²⁺, while the peaks at 854.92-855.04 eV and 872.22–872.34 eV correspond to Ni³⁺ [19]. The Co 2p high-resolution spectra are shown in Figure 4b. The fitting peaks positioned at 778.68–778.69 eV and 793.88–793.89 eV are assigned to Co³⁺, while the peaks at 779.83–779.86 eV and 795.03–795.06 eV correspond to Co²⁺ [19]. Figure S5a shows the S 2p XPS spectra. The peaks positioned at 161.54–161.58 eV and 162.46–162.53 eV are assigned to S^{2-} , while the peaks at 162.94–163.00 eV and 163.84–163.97 eV are assigned to S⁻. The peaks at 165.95–166.29 eV are assigned to SO_4^{2-}/SO_3^{2-} , which may be caused by oxidation of the surface sulfur [40]. The Au 4f XPS spectrum of the Au@NiCo₂S₄ is shown in Figure S5b.; the fitting peaks positioned at 84.16 eV and 87.81 eV are assigned to metallic Au, and the peaks at 85.19 eV and 88.74 eV can be assigned to Au⁺ [41]. These results indicate that Ni and Co atoms possess multi-valence in the bimetallic sulfides. The ratios of valence states are shown in Table S3. Compared with bare NiCo₂S₄, the ratio of Ni³⁺:Ni²⁺ in Au@NiCo₂S₄ was increased, which is similar to the trend of $Co^{3+}:Co^{2+}$. These results indicate that there is strong electron interaction between Au and NiCo₂S₄. Due to the addition of Au NPs, the proportion of Co³⁺ and Ni³⁺ in NiCo₂S₄ NPs increases, which is beneficial to their electrochemical performances, because Ni³⁺/Co³⁺ have been considered as active sites during the oxygen evolution [6].



Figure 4. High resolution XPS spectra for the (a) Ni 2p, (b) Co 2p of Au@NiCo₂S₄, and NiCo₂S₄ NPs.

The OER catalytic performances of the Au@NiCo₂S₄ heterostructure and bare NiCo₂S₄ NPs were tested in alkaline solutions. The OER catalytic parameters are shown in Table S4. Figure 5a shows the polarization curves of the as-prepared samples. The overpotential of Au@NiCo₂S₄ NPs (299 mV) is lower than that of bare NiCo₂S₄ NPs (312 mV) at a current density of 10 mA cm⁻². The OER catalytic performance is improved by the interaction between Au NPs and NiCo₂S₄ shells. The overpotential of Au@NiCo₂S₄ NPs is comparable to the value of previously reported catalysts such as NiCo₂S₄@g-C₃N₄-CNT (320 mV, 10 mA cm⁻²) [19], NiCo₂S₄ nanoflakes (319 mV, 100 mA cm⁻²) [16], and Au@CoFeO_x (328 mV, 10 mA cm⁻²) [9]. The Tafel slopes of Au@NiCo₂S₄ NPs and NiCo₂S₄ NPs are shown in Figure 5b. Compared with bare NiCo₂S₄ NPs (49.1 mV dec⁻¹), the Tafel slope of Au@NiCo₂S₄ (44.5 mV dec⁻¹) is lower, indicating that Au@NiCo₂S₄ NPs possess a superior reaction kinetic, and a faster mass/electron transport rate. The Tafel slopes of these two samples are comparable or superior to other OER catalysts such as NiCo₂S₄ @NiFe LDH (46.3 mV dec⁻¹) [23] and P-Co-Ni-S nanosheets

(61.1 mV dec⁻¹) [42]. All these results demonstrate that, due to the interaction between Au and NiCo₂S₄, Au@NiCo₂S₄ NPs exhibit better OER catalytic activity than bare NiCo₂S₄ NPs.



Figure 5. OER performances of Au@NiCo₂S₄, and bare NiCo₂S₄ NPs in 1 M KOH: (**a**) polarization curves (**b**) Tafel curves, (**c**) Nyquist plots, and (**d**) time–current curves.

To further analyze the electronical factors affecting the OER activity of the samples, the EIS of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs were measured. The diameter of the Nyquist plots of Au@NiCo₂S₄ is smaller than that of bare NiCo₂S₄, as shown in Figure 5c. The equivalent circuit, fitted according to the EIS, is shown in the inset of Figure 5c. The charge transfer resistance R_t corresponds to the diameter of the Nyquist plot, and represents the resistance of mass transfer during the OER catalytic reaction, which is the decisive parameter affecting OER catalytic efficiency [43]. It can be seen that the R_t of Au@NiCo₂S₄ (1.6 Ω) is lower than that of bare NiCo₂S₄ (2.0 Ω). The decrease of R_t is due to the interaction between the Au NP and the NiCo₂S₄ shell, which can enhance the conductivity and shorten the length of charge diffusion [39]. The double-layer capacitance (C_d) of the NPs surface is reflected by the Y_0 value of the CPE, which represents the location of the absorbed molecules, and is related to the electrochemical surface area [36]. The Y_0 value of Au@NiCo₂S₄ NPs is much larger than that of bare NiCo₂S₄ NPs, as shown in Table S4, indicating that its effective surface area is larger than that of bare NiCo₂S₄ NPs, and that Au@NiCo₂S₄ core-shell NPs have more active sites and exhibit better OER activity. In addition, as demonstrated by the XPS results, in Au@NiCo₂S₄ NPs, the proportion of high-valance Ni and Co cations is increased. The high-valance Ni and Co cations are the active sites for OER, so the Au@NiCo2S4 core-shell NPs possess better OER catalytic activity than bare NiCo₂S₄ [6]. Therefore, benefiting from the lower R_t , larger effective surface area, the increased proportion of high-valence Ni and Co cations, and the single crystal NiCo2S4 shells, the Au@NiCo2S4 NPs possess better OER activity than bare NiCo₂S₄. As shown in Figure 5d, to test the stability of the materials, a current-time curve for the as-prepared NPs was characterized. Au@NiCo₂S₄ and bare NiCo₂S₄ have relatively excellent OER catalytic stability, maintaining 98.9%, and 95.2% after 5 h, respectively. This indicates that Au@NiCo2S4 and bare NiCo2S4 NPs have a superior stability over a long period of OER catalysis. The stability of Au@NiCo2S4 core-shell NPs is superior to NoCo2S4

NPs, which should be attributed to the following factors: (1) The introduction of Au cores reduced the overpotential, thus reducing the driving force for the reconstruction of NiCo₂S₄ [9]. (2) The interface interaction between Au and NiCo₂S₄ increased the proportion of Co³⁺ and Ni³⁺, thus enhancing the charge density at the specific domains and increasing the number of active sites [44]. (3) The larger effective surface area of Au@NiCo₂S₄ makes it easier for bubbles to detach from the electrode [45].

4. Conclusions

In summary, Au@NiCo₂S₄ and bare NiCo₂S₄ NPs were controllably prepared. The Au@NiCo₂S₄ sample exhibited a core-shell heterostructure with single crystal shells. The OER catalytic results confirm that the core-shell structure exhibits superior OER catalytic performance to bare NiCo₂S₄ NPs, which may be due to the interaction between Au and NiCo₂S₄. The XPS and EIS results demonstrated that the electronic conductivity, and the ratio of high-valance Ni and Co, were improved with the Au-NiCo₂S₄ interaction, which are beneficial to its electrocatalytic performance. The overpotential and Tafel slope of the Au@NiCo₂S₄ heterostructure NPs is 299 mV at 10 mA cm⁻² and 44.5 mV dec⁻¹, respectively. The construction of metal-semiconductor core-shell heterostructure will provide more chances for its application in the field of electrochemical water splitting.

Supplementary Materials: The following are available online at http://www.mdpi.com/2079-4991/10/4/611/s1, Figure S1. TEM images of Au@NiCo₂S₄ NPs evolution experiment. Table S1. The ratios of elements at different times of Au@NiCo₂S₄ NPs evolution experiment. Figure S2. EDS spectra of the Au@NiCo₂S₄ and bare NiCo₂S₄ NPs. Table S2. Atomic ratio of Au, Ni, Co and S of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs calculated by EDS. Figure S3. Angle-dependent TEM characterization of Au@NiCo₂S₄ NPs verifying the core-shell of the products. The shells produced in the outer shell of the NP were reasoned from the carbon deposit induced by the long-time high-energy electron irradiation. Scale bar 20 nm. Figure S4. HAADF-STEM images and STEM-EDS mappings for the elements Au, Ni, Co, and S of Au@NiCo₂S₄ NPs. Figure S5. XPS survey spectra of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs. Table S3. XPS peaks area ratio of Ni, and Co of Au@NiCo₂S₄ and bare NiCo₂S₄ NPs. Table S3. XPS peaks area ratio of Ni, and Co of Au@NiCo₂S₄ and bare NiCo₂S₄, and bare NiCo₂S₄ NPs. Table S3. XPS peaks area ratio of Ni, and Co of Au@NiCo₂S₄ and bare NiCo₂S₄, and bare NiCo₂S₄ NPs.

Author Contributions: Y.L., S.D. and R.W. conceived and designed the experiments. Y.L. and P.Y. synthesized the samples. Y.L. performed the OER catalytic experiments. Y.Z. performed the TEM characterization. Y.L., S.D. and R.W. wrote and refined the manuscript. All authors analyzed the data, discussed the results, and approved the manuscript. Y.L. and S.D. contributed equally to this work. All authors have read and agreed to the published version of the manuscript.

Funding: This research was funded by the National Key Research and Development Program of China (No. 2018YFA0703700), the National Natural Science Foundation of China (Nos. 51971025 and 51901012), the Fundamental Research Funds for the Central Universities (FRF-TP-17-073A1) and 111 Project (No. B170003).

Conflicts of Interest: The authors declare no conflict of interest.

References

- Guo, Y.N.; Park, T.; Yi, J.W.; Henzie, J.; Kim, J.; Wang, Z.L.; Jiang, B.; Bando, Y.; Sugahara, Y.; Tang, J.; et al. Nanoarchitectonics for transition-metal-sulfide-based electrocatalysts for water splitting. *Adv. Mater.* 2019, 31, 34. [CrossRef]
- 2. You, B.; Sun, Y.J. Innovative strategies for electrocatalytic water splitting. *Acc. Chem. Res.* **2018**, *51*, 1571–1580. [CrossRef]
- Du, X.C.; Huang, J.W.; Zhang, J.J.; Yan, Y.C.; Wu, C.Y.; Hu, Y.; Yan, C.Y.; Lei, T.Y.; Chen, W.; Fan, C.; et al. Modulating electronic structures of inorganic nanomaterials for efficient electrocatalytic water splitting. *Angew. Chem. Int. Ed.* 2019, *58*, 4484–4502. [CrossRef] [PubMed]
- 4. Wang, Y.Y.; Yan, D.F.; El Hankari, S.; Zou, Y.Q.; Wang, S.Y. Recent progress on layered double hydroxides and their derivatives for electrocatalytic water splitting. *Adv. Sci.* **2018**, *5*, 32. [CrossRef]
- Zhang, B.; Zheng, X.L.; Voznyy, O.; Comin, R.; Bajdich, M.; Garcia-Melchor, M.; Han, L.L.; Xu, J.X.; Liu, M.; Zheng, L.R.; et al. Homogeneously dispersed multimetal oxygen-evolving catalysts. *Science* 2016, 352, 333–337. [CrossRef] [PubMed]

- Kang, Z.; Guo, H.J.; Wu, J.; Sun, X.; Zhang, Z.; Liao, Q.L.; Zhang, S.C.; Si, H.N.; Wu, P.W.; Wang, L.; et al. Engineering an earth-abundant element-based bifunctional electrocatalyst for highly efficient and durable overall water splitting. *Adv. Funct. Mater.* 2019, *29*, 1. [CrossRef]
- McCrory, C.C.L.; Jung, S.; Ferrer, I.M.; Chatman, S.M.; Peters, J.C.; Jaramillo, T.F. Benchmarking hydrogen evolving reaction and oxygen evolving reaction electrocatalysts for solar water splitting devices. *J. Am. Chem. Soc.* 2015, *137*, 4347–4357. [CrossRef] [PubMed]
- 8. Xu, Y.; Tu, W.; Zhang, B.; Yin, S.; Huang, Y.; Kraft, M.; Xu, R. Nickel nanoparticles encapsulated in few-layer nitrogen-doped graphene derived from metal-organic frameworks as efficient bifunctional electrocatalysts for overall water splitting. *Adv. Mater.* **2017**, *29*, 1605957. [CrossRef] [PubMed]
- 9. Strickler, A.L.; Escudero-Escribano, M.; Jaramillo, T.F. Core-shell Au@metal-oxide nanoparticle electrocatalysts for enhanced oxygen evolution. *Nano Lett.* **2017**, *17*, 6040–6046. [CrossRef]
- 10. Wang, Y.; Chen, L.; Yu, X.; Wang, Y.; Zheng, G. Superb alkaline hydrogen evolution and simultaneous electricity generation by Pt-decorated Ni₃N nanosheets. *Adv. Energy Mater.* **2017**, *7*, 1601390. [CrossRef]
- Wang, F.; Li, Y.; Shifa, T.A.; Liu, K.; Wang, F.; Wang, Z.; Xu, P.; Wang, Q.; He, J. Selenium-enriched nickel selenide nanosheets as a robust electrocatalyst for hydrogen generation. *Angew. Chem. Int. Ed.* 2016, 55, 6919–6924. [CrossRef]
- Chen, P.Z.; Zhou, T.P.; Zhang, M.X.; Tong, Y.; Zhong, C.G.; Zhang, N.; Zhang, L.D.; Wu, C.Z.; Xie, Y. 3D nitrogen-anion-decorated nickel sulfides for highly efficient overall water splitting. *Adv. Mater.* 2017, 29, 6. [CrossRef] [PubMed]
- Sivanantham, A.; Shanmugam, S. Nickel selenide supported on nickel foam as an efficient and durable non-precious electrocatalyst for the alkaline water electrolysis. *Angew. Chem. Int. Ed.* 2017, 203, 485–493. [CrossRef]
- Guan, C.; Xiao, W.; Wu, H.J.; Liu, X.M.; Zang, W.J.; Zhang, H.; Ding, J.; Feng, Y.P.; Pennycook, S.J.; Wang, J. Hollow Mo-doped CoP nanoarrays for efficient overall water splitting. *Nano Energy* 2018, 48, 73–80. [CrossRef]
- 15. Kulkarni, P.; Nataraj, S.K.; Balakrishna, R.G.; Nagaraju, D.H.; Reddy, M.V. Nanostructured binary and ternary metal sulfides: Synthesis methods and their application in energy conversion and storage devices. *J. Mater. Chem. A* **2017**, *5*, 22040–22094. [CrossRef]
- Yu, J.; Lv, C.X.; Zhao, L.; Zhang, L.X.; Wang, Z.H.; Liu, Q.Y. Reverse microemulsion-assisted synthesis of NiCo₂S₄ nanoflakes supported on nickel foam for electrochemical overall water splitting. *Adv. Mater. Interfaces* 2018, 5, 8. [CrossRef]
- 17. Liu, Q.; Jin, J.; Zhang, J. NiCo₂S₄@graphene as a bifunctional electrocatalyst for oxygen reduction and evolution reactions. *ACS Appl. Mater. Inter.* **2013**, *5*, 5002–5008. [CrossRef] [PubMed]
- 18. Liu, D.; Lu, Q.; Luo, Y.; Sun, X.; Asiri, A.M. NiCo₂S₄ nanowires array as an efficient bifunctional electrocatalyst for full water splitting with superior activity. *Nanoscale* **2015**, *7*, 15122–15126. [CrossRef] [PubMed]
- Han, X.; Zhang, W.; Ma, X.; Zhong, C.; Zhao, N.; Hu, W.; Deng, Y. Identifying the activation of bimetallic sites in NiCo₂S₄@g-C₃N₄-CNT hybrid electrocatalysts for synergistic oxygen reduction and evolution. *Adv. Mater.* 2019, *31*, e1808281. [CrossRef]
- Zhu, W.X.; Ren, M.R.; Hu, N.; Zhang, W.T.; Luo, Z.T.; Wang, R.; Wang, J.; Huang, L.J.; Suo, Y.R.; Wang, J.L. Traditional NiCo₂S₄ phase with porous nanosheets array topology on carbon cloth: A flexible, versatile and fabulous electrocatalyst for overall water and urea electrolysis. *ACS Sustain. Chem. Eng.* **2018**, *6*, 5011–5020. [CrossRef]
- 21. Gong, Y.Q.; Wang, J.L.; Lin, Y.; Yang, Z.; Pan, H.L.; Xu, Z.F. Synthesis of 1D to 3D nanostructured NiCo₂S₄ on nickel foam and their application in oxygen evolution reaction. *Appl. Surf. Sci.* **2019**, 476, 600–607. [CrossRef]
- 22. Sivanantham, A.; Ganesan, P.; Shanmugam, S. Hierarchical NiCo₂S₄ nanowire arrays supported on ni foam: An efficient and durable bifunctional electrocatalyst for oxygen and hydrogen evolution reactions. *Adv. Funct. Mater.* **2016**, *26*, 4661–4672. [CrossRef]
- Liu, J.; Wang, J.; Zhang, B.; Ruan, Y.; Lv, L.; Ji, X.; Xu, K.; Miao, L.; Jiang, J. Hierarchical NiCo₂S₄@NiFe LDH heterostructures supported on nickel foam for enhanced overall-water-splitting activity. *ACS Appl. Mater. Inter.* 2017, *9*, 15364–15372. [CrossRef]
- Li, X.X.; Wang, X.T.; Xiao, K.; Ouyang, T.; Li, N.; Liu, Z.Q. In situ formation of consubstantial NiCo₂S₄ nanorod arrays toward self-standing electrode for high activity supercapacitors and overall water splitting. *J. Power Sources* 2018, 402, 116–123. [CrossRef]

- Gao, Q.Y.; Wang, X.Q.; Shi, Z.Y.; Ye, Z.R.; Wang, W.C.; Zhang, N.; Hong, Z.L.; Zhi, M.J. Synthesis of porous NiCo₂S₄ aerogel for supercapacitor electrode and oxygen evolution reaction electrocatalyst. *Chem. Eng. J.* 2018, 331, 185–193. [CrossRef]
- Li, J.W.; Zhuang, Q.N.; Xu, P.M.; Zhang, D.W.; Wei, L.C.; Yuan, D.S. Three-dimensional lily-like CoNi₂S₄ as an advanced bifunctional electrocatalyst for hydrogen and oxygen evolution reaction. *Chin. J. Catal.* 2018, *39*, 1403–1410. [CrossRef]
- Huang, R.; Chen, W.; Zhang, Y.; Huang, Z.; Dai, H.; Zhou, Y.; Wu, Y.; Lv, X. Well-designed cobalt-nickel sulfide microspheres with unique peapod-like structure for overall water splitting. *J. Colloid Interface Sci.* 2019, 556, 401–410. [CrossRef]
- Xiao, J.; Wan, L.; Yang, S.; Xiao, F.; Wang, S. Design hierarchical electrodes with highly conductive NiCo₂S₄ nanotube arrays grown on carbon fiber paper for high-performance pseudocapacitors. *Nano Lett.* 2014, 14, 831–838. [CrossRef]
- Xu, M.J.; Xu, R.J.; Zhao, Y.; Chen, L.B.; Huang, B.Y.; Wei, W.F. Hierarchically porous Ni monolith@branch-structured NiCo₂O₄ for high energy density supercapacitors. *Prog. Nat. Sci.* 2016, 26, 276–282. [CrossRef]
- 30. Zhang, J.; Bai, X.; Wang, T.; Xiao, W.; Xi, P.; Wang, J.; Gao, D.; Wang, J. Bimetallic Nickel Cobalt Sulfide as Efficient Electrocatalyst for Zn-Air Battery and Water Splitting. *Nano Micro Lett.* **2019**, *11*, 2. [CrossRef]
- 31. Liu, X.; Iocozzia, J.; Wang, Y.; Cui, X.; Chen, Y.; Zhao, S.; Li, Z.; Lin, Z. Noble metal–metal oxide nanohybrids with tailored nanostructures for efficient solar energy conversion, photocatalysis and environmental remediation. *Energ. Environ. Sci.* **2017**, *10*, 402–434. [CrossRef]
- 32. Wang, M.; Ye, M.; Iocozzia, J.; Lin, C.; Lin, Z. Plasmon-mediated solar energy conversion via photocatalysis in noble metal/semiconductor composites. *Adv. Sci.* **2016**, *3*, 1600024. [CrossRef]
- Feng, J.; Liu, J.; Cheng, X.; Liu, J.; Xu, M.; Zhang, J. Hydrothermal cation exchange enabled gradual evolution of Au@ZnS-AgAuS yolk-shell nanocrystals and their visible light photocatalytic applications. *Adv. Sci.* 2018, 5, 1700376. [CrossRef]
- Sun, Y.H.; Yang, X.Z.; Zhao, H.F.; Wang, R.M. Non-symmetric hybrids of noble metal-semiconductor: Interplay of nanoparticles and nanostructures in formation dynamics and plasmonic applications. *Prog. Nat. Sci.* 2017, 27, 157–168. [CrossRef]
- 35. Lv, Y.; Duan, S.; Wang, R. Structure design, controllable synthesis, and application of metal-semiconductor heterostructure nanoparticles. *Prog. Nat. Sci.* 2020, *30*, 1–12. [CrossRef]
- 36. Xu, Y.Y.; Duan, S.B.; Li, H.Y.; Yang, M.; Wang, S.J.; Wang, X.; Wang, R.M. Au/Ni₁₂P₅ core/shell single-crystal nanoparticles as oxygen evolution reaction catalyst. *Nano Res.* **2017**, *10*, 3103–3112. [CrossRef]
- 37. Duan, S.B.; Wang, R.M. Au/Ni₁₂P₅ core/shell nanocrystals from bimetallic heterostructures: In situ synthesis, evolution and supercapacitor properties. *NPG Asia Mater.* **2014**, *6*, e122. [CrossRef]
- 38. Wang, R. The dynamic of the peel. Nat. Catal. 2020. [CrossRef]
- 39. Lv, Y.; Duan, S.; Zhu, Y.; Guo, H.; Wang, R. Interface control and catalytic performances of Au-NiS heterostructures. *Chem. Eng. J.* 2020, *382*, 122794. [CrossRef]
- Feng, J.X.; Wu, J.Q.; Tong, Y.X.; Li, G.R. Efficient hydrogen evolution on Cu nanodots-decorated Ni₃S₂ nanotubes by optimizing atomic hydrogen adsorption and desorption. *J. Am. Chem. Soc.* 2018, 140, 610–617. [CrossRef]
- Moon, S.Y.; Song, H.C.; Gwag, E.H.; Nedrygailov, I.I.; Lee, C.; Kim, J.J.; Doh, W.H.; Park, J.Y. Plasmonic hot carrier-driven oxygen evolution reaction on Au nanoparticles/TiO₂ nanotube arrays. *Nanoscale* 2018, 10, 22180–22188. [CrossRef] [PubMed]
- 42. Zhang, F.; Ge, Y.; Chu, H.; Dong, P.; Baines, R.; Pei, Y.; Ye, M.; Shen, J. Dual-functional starfish-like P-doped Co-Ni-S nanosheets supported on nickel foams with enhanced electrochemical performance and excellent stability for overall water splitting. *ACS Appl. Mater. Inter.* **2018**, *10*, 7087–7095. [CrossRef] [PubMed]
- 43. Hu, J.M.; Zhang, J.Q.; Cao, C.N. Oxygen evolution reaction on IrO₂-based DSA (R) type electrodes: Kinetics analysis of Tafel lines and EIS. *Int. J. Hydrogen Energy* **2004**, *29*, 791–797. [CrossRef]

- 44. Guo, Y.N.; Tang, J.; Wang, Z.L.; Kang, Y.M.; Bando, Y.; Yamauchi, Y. Elaborately assembled core-shell structured metal sulfides as a bifunctional catalyst for highly efficient electrochemical overall water splitting. *Nano Energy* **2018**, 47, 494–502. [CrossRef]
- 45. Li, M.; Wang, H.; Zhu, Y.; Tian, D.; Wang, C.; Lu, X. Mo/Mo₂C encapsulated in nitrogen-doped carbon nanofibers as efficiently integrated heterojunction electrocatalysts for hydrogen evolution reaction in wide pH range. *Appl. Surf. Sci.* **2019**, *496*, 143672. [CrossRef]



© 2020 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (http://creativecommons.org/licenses/by/4.0/).