

Research Article ZnFe₂O₄-TiO₂ Nanoparticles within Mesoporous MCM-41

Aidong Tang,¹ Yuehua Deng,² Jiao Jin,² and Huaming Yang²

¹ School of Chemistry and Chemical Engineering, Central South University, Changsha 410083, China

² Department of Inorganic Materials, School of Resources Processing and Bioengineering, Central South University, Changsha 410083, China

Correspondence should be addressed to Huaming Yang, hmyang9392@hotmail.com

Received 4 May 2012; Accepted 5 June 2012

Academic Editors: G. Gorrasi, S. H. Hur, and J. Koetz

Copyright © 2012 Aidong Tang et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

A novel nanocomposite $ZnFe_2O_4$ -TiO₂/MCM-41 (ZTM) was synthesized by a sol-gel method and characterized through X-ray diffraction (XRD), high-resolution transmission electron microscopy (HRTEM), N₂ adsorption-desorption, Raman spectroscopy, and ultraviolet visible (UV-vis) spectrophotometry. The results confirmed the incorporation of $ZnFe_2O_4$ -TiO₂ nanoparticles inside the pores of the mesoporous MCM-41 host without destroying its integrity. $ZnFe_2O_4$ nanoparticles can inhibit the transformation of anatase into rutile phase of TiO₂. Incorporation of $ZnFe_2O_4$ -TiO₂ within MCM-41 avoided the agglomeration of nanoparticles and reduced the band gap energy of TiO₂ to enhance its visible light photocatalytic activity. UV-vis absorption edges of ZTM nanocomposites redshifted with the increase of Zn/Ti molar ratio. The nanocomposite approach could be a potential choice for enhancing the photoactivity of TiO₂, indicating an interesting application in the photodegradation and photoelectric fields.

1. Introduction

TiO₂ had been widely used in various applications, such as functional ceramics [1, 2], sensor materials [3-5], cosmetic products [6, 7], photocatalyst [8-10], high grade coatings [11-13], pigment in the paint, and paper and pulp industry [14, 15]. As an interesting photocatalyst, TiO₂ had attracted much attention due to high efficiency with low cost, chemical inertness, and photostability. Different kinds of TiO₂ were obtained through several procedures: porous TiO₂ cryogel fibers through unidirectional freezing of hydrogel [16], wormhole-like mesoporous TiO₂ by chemical vapor deposition [17], hollow TiO₂ microspheres obtained by a single-step synthesis in ionic liquids [18], and coral-like TiO₂ produced by templating polymer gels [17]. However, the widespread use of TiO_2 was impaired by some defects of its structure, agglomeration easily occurred during the synthesis process and wide band gap (3.2 eV)which requires ultraviolet irradiation for photocatalytic activation.

In order to improve the photocatalytic properties of TiO_2 , effective measurements had been taken into experiment. Doping of transition [19] and noble metals [20, 21] can improve the photocatalytic activity of TiO_2 to some

degree. Zinc ferrite (ZnFe₂O₄), with a spinel structure and a relatively small band gap (1.9 eV), has a potential application in the conversion of sunlight. However, because of the lower valence band potential and poor property in photoelectric conversion, ZnFe₂O₄ cannot be directly used in the photocatalytic destruction. It was demonstrated that ZnFe₂O₄ doping extend the adsorption spectrum to the longer wavelength, this material had high utility of sunlight, high photoactivity, and high efficiency of photoelectric conversion [22–24].

Meanwhile, considering that mesoporous molecular sieves, MCM-41, which possesses a regular hexagonal array of uniform pore openings, we propose that the uniform ordered channels of MCM-41 may be able to control the particle size of TiO₂ and efficiently prevent particles from agglomeration. It was a new route to keep nanoparticles inside the pores of MCM-41 material [25]. There are many researches focused on the substitution of silicon by metals such as Ti [26] and Ni [27] and incorporating nanoparticles within the pores of mesoporous materials, including gold nanoparticles within mesoporous silica [28], MCM-41 modified SnO₂ [29], and MCM-48 containing TiO₂ nanoparticles [30], all of which can enhance the properties of the nanoparticles or the incorporated hosts. In this paper, we demonstrate a novel route to improve the properties of TiO_2 through the addition of $ZnFe_2O_4$ and incorporating the $ZnFe_2O_4$ - TiO_2 nanoparticles into the channels of mesoporous MCM-41. The effect of $ZnFe_2O_4$ addition on the structure and the properties of $ZnFe_2O_4$ - TiO_2 and $ZnFe_2O_4$ - TiO_2/MCM -41 composites are also investigated. The composites were in detail characterized by XRD, TG-DSC, TEM, BET, Raman, and UV-vis spectroscopy.

2. Experimental

2.1. Materials Synthesis. MCM-41 mesoporous materials were prepared according to our previous work [31]. $TiO_2/MCM-41$ composite (molar ratio of Ti/Si = 0.4) was obtained using tetrabutyl titanate as Ti source. The synthesis procedure of TiO₂/MCM-41 composite was as follows: a certain amount of tetrabutyl titanate was added to 40 mL ethanol with uniform stirring. Diethanolamine, used as catalyst and stabilizing agent, was added and constantly stirred for 0.5 h to form a solution S. 1.8 g MCM-41 was added to the above solution S and stirred for 10 min. A mixture of water and ethanol was further dropped, stirred for 4 h and aged for 24 h to obtain a gel. The gel was dried at 80°C overnight and calcined at 600°C to produce TiO₂/MCM-41 composites. Pure TiO₂ was synthesized according to this procedure without the addition of MCM-41. The synthesis procedure of ZnFe₂O₄-TiO₂ with different Zn/Ti molar ratio was similar to the above procedure as TiO₂. Certain amount of ferric nitrate and zinc acetate (molar ratio of Zn/Fe = 0.5) were dissolved in an ethanol solution to obtain a uniform precursor. The precursor was added to the solution S with different Zn/Ti molar ratios (1%, 3%, 5%, and 7%, denoting the corresponding product ZnFe₂O₄-TiO₂ as ZT1, ZT3, ZT5, and ZT7, resp.). When MCM-41 was simultaneously added to the above solution S according to Ti/Si molar ratio of 0.4, the final product ZnFe₂O₄-TiO₂/MCM-41 was correspondingly indicated as ZTM1, ZTM3, ZTM5, and ZTM7, respectively.

2.2. Characterization. X-ray diffraction (XRD) was carried out using a Bruker D8 advance with Cu K α radiation (λ = 0.15406 nm) over the scanning range $2\theta = 1^{\circ} \sim 10^{\circ}$ for small angle XRD (SAXRD) at a voltage of 40 kV and 300 mA and 2θ = $1^{\circ} \sim 10^{\circ}$ for wide angle XRD (WAXRD) at a voltage of 40 kV and 200 mA both with a step width of 0.0085°. Nitrogen gas adsorption-desorption isotherms were measured at 77 K using an ASAP 2020 unit. Prior to the sorption experiment, the samples were vacuum-dried at 200°C for 10 h. The specific surface area and pore size distribution were calculated by the Brunauer-Emmett-Teller (BET) method and the Barrett-Joyner-Halenda (BJH) method using the adsorptiondesorption isotherms, respectively. The total pore volume was obtained from the maximum amount of nitrogen gas adsorbed at partial pressure ($P/P_0 = 0.999$). A Tecnai G220 AEM electron microscope operating at accelerating voltages up to 200 kV was used for the high-resolution TEM (HRTEM) studies. Samples were prepared by suspending MCM-41 material with or without TiO₂ nanoparticles in



FIGURE 1: WAXRD patterns of pure TiO₂ and ZT series samples.

ethanol followed by sonication for 15 min in an ultrasonic bath. The suspension was dripped onto a carbon-coated copper grid and allowed to dry, respectively. Ultraviolet visible (UV-vis) spectrophotometry spectra were collected on a SHIMADZU UV-2450 spectrophotometer at room temperature, and the detection range of wavelength is from 190 nm to 700 nm. The Raman spectra were obtained using Renishaw InVia Raman system which can extend to 100 cm^{-1} . The 514 nm line of an Argon laser was used as the excitation source.

3. Results and Discussion

XRD analysis can provide detailed information on crystallite structure characteristics. WAXRD patterns of pure TiO₂ and ZT series samples showed both anatase and rutile phase of TiO₂ (Figure 1). The peak intensity of rutile phase decreased with increasing the amount of ZnFe₂O₄. The percentage of anatase phase in pure TiO2 and ZT series (Zn/Ti from 1% to 7%) were 74%, 76%, 52%, 55%, and 18%, respectively. It was concluded that the addition of ZnFe₂O₄ can promote the transformation of TiO₂ from anatase to rutile phase. Li et al. [32] and Liu et al. [23] obtained similar conclusion from their study. Meanwhile, all the peaks became broadened, suggesting that the grain size decreased with the increasing addition of ZnFe₂O₄. A weak diffraction peak due to spinel ZnFe₂O₄ phase appeared at the Zn/Ti molar ratio of 3%, indicating the formation of $ZnFe_2O_4$ in the composites, which was in good accordance with the references [33, 34]. The grain sizes of anatase and rutile TiO₂ phase were calculated using Jade 5.0 (Figure 2) which all decreased with increasing the amount of ZnFe₂O₄, ZnFe₂O₄ seemed to play an important role in inhibiting the growth of TiO₂ particles [35, 36].

Figure 3 showed the WAXRD patterns of MCM-41 incorporated within pure TiO_2 and ZT nanoparticles.



FIGURE 2: Variation of grain sizes of anatase and rutile TiO_2 in ZT series samples.



FIGURE 3: WAXRD patterns of TiO_2/MCM -41 and ZTM series samples.

TiO₂/MCM-41, ZTM1, and ZTM3 only presented the characteristic peaks of anatase TiO₂, while rutile phase was observed in the WAXRD patterns of the other two composites. The peaks corresponding to anatase and rutile became broadened, which was attributed to the confinement of nanoparticles within MCM-41 pore channel. All the patterns did not show any peaks corresponding to spinel $ZnFe_2O_4$. The percentage of anatase in ZTM5 and ZTM7 were 69% and 28%, respectively, larger than those of ZT5 and ZT7 samples (55% and 18%), suggesting that MCM-41 had an obvious effect on the anatase-rutile phase transformation of TiO₂.

All the samples presented three characteristic peaks of typical MCM-41 in their SAXRD patterns (Figure 4), which was in accordance with the previous report [37], indicating that the pore channel of MCM-41 remained well even after the incorporation of nanoparticles. No change in the position of main peak demonstrated that Ti^{4+} ions, Zn^{2+} ions,



FIGURE 4: SAXRD patterns of TiO_2/MCM -41 and ZTM series samples.

and Fe³⁺ ions were not incorporated into the framework of MCM-41. The increase in intensity of (100) peak after incorporation demonstrated that $ZnFe_2O_4$ can inhibit the growth of TiO₂ particles. However, compared with SAXRD pattern of pure MCM-41 [31], the peak intensity of all samples decreased visibly, one can be attributed to the pore filling of the host material, which reduced the scattering contrast between pore walls and pores, thus leading to a decrease in peak intensity [38]; another is possibly related to the loss of sample integrity [30].

HRTEM images of MCM-41, TiO₂/MCM-41, and ZnFe₂O₄-TiO₂/MCM-41 (Zn : Tin = 0.07, ZTM = 7) were collected to find out the location of TiO₂ (Figure 5), the ordered mesopores of MCM-41 with an average pore size of 3 nm were clearly observed. After incorporated with nanoparticles, the pore channels were maintained well, and no TiO₂ particles were detected on the surface of MCM-41. EDS spectrum of TiO₂/MCM-41 (Figure 6) showed the existence of Si, O, and Ti elements with the Ti/Si molar ratio approximatively equal to the experimental value (Ti/Si = 0.4). The HRTEM images of ZTM7 also displayed the ordered hexagonal mesopores without any particles on the surface. Combined with above XRD results, it was concluded that the TiO₂ or ZT nanoparticles were incorporated into the pore channel of MCM-41.

TG-DSC measurements were performed from room temperature to 1100° C to reveal the thermal behavior of three precursors (Figures 7–9). It was well known that the thermal behavior of TiO₂ usually depended on the chemical composition, preparation condition, and existing phases [39]. An endothermic peak at 99°C with mass loss of 13.78% was due to the desorption of physically adsorbed water (Figure 7). Three small exothermic peaks at 200~ 400°C were due to the decomposition and oxidation of organic substances as well as the transformation of TiO₂ from amorphous to anatase phase [40]. Peaks at 400~600°C with mass loss of 16.67% were attributed to the oxidation of residual organic substances and the dehydration of



(c)

FIGURE 5: HRTEM images of (a) MCM-41, (b) TiO₂/MCM-41, and (c) ZTM7 sample.



FIGURE 6: EDS spectrum of TiO₂/MCM-41 sample.

structural water. From the above XRD result, TiO_2 particles were composed of anatase and rutile phases, therefore, the strong peak at 500~600°C also contained the exothermic

peak of phase transformation from anatase to rutile. An exothermic shoulder at 600~800°C could be related to the phase transformation of TiO₂ from anatase to rutile. The DSC curve of TiO₂/MCM-41 was much simpler than that of TiO₂, only one endothermic peak and two exothermic peaks appeared in the DSC curves (Figure 8). The endothermic peak at 70°C was due to the adsorbed water, and the peaks at 323°C and 584°C can be attributed to the oxidation of organic substances and the dehydration of structure water. The whole mass loss of TiO₂/MCM-41 precursor was 17.99%. The amount of TiO₂ incorporated to MCM-41 can be calculated from the mass loss, and the result was basically in accordance with the experimentally designed values. Since the XRD showed that TiO₂/MCM-41 only contained pure anatase phase TiO_2 (Figure 3), the exothermic area from 800~1000°C was directly related to the phase transformation from anatase to rutile. The DSC curve of ZTM7 appeared as a sharp peak at 187°C with a big mass loss of 37.26% (Figure 9), probably presenting the oxidation of organic substances and the decomposition of nitrate. The peaks at 200~600°C were due to the oxidation of residual organic



FIGURE 7: TG-DSC curves of TiO₂ sample.



FIGURE 8: TG-DSC curves of TiO₂/MCM-41 sample.

substances and the dehydration of precursor, accompanying the crystallization of $ZnFe_2O_4$, and the phase transformation of TiO_2 .

 N_2 adsorption-desorption isotherms were carried out to investigate the textural characteristics of the samples (Figure 10). All the isotherms exhibited the typical type IV corresponding to the mesophases, indicating that incorporation of ZnFe₂O₄-TiO₂ did not destroy the integrity of mesoporous MCM-41 host. The specific surface area (S_{BET}) and pore wall thickness of ZTM series became smaller than that of MCM-41 (Table 1), confirming the integrated incorporation of ZT nanoparticles inside the MCM-41 pore channels. The reason that the N2 gas absorption at $P/P_0 = 0$ is not zero is attributed to likely existing plentiful micropores, which lead to degassing incompletely.

Raman spectroscopy is a powerful technique for the investigation of various phases of titanium oxides. Raman spectrum of pure TiO₂ exhibited the vibration modes of anatase phase at 145, 196, 397, 514, 637 cm⁻¹, and rutile phase at 445, 613 cm⁻¹ (Figure 11) [41, 42], but no peaks corresponding to Fe₂O₃, ZnO, and spinel ZnFe₂O₄ was observed in the ZT3 sample, the peaks became broadened



FIGURE 9: TG-DSC curves of ZT7 sample.



FIGURE 10: N_2 adsorption-desorption isotherms of MCM-41, TiO₂/MCM-41, and ZTM series samples.

asymmetrically with the decrease in intensity. One was attributed to the decrease in particle size [41]; another was the breaking of the symmetry of TiO_2 molecular structure resulted from the doping of Zn^{2+} and Fe^{3+} ions in the lattice of TiO_2 [43]. ZTM3 composites only showed the characteristic vibration of anatase, which further demonstrated that MCM-41 can inhibit the phase transformation of TiO_2 , and the broadening of the peaks obviously indicated the smaller particle size of TiO_2 .

An obvious redshift in ZT samples was observed compared with pure TiO₂ (Figure 12), the redshift increased regularly with increasing the Zn/Ti molar ratio. The energy gaps were 2.86, 2.19, 1.83, 1.79, and 1.71 eV corresponding to pure TiO₂ and ZT1, ZT3, ZT5, and ZT7, respectively, the adsorption edges of ZT samples were all in the visible light region, so the addition of ZnFe₂O₄ exactly reduced the energy gaps and made the ZT active in visible light [44]. Though an obvious blue shift in MCM-41/TiO₂ sample

Sample	$S_{\rm BET} (m^2 \cdot g^{-1})$	$V (mL \cdot g^{-1})$	D(nm)	<i>d</i> ₁₀₀ (nm)	<i>a</i> (nm)	<i>t</i> (nm)
MCM-41	830.0	0.64	3.08	3.86	4.46	1.38
ZTM1	657.2	0.49	2.98	3.80	4.39	1.41
ZTM3	838.6	0.64	3.07	3.80	4.39	1.32
ZTM5	655.5	0.46	2.83	3.80	4.39	1.56
ZTM7	724.5	0.52	2.88	3.83	4.42	1.54

TABLE 1: Textural characteristics of MCM-41 and ZTM series samples.

 S_{BET} : BET surface area, V: pore volume, D: average pore diameter, d_{110} : d spacing, a_0 : crystal cell parameter, calculated from $a_0 = 2d_{100}/\sqrt{3}$, and t: wall thickness ($t = a_0 - D$).



FIGURE 11: Raman spectra of different samples. (A: anatase, R: rutile.)

was observed compared with pure TiO₂ (Figure 13), which illustrated that the effect of MCM-41 is that it can be able to control the particle size of TiO₂ and efficiently prevent particles from agglomeration; Figure 13 further showed an obvious redshift in adsorption edge of ZTM compared with pure TiO₂, indicating the interesting application of the assynthesized nanocomposites in the fields of photodegradation and photoelectric devices. The photochemical reactions such as a waste treatment should be developed in the future research.

4. Conclusions

ZnFe₂O₄-TiO₂/MCM-41 (ZTM) nanocomposites with different amount of ZnFe₂O₄ have been successfully synthesized via a sol-gel method. The addition of ZnFe₂O₄ inhibited the growth of TiO₂ particles and promoted the anatase-rutile phase transformation of TiO₂. ZnFe₂O₄-TiO₂ nanoparticles would not destroy the pore structure of MCM-41. The ordered pore structure of MCM-41 can effectively control the growth of TiO₂ nanoparticles. UV-vis absorption edge of ZTM shifted to red regularly with the increase of ZnFe₂O₄ and indicated likely excellent visible-light activity. Our present results showed that the as-synthesized ZTM



FIGURE 12: UV-vis spectra of pure TiO₂ and ZT series samples.



FIGURE 13: UV-vis spectra of TiO₂, MCM-41, TiO₂/MCM-41, and ZTM series samples.

nanocomposite could be a promising multifunctional material in the fields of photodegradation and photoelectric devices.

Acknowledgments

This work was supported by the National Natural Science Foundation of China (50774095) and the Scientific Research Foundation for ROCS of SEM (2011-1139).

References

- S. Luo, Z. Tang, J. Li, and Z. Zhang, "Effect of Ta₂O₅ in (Ca, Si, Ta)-doped TiO₂ ceramic varistors," *Ceramics International*, vol. 34, no. 5, pp. 1345–1347, 2008.
- [2] C. Li, J. Wang, X. Wang, W. Su, H. Chen, and D. Zhuang, "Nonlinear electrical properties of TiO₂-Y₂O₃-Nb₂O₅ capacitor-varistor ceramics," *Materials Science and Engineering B*, vol. 85, no. 1, pp. 6–10, 2001.
- [3] P. G. Su, Y. L. Sun, and C. C. Lin, "Novel low humidity sensor made of TiO₂ nanowires/poly(2-acrylamido-2-methylpropane sulfonate) composite material film combined with quartz crystal microbalance," *Talanta*, vol. 69, no. 4, pp. 946– 951, 2006.
- [4] B. Karunagaran, P. Uthirakumar, S. J. Chung, S. Velumani, and E. K. Suh, "TiO₂ thin film gas sensor for monitoring ammonia," *Materials Characterization*, vol. 58, no. 8-9, pp. 680–684, 2007.
- [5] C. H. Han, D. W. Hong, S. D. Han, J. Gwak, and K. C. Singh, "Catalytic combustion type hydrogen gas sensor using TiO₂ and UV-LED," *Sensors and Actuators, B*, vol. 125, no. 1, pp. 224–228, 2007.
- [6] A. Nasu and Y. Otsubo, "Effects of polymeric dispersants on the rheology and UV-protecting properties of complex suspensions of titanium dioxides and zinc oxides," *Colloids and Surfaces A*, vol. 326, no. 1-2, pp. 92–97, 2008.
- [7] A. Nasu and Y. Otsubo, "Rheology and UV-protecting properties of complex suspensions of titanium dioxides and zinc oxides," *Journal of Colloid and Interface Science*, vol. 310, no. 2, pp. 617–623, 2007.
- [8] L. Zhang, T. Kanki, N. Sano, and A. Toyoda, "Development of TiO₂ photocatalyst reaction for water purification," *Separation* and Purification Technology, vol. 31, no. 1, pp. 105–110, 2003.
- [9] H. Yamashita, H. Nose, Y. Kuwahara, Y. Nishida, S. Yuan, and K. Mori, "TiO₂ photocatalyst loaded on hydrophobic Si₃N₄ support for efficient degradation of organics diluted in water," *Applied Catalysis A*, vol. 350, no. 2, pp. 164–168, 2008.
- [10] J. H. Lee, M. Kang, S. J. Choung et al., "The preparation of TiO₂ nanometer photocatalyst film by a hydrothermal method and its sterilization performance for Giardia lamblia," *Water Research*, vol. 38, no. 3, pp. 713–719, 2004.
- [11] A. Balamurugan, S. Kannan, and S. Rajeswari, "Evaluation of TiO₂ coatings obtained using the sol-gel technique on surgical grade type 316L stainless steel in simulated body fluid," *Materials Letters*, vol. 59, no. 24-25, pp. 3138–3143, 2005.
- [12] A. R. Boccaccini, M. Rossetti, J. A. Roether, S. H. Sharif Zein, and M. Ferraris, "Development of titania coatings on glass foams," *Construction and Building Materials*, vol. 23, no. 7, pp. 2554–2558, 2009.
- [13] Z. Yang, S. Si, X. Zeng, C. Zhang, and H. Dai, "Mechanism and kinetics of apatite formation on nanocrystalline TiO₂ coatings:

- [14] S. Farrokhpay, "TiO₂ pigment suspension behaviour upon adsorption of polymeric dispersants," *Progress in Color, Colorants and Coating*, vol. 3, pp. 66–72, 2010.
- [15] B. Mehdi, M. Shigenao, and K. Atsuki, "The effects of TiO₂ pigmented coatings characteristics on temperature and brightness of a coated black substrate," *Solar Energy*, vol. 86, no. 1, pp. 200–207, 2012.
- [16] S. R. Mukai, H. Nishihara, S. Shichi, and H. Tamon, "Preparation of porous TiO₂ cryogel fibers through unidirectional freezing of hydrogel followed by freeze-drying," *Chemistry of Materials*, vol. 16, no. 24, pp. 4987–4991, 2004.
- [17] H. Yoshitake, T. Sugihara, and T. Tatsumi, "Preparation of wormhole-like mesoporous TiO₂ with an extremely large surface area and stabilization of its surface by chemical vapor deposition," *Chemistry of Materials*, vol. 14, no. 3, pp. 1023– 1029, 2002.
- [18] T. Nakashima and N. Kimizuka, "Interfacial synthesis of hollow TiO₂ microspheres in ionic liquids," *Journal of the American Chemical Society*, vol. 125, no. 21, pp. 6386–6387, 2003.
- [19] E. P. Reddy, B. Sun, and P. G. Smirniotis, "Transition metal modified TiO₂-loaded MCM-41 catalysts for visible- and UVlight driven photodegradation of aqueous organic pollutants," *Journal of Physical Chemistry B*, vol. 108, no. 44, pp. 17198– 17205, 2004.
- [20] H. Haick and Y. Paz, "Long-range effects of noble metals on the photocatalytic properties of titanium dioxide," *Journal of Physical Chemistry B*, vol. 107, no. 10, pp. 2319–2326, 2003.
- [21] F. Zhang, Y. Pi, J. Cui, Y. Yang, X. Zhang, and N. Guan, "Unexpected selective photocatalytic reduction of nitrite to nitrogen on silver-doped titanium dioxide," *Journal of Physical Chemistry C*, vol. 111, no. 9, pp. 3756–3761, 2007.
- [22] P. Cheng, W. Li, T. Zhou, Y. Jin, and M. Gu, "Physical and photocatalytic properties of zinc ferrite doped titania under visible light irradiation," *Journal of Photochemistry and Photobiology A*, vol. 168, no. 1-2, pp. 97–101, 2004.
- [23] G. G. Liu, X. Z. Zhang, Y. J. Xu, X. S. Niu, L. Q. Zheng, and X. J. Ding, "Effect of ZnFe₂O₄ doping on the photocatalytic activity of TiO₂," *Chemosphere*, vol. 55, no. 9, pp. 1287–1291, 2004.
- [24] K. Xu, "Preparation and characterization of nano-ZnFe₂O₄/ TiO₂ films," *Journal of Natural Gas Chemistry*, vol. 16, no. 1, pp. 100–105, 2007.
- [25] V. Hornebecq, M. Antonietti, T. Cardinal, and M. Treguer-Delapierre, "Stable silver nanoparticles immobilized in mesoporous silica," *Chemistry of Materials*, vol. 15, no. 10, pp. 1993– 1999, 2003.
- [26] M. V. Cagnoli, S. G. Casuscelli, A. M. Alvarez et al., "Ti-MCM-41 silylation: development of a simple methodology for its estimation: silylation effect on the activity and selectivity in the limonene oxidation with H₂O₂," *Catalysis Today*, vol. 107-108, pp. 397–403, 2005.
- [27] T. Jiang, Y. Tang, Q. Zhao, and H. Yin, "Effect of Ni-doping on the pore structure of pure silica MCM-41 mesoporous molecular sieve under microwave irradiation," *Colloids and Surfaces A*, vol. 315, no. 1–3, pp. 299–303, 2008.
- [28] M. T. Bore, H. N. Pham, E. E. Switzer, T. L. Ward, A. Fukuoka, and A. K. Datye, "The role of pore size and structure on the thermal stability of gold nanoparticles within mesoporous silica," *Journal of Physical Chemistry B*, vol. 109, no. 7, pp. 2873–2880, 2005.

- [29] H. Yang, C. Du, S. Jin, A. Tang, and G. Li, "Enhanced photoluminescence property of SnO₂ nanoparticles contained in mesoporous silica synthesized with leached talc as Si source," *Microporous and Mesoporous Materials*, vol. 102, no. 1–3, pp. 204–211, 2007.
- [30] M. Bandyopadhyay, A. Birkner, M. W. E. Van Den Berg et al., "Synthesis and characterization of mesoporous MCM-48 containing TiO₂ nanoparticles," *Chemistry of Materials*, vol. 17, no. 15, pp. 3820–3829, 2005.
- [31] H. Yang, Y. Deng, and C. Du, "Synthesis and optical properties of mesoporous MCM-41 containing doped TiO₂ nanoparticles," *Colloids and Surfaces A*, vol. 339, no. 1–3, pp. 111–117, 2009.
- [32] G. H. Li, L. Yang, Y. X. Jin, and L. D. Zhang, "Structural and optical properties of TiO₂ thin film and TiO₂+2 wt.% ZnFe₂O₄ composite film prepared by r.f. sputtering," *Thin Solid Films*, vol. 368, no. 1, pp. 163–167, 2000.
- [33] Y. Jin, G. Li, Y. Zhang, Y. Zhang, and L. Zhang, "Photoluminescence of anatase TiO₂ thin films achieved by the addition of ZnFe₂O₄," *Journal of Physics Condensed Matter*, vol. 13, no. 44, pp. L913–L918, 2001.
- [34] Y. Jin, G. Li, Y. Zhang, Y. Zhang, and L. Zhang, "Fine structures of photoluminescence spectra of TiO₂ thin films with the addition of ZnFe₂O₄," *Journal of Physics D*, vol. 35, no. 11, pp. L37–L40, 2002.
- [35] G. H. Li, Y. C. Wu, and L. D. Zhang, "Effect of ZnFe₂O₄ doping on the optical properties of TiO₂ thin films," *Chinese Physics*, vol. 10, no. 2, pp. 148–151, 2001.
- [36] Z. H. Yuan and L. D. Zhang, "Synthesis, characterization and photocatalytic activity of ZnFe₂O₄/TiO₂ nanocomposite," *Journal of Materials Chemistry*, vol. 11, no. 4, pp. 1265–1268, 2001.
- [37] J. S. Beck, J. C. Vartuli, W. J. Roth et al., "A new family of mesoporous molecular sieves prepared with liquid crystal templates," *Journal of the American Chemical Society*, vol. 114, no. 27, pp. 10834–10843, 1992.
- [38] H. Parala, H. Winkler, M. Kolbe et al., "Confinement of CdSe Nanoparticles Inside MCM-41," *Advanced Materials*, vol. 12, no. 14, pp. 1050–1055, 2000.
- [39] J. Yu, X. Zhao, and Q. Zhao, "Effect of surface structure on photocatalytic activity of TiO₂ thin films prepared by sol-gel method," *Thin Solid Films*, vol. 379, no. 1-2, pp. 7–14, 2000.
- [40] H. E. Chao, Y. U. Yun, H. U. Xingfang, and A. Larbot, "Effect of silver doping on the phase transformation and grain growth of sol-gel titania powder," *Journal of the European Ceramic Society*, vol. 23, no. 9, pp. 1457–1464, 2003.
- [41] T. Ohsaka, F. Izumi, and Y. Fujiki, "Raman spectrum of Anatase, TiO₂," *Journal of Raman Spectroscopy*, vol. 7, no. 6, pp. 321–324, 1978.
- [42] A. Orendorz, A. Brodyanski, J. Lösch et al., "Phase transformation and particle growth in nanocrystalline anatase TiO₂ films analyzed by X-ray diffraction and Raman spectroscopy," *Surface Science*, vol. 601, no. 18, pp. 4390–4394, 2007.
- [43] F. Dong, H. Wang, and Z. Wu, "One-step "Green" synthetic approach for mesoporous C-doped titanium dioxide with efficient visible light photocatalytic activity," *Journal of Physical Chemistry C*, vol. 113, no. 38, pp. 16717–16723, 2009.
- [44] J. Yin, L. J. Bie, and Z. H. Yuan, "Photoelectrochemical property of ZnFe₂O₄/TiO₂ double-layered films," *Materials Research Bulletin*, vol. 42, no. 8, pp. 1402–1406, 2007.