

MeT-DB V2.0: elucidating context-specific functions of N^6 -methyl-adenosine methyltranscriptome

Hui Liu^{1,†}, Huaizhi Wang^{1,†}, Zhen Wei^{2,†}, Songyao Zhang^{3,4}, Gang Hua¹, Shao-Wu Zhang⁴, Lin Zhang¹, Shou-Jiang Gao⁵, Jia Meng^{2,*}, Xing Chen^{1,*} and Yufei Huang^{3,6,*}

¹School of Information and Control Engineering, China University of Mining and Technology, Xuzhou, Jiangsu 221116, China, ²Department of Biological Sciences, Xi'an Jiaotong-Liverpool University, Suzhou, Jiangsu 215123, China, ³Department of Electrical and Computer Engineering, the University of Texas at San Antonio, San Antonio, TX 78249, USA, ⁴Key Laboratory of Information Fusion Technology of Ministry of Education, School of Automation, Northwestern Polytechnical University, Xi'an 710072, China, ⁵Department of Molecular Microbiology and Immunology, Keck School of Medicine, University of Southern California, Los Angeles, CA 90033, USA and ⁶Department of Epidemiology and Biostatistics, University of Texas Health at San Antonio, San Antonio, TX 78229, USA

Received September 15, 2017; Revised October 16, 2017; Editorial Decision October 17, 2017; Accepted November 06, 2017

ABSTRACT

Methyltranscriptome is an exciting new area that studies the mechanisms and functions of methylation in transcripts. A knowledge base with the systematic collection and curation of context specific transcriptome-wide methylations is critical for elucidating their biological functions as well as for developing bioinformatics tools. Since its inception in 2014, the Met-DB (Liu, H., Flores, M.A., Meng, J., Zhang, L., Zhao, X., Rao, M.K., Chen, Y. and Huang, Y. (2015) MeT-DB: a database of transcriptome methylation in mammalian cells. *Nucleic Acids Res.*, 43, D197–D203), has become an important resource for methyltranscriptome, especially in the N^6 -methyl-adenosine (m^6A) research community. Here, we report Met-DB v2.0, the significantly improved second version of Met-DB, which is entirely redesigned to focus more on elucidating context-specific m^6A functions. Met-DB v2.0 has a major increase in context-specific m^6A peaks and single-base sites predicted from 185 samples for 7 species from 26 independent studies. Moreover, it is also integrated with a new database for targets of m^6A readers, erasers and writers and expanded with more collections of functional data. The redesigned Met-DB v2.0 web interface and genome browser provide more friendly, powerful, and informative ways to query and visualize the data. More importantly, MeT-DB v2.0 offers for the first time a series of tools specifically

designed for understanding m^6A functions. Met-DB V2.0 will be a valuable resource for m^6A methyltranscriptome research. The Met-DB V2.0 database is available at <http://compgenomics.utsa.edu/MeTDB/> and <http://www.xjtlu.edu.cn/metdb2>.

INTRODUCTION

Methyltranscriptome is an exciting, emerging area that studies methylation in the transcriptome. In contrast to well-established DNA methylation, transcriptome methylation is largely an uncharted territory. Among different types, N^6 -methyl-adenosine (m^6A) is the most abundant and intensively studied transcriptome methylation, existing in transcriptomes of mammalian and other organisms. Through methylated RNA immunoprecipitation sequencing (MeRIP-seq) (1), m^6A has been found to exist in >25% mRNAs in mammalian cells, particularly enriched near stop codon and with a consensus RRACH motif (R = G or A; H = A, C or U) (2). m^6A is also found to be highly dynamic (3). It is catalyzed by 'writers' or m^6A methylases METTL3 and METTL14, two interacting with the Wilms Tumor 1 Associated Protein (WTAP) (4) to form methyltransferase complex (5). This methylation can also be reversed by 'erasers' including the alkylated DNA repair protein (ALKBH5) (6) and the obesity associated protein (FTO) (3) (less effective *in vivo* (7)). In addition to writers and erasers, m^6A -binding proteins such as YTH protein family have been identified as m^6A readers, which can mediate the biological function of m^6A through selectively recognizing and binding to m^6A . A close relationship between m^6A and mRNA metabolism has also been established, and

*To whom correspondence should be addressed. Tel: +1 210 458 6270; Fax: +1 210 458 5947; Email: yufei.huang@utsa.edu
Correspondence may also be addressed to Xing Chen. Tel: +86 516 8359 0818; Fax: +1 210 8359 0818; Email: xingchen@cumt.edu.cn
Correspondence may also be addressed to Jia Meng. Tel: +86 512 8188 0492; Fax: +86 512 81880440; Email: jia.meng@xjtlu.edu.cn

[†]These authors contributed equally to the paper as first authors.

m⁶A is involved in regulating diseases and virus infection (5,6,8–14). These exciting findings have spurred intense research recently on roles of m⁶A in regulating different physiological processes as well as their potential as therapeutic targets (5,6,11,14–21).

MeT-DB (22), established in 2014, was the first comprehensive database focusing on m⁶A methyltranscriptome. Since then, a large additional number of MeRIP-seq datasets produced under different experimental conditions have been released (Supplementary Figure S1). Moreover, a series of bioinformatics tools have been developed for predicting m⁶A peaks (exomePeak (23), MeTPeak (24)) and differential m⁶A analysis (exomePeak, MeTDiff (25)), for visualizing the characteristics of peaks in transcripts (Guitar (26)), and for predicting context-specific m⁶A driver genes and networks (m⁶A-Driver (27)).

Here, we present the second version of MeT-DB, which has been entirely redesigned to focus more on helping elucidate context-specific m⁶A functions (Figure 1). Compared with MeT-DB, MeT-DB V2.0 has ~2.5× MeRIP-seq samples and ~7.6× predicted m⁶A peaks from 7 species and 26 studies. Particularly, a new database, TREW, which includes over 118k targets of eight different m⁶A readers, erasers and writers is also integrated. MeT-DB V2.0 also expands the collections of other functional data such as micro-RNA target sites, Single nucleotide polymorphisms (SNPs), binding sites of splicing factor as well as RNA-binding proteins (RBPs), and information about cancer genes. MeT-DB v2.0 adopts a table view interface with multiple query options to deliver diverse information about m⁶A in parallel. MeT-DB v2.0 also replaces the original genome browser with a more efficient and powerful genome browser to be able to display 979 tracks for all species in a standard manner. More importantly, MeT-DB v2.0 also offers for the first time a series of tools specifically designed for understanding m⁶A functions. We discuss next the detailed improvements in database and web interface.

MATERIALS AND METHODS

MeRIP-seq data processing

MeRIP-seq experimental information of all collected studies was obtained from the original papers or NCBI Gene Expression Omnibus, while raw sequencing data samples were downloaded from short read archive.

To detect m⁶A peaks, sequencing data quality was first evaluated by FASTQC (v0.11.4). Adaptors or low quality nucleotides were removed by Trim Galore (v0.4.2) according to the evaluation results of FastQC. Then, reads in the IP/Input FASTQ files were aligned to the genome by Tophat2 (v2.1.0) (28) with default options to generate IP/Input BAM files. BAM files were subsequently converted to bigwig files for visualization. Peak calling was performed on the input and IP BAM files by exomePeak (23). For each predicted m⁶A peak, its chromosomal location including start/end position, strand information, *P*-value, fold enrichment and *q*-value (FDR) were reported. For each sample, sequence motifs of predicted m⁶A peaks were obtained using the MEME (v4.11.2) (29) suite and the peak

distribution at a transcript level was also plotted by the Guitar package (26).

Single-base m⁶A sites were also predicted by searching the RRACH motif in peaks identified by exomePeak. Transcript sequences of the peak region that contain only exons were first extracted, from which the location of RRACH motifs was identified. The genome positions of 'A' in the identified motifs were annotated as single-base m⁶A sites. The distances of the predicted single-base m⁶A sites to their corresponding peak center were also calculated as the confidence scores of the prediction.

Transcriptome-wide expression levels for each sample were also calculated based on the aligned BAM files of the MeRIP-seq input samples; cufflinks (v4.11.2) (30) with default settings was employed to calculate the gene/isoform expression Fragments Per Kilobase of transcript per Million mapped reads (FPKM) values and the reads counts generated by HTSeq (v0.6.1) (31) were also provided to facilitate further analysis.

TREW data preparing

TREW or the Target of m⁶A readers, erasers and writers is our newly constructed database about the binding sites of m⁶A methyltransferases (METTL3, WTAP, METTL14 and KIAA1429), demethylases (FTO and ALKBH5) and readers (YTH family proteins). (Supplementary Figure S2). To determine the target sites, ParCLIP-seq data were retrieved directly from original publications, where the raw data were first processed with Trim Galore and FASTX-Toolkit (v0.0.13) for quality control, and then aligned to human hg19 or mouse mm10 reference genome respectively with Tophat2. Also, differential m⁶A analysis was performed with exomePeak and QNB (32) packages under the default setting on MeRIP-seq data of m⁶A methylase or demethylase perturbation. The significant differential m⁶A peaks after perturbation were determined to the target peaks.

Techniques

All datasets were processed and stored in a MySQL Database Management System installed on an X86–64 server with CentOS Linux OS. The database consists of 60 tables that comprise ~41 million records. The database query, genome browser and user interface were developed using PHP, JavaScript, jQuery and Bootstrap frameworks.

RESULTS

Content of database

Core MeT-DB V2.0 database. We expanded the number of MeRIP-seq samples in this update from 74 to 185, which come from 26 independent studies covering 7 species (Supplementary Figure S3 and Table S1) (1,2,9,11,13–15,17,19–21,33–47). More than 2.6 million m⁶A peaks and 1.1 million single-base sites were identified from these 185 samples. Annotation information was generated, including the transcript identifiers (UCSC ID, Entrez Gene ID, Gene Symbol and RefSeq ID), the transcript location information (5'UTR/CDS/3'UTR) and information regarding if




Figure 1. Overall design of MeT-DB V2.0 database. MeT-DB V2.0 is composed of the database and web interface. The MeT-DB database includes the core database that contains context-specific m⁶A peaks and single-base sites, the TREW database that contains target sites of m⁶A readers, writers and erasers, and the functional database such as micro-RNA target sites, binding sites of RNA binding proteins and information about cancer genes. There are three functional modules in the web interface: table view facilitates researcher to explore and search the data in detail, the genome browser helps the user visualize and compare m⁶A peaks and functions data, and the tool module includes two useful web servers for investigating the functions of m⁶A methyltranscriptome.

the peak is on mRNA/lncRNA. Despite considerable variation in the numbers of detected m⁶A peaks across different MeRIP-seq conditions, the most enriched consensus sequences are all similar to the previously reported RRACH motif of m⁶A, suggesting that the exomePeak detected m⁶A peaks should have high specificity.

All the processing results, including m⁶A peaks, single-base m⁶A sites, motif, peak distribution plot, gene expression profiles, were stored in the MeT-DB core database and can be downloaded from the web page. The scale of data with comparison with MeT-DB V1.0 is summarized in Table 1.

TREW database. We collected ParCLIP-seq and MeRIP-seq samples for eight regulator/reader proteins (including FTO, KIAA1429, METTL14, METTL3, WTAP, HNRNPC, YTHDC1 and YTHDF1) from 10 independent studies (Supplementary Table S2) (8,9,15,20,21,36,47–50). Finally, a total of 118,164 m⁶A modifications sites that preferentially targeted by a specific protein regulator are collected or detected. The target sites are further annotated with transcript regions (5'UTR, CDS, 3'UTR, stop codon, transcription start sites and miRNA target site) and RNA types (tRNA, mRNA, lncRNA and snRNA). Target sites were also converted to hg38 and mm9 by UCSC liftOver tool (51). This information is essential for understanding the biological functions of m⁶A.

Functional data. To help understand the regulatory roles of m⁶A, we also integrated the following six relevant functional datasets into the MeT-DB v2.0 database.

miRNA target sites. Predicted miRNA target sites from TargetScan (version 7.1) (52) for human and mouse as well as from miRanda for human, mouse and fly (August 2010 release) (53) were included. Furthermore, experimentally validated miRNA and target genes interaction pair information for human, mouse, zebrafish and fly were downloaded from miRTarBase (54).

Splicing factor binding sites. A total of 655 and 125 binding sites of human and mouse splicing factors, respectively, were obtained from SpliceAidF(v1.1 03/2013) (55). Each site includes the name of the binding splicing factor and the genome location of the binding site.

SNP. 40627 human literature-derived collected SNP-trait associations of 30044 SNPs obtained from GWAS (All associations v1.0.1) (56) were included.

RBP-binding site. PAR-CLIP and HITS-CLIP detected binding locations of 24 human and 5 mouse RBPs were retrieved from StarBase version 2.0 (57) and included in the database.

Cancer related genes. A total of 761 human and 628 mouse tumor suppressor genes were obtained from TS-Gene database version 2.0 (58). Also, 576 cancer genes were downloaded from COSMIC (v82) (59).

These relevant functional data are displayed as part of the query output of the core MeT-DB database. Each functional dataset can also be downloaded from the website.

Table 1. Total number of identified m⁶A peaks and single-base m⁶A sites

Species	Included		Studies		Samples		m ⁶ A Peaks		Single-base m ⁶ A in V2.0		Genome assembly
	V1.0	V2.0	V1.0	V2.0	V1.0	V2.0	V1.0	V2.0	Total	AVG. supp ¹	
<i>Homo sapiens</i>	Y	Y	4	13	16	75	2.1E + 5	1.3E + 6	4.3E + 5	14.5	hg19/hg38
<i>Mus musculus</i>	Y	Y	2	8	6	52	1.4E + 5	1.1E + 6	5.4E + 5	10.7	mm9/mm10
<i>Sus scrofa</i>		Y		1		3		1.3E + 4	2.9E + 4	2.4	susScr3
<i>Danio rerio</i>		Y		1		5		2.4E + 4	3.7E + 4	2.8	danRer10
<i>Drosophila melanogaster</i>		Y		1		2		83	92	1.4	dm6
<i>Saccharomyces cerevisiae</i>		Y		1		34		1.8E + 5	6.9E + 4	11.4	R64-1-1
<i>Arabidopsis thaliana</i>		Y		3		14		7.9E + 4	7.4E + 4	3.5	tair10
Total	2	7	5	26	22	185	3.5E + 5	2.6E + 6	1.1E + 6		

Comparison of MeRIP-seq data collection and procession results between MeT-DB V1.0 and MeT-DB V2.0.

¹AVG. supp (average support number) stands for average number of MeRIP-Seq samples that support each single-based m⁶A site.

Table view interface and query the database

To facilitate the examination of the context-specific samples and the query of the entries of the database, MeT-DB V2.0 included a table view interface (Supplementary Figure S4) based on DataTables jQuery plug-in. A table view presents information of every genomic features of an m⁶A peak/site as a row, thus simultaneously offering a large amount of information about m⁶A. It can also show the potential interactions between a particular m⁶A peak/site with other transcriptome features and functional data. Presenting this rich information can provide multifaceted perspectives of m⁶A methylation and help generate hypotheses of their potential biological functions. Moreover, the table view provides flexible ways to search the large database, making MeT-DB V2.0 a powerful platform for discovering the biological functions of m⁶A.

Three different ways of querying the database are made available through the MeT-DB web page, namely by samples, by m⁶A peaks and by single-base m⁶A sites, providing information about m⁶A methyltranscriptome at different scales ranging from a global perspective to a single-nucleotide resolution. The search-by-sample function aims to provide the user with a comprehensive view of context-specific m⁶A methyltranscriptome. The query takes sample ID, experiments, species, cell line or tissue as input and returns transcriptome-wide information about m⁶A. For each returned sample, the user can investigate the m⁶A peak distribution at a transcript level and m⁶A peak sequence motif and download the BED file, detailed information of the transcriptome-wide predicted m⁶A peaks, the gene and isoform expression FPKMs and sample reads counts. The search-by-peak and search-by-site functions instead deliver information about predicted m⁶A peaks and single-base site integrated from all the samples and display it in the table view interface. For each peak/site, the genomic location, associated gene name/ID, peak enrichment fold change, prediction confidence and the number of other peaks/sites from other samples that overlap with this queried m⁶A peak/site are displayed in the columns of the table. To further facilitate functional discovery, additional functional information including overlapped binding sites of m⁶A readers, writer and erasers, binding sites of RNA-binding proteins and slicing factors, miRNA target sites, SNPs and status of its association with a tumor suppressor or a cancer gene is also provided in the columns of the table view. Col-

umn specific search, located at the bottom of the table, further enables the search within a corresponding column. Advanced filtering functions are also implemented to allow the user to further restrict their search by any entry attribute such as genome location, *P*-value, score, gene name, transcript name, etc. These query functions should allow users to screen out most relevant elements from the huge information stored in the MeT-DB database. Users can also export data by clicking export buttons under any search conditions for offline investigation. Besides, users can view the detailed information of a specific entry in the genome browser by clicking the genome browser icon at the very left end of each row.

Genome browser

MeT-DB originally included a self-constructed genome browser to graphically illustrate the genomic features and context of m⁶A peaks. To provide an efficient service on MeT-DB data of a much larger scale, MeT-DB v2.0 replaced the old genome browser with JBrowse (60). JBrowse is a lightweight open source, JavaScript-based genome browser that effectively renders most genomic features on the client machine rather than the server. Besides, JBrowse contains more dynamic visualization capabilities and commonly used functions. With this significant update, the response speed of genome browser is much quick comparing to the old version.

All information of MeRIP-Seq data, TREW and other functional datasets have been converted to BED, GFF or BigWig format and imported into JBrowse as tracks. Furthermore, categories as well as attributes of each track have been described explicitly for generating track filter function module. Based on this module, users can screen out their interested ones among hundreds of tracks by JBrowse track filtering panel.

Guitar plot

The ability to visualize the distribution of m⁶A at a transcript level and compare the differences of such distribution under the different condition is very important in generating new hypotheses about m⁶A functions. Guitar plot (26) is a tool designed for visualizing the transcript level m⁶A distribution. It can also be used to visualize distributions of any other type of genome features and transcriptome

methyations stored in BED files. MeT-DB V2.0 includes a web server for Guita to generate the plots of m⁶A distribution from user custom data. The web server brings the full capability of Guita to generate not only the distribution plot of a single sample but also the plot that compares distributions from multiple samples. The plot is in PDF format and is publication ready.

m⁶A-Driver

m⁶A-Driver (27) is a published tool for predicting m⁶A-driven genes and associated networks, whose functional interactions are likely to be actively modulated by m⁶A methylation under a particular condition. MeT-DB V2.0 also includes a web server for m⁶A-Driver to generate m⁶A-driven genes and associated networks from user custom data samples. The inputs to the m⁶A-Driver web server are txt files, each containing a list of official gene symbols, representing a replicate sample of context-specific m⁶A targeted genes under a case-control condition obtained from, for instance, differential m⁶A analysis using exomePeak or MetDiff. m⁶A-Driver predicts m⁶A driven genes from the provided gene lists by assessing their topological and biological significance using a random walk with restart algorithm applied to the protein–protein interaction network. The output of m⁶A-Driver web server contains two files; one is a text that contains m⁶A driven genes and the edges of underlying m⁶A driven gene network and the second file is the figure of the network.

Data download and export

All MeT-DB V2.0 data samples including transcriptome-wide m⁶A peaks and single-base sites, TREW dataset and six functional data files are available for downloading on the download web page. Transcript-level peak distribution, m⁶A sequence motif, gene/isoform FPKM expression levels, reads counts for each MeRIP-seq experiment can be downloaded in detail information region of MeT-DB Core experiments table view web page. User query or filtering results of each table can also be downloaded in a comma-separated value or tab-delimited text format, accessible via the export buttons above the corresponding table.

CONCLUSION

MeT-DB V2.0 is a comprehensive and significantly enhanced database with a redesigned web interface. By collecting and integrating more MeRIP-seq samples, functional datasets and tools in one place, we believe that MeT-DB V2.0 can help accelerate the discovery of the unrecognized regulatory roles of m⁶A and foster the further development of bioinformatics tools for methyltranscriptome research. Comparing with the RMBase (61), another database for RNA modifications, MeT-DB V2.0 not only included more MeRIP-seq experiments from different studies, species and conditions, but also provided more functional data, additional web tools and convenient access to condition-specific RNA methylation information for functional studies.

m⁶A and methyltranscriptome research is a fast evolving area, with exciting discoveries and new datasets being published with an unprecedented pace. To appropriately reflect

the development of this research, the MeT-DB database needs to be continuously updated and improved. Specific areas that will see further updates include: (i) continuously collecting published MeRIP-seq samples and carrying out predictions of m⁶A peaks/sites, (ii) including other types of post-transcriptional methylations once the corresponding data samples are enough for us to build a high-quality database, (iii) improving user interface to improve the ability to mine information from database and (iv) providing more web server tools for methyltranscriptome data analysis and functional prediction. We envision that MeT-DB would become the central resource for data and discovery hub for methyltranscriptome research.

AVAILABILITY

The MeT-DB V2.0 database is available at <http://compgenomics.utsa.edu/MeTDB/> and <http://www.xjtlu.edu.cn/metdb2>.

SUPPLEMENTARY DATA

Supplementary Data are available at NAR Online.

ACKNOWLEDGEMENTS

We are grateful for the computational support from the UTSA as well as the Advanced Analysis and Computation Center of CUMT.

FUNDING

China Fundamental Research Funds for the Central Universities [2014QNA84 to H.L.]; National Natural Science Foundation of China [31671373, 61401370 to J.M., 61473232 to S.Z., 61772531, 11631014 to X.C., 61501466 to L.Z.]; National Institute of Health [R01GM113245 to Y.H., R01CA124332 to S.J.G.]. Funding for open access charge: National Natural Science Foundation of China.

Conflict of interest statement. None declared.

REFERENCES

- Meyer, K.D., Saletore, Y., Zumbo, P., Elemento, O., Mason, C.E. and Jaffrey, S.R. (2012) Comprehensive analysis of mRNA methylation reveals enrichment in 3' UTRs and near stop codons. *Cell*, **149**, 1635–1646.
- Dominissini, D., Moshitch-Moshkovitz, S., Schwartz, S., Salmon-Divon, M., Ungar, L., Osenberg, S., Cesarkas, K., Jacob-Hirsch, J., Amariglio, N., Kupiec, M. *et al.* (2012) Topology of the human and mouse m⁶A RNA methylomes revealed by m⁶A-seq. *Nature*, **485**, 201–206.
- Jia, G., Fu, Y., Zhao, X., Dai, Q., Zheng, G., Yang, Y., Yi, C., Lindahl, T., Pan, T. and Yang, Y.-G. (2011) N⁶-methyladenosine in nuclear RNA is a major substrate of the obesity-associated FTO. *Nat. Chem. Biol.*, **7**, 885–887.
- Nilsen, T.W. (2014) Internal mRNA methylation finally finds functions. *Science*, **343**, 1207–1208.
- Ping, X.-L., Sun, B.-F., Wang, L., Xiao, W., Yang, X., Wang, W.-J., Adhikari, S., Shi, Y., Lv, Y., Chen, Y.-S. *et al.* (2014) Mammalian WTAP is a regulatory subunit of the RNA N⁶-methyladenosine methyltransferase. *Cell Res.*, **24**, 177–189.
- Zheng, G., Dahl, J.A., Niu, Y., Fedorcsak, P., Huang, C.-M., Li, C.J., Vågbo, C.B., Shi, Y., Wang, W.-L. and Song, S.-H. (2013) ALKBH5 is a mammalian RNA demethylase that impacts RNA metabolism and mouse fertility. *Mol. Cell*, **49**, 18–29.

7. Mauer, J., Luo, X., Blanjoie, A., Jiao, X., Grozhik, A.V., Patil, D.P., Linder, B., Pickering, B.F., Vasseur, J.-J., Chen, Q. *et al.* (2017) Reversible methylation of m6Am in the 5' cap controls mRNA stability. *Nature*, **541**, 371–375.
8. Wang, X., Zhao, B.S., Roundtree, I.A., Lu, Z., Han, D., Ma, H., Weng, X., Chen, K., Shi, H. and He, C. (2015) N(6)-methyladenosine modulates messenger RNA translation efficiency. *Cell*, **161**, 1388–1399.
9. Zhou, J., Wan, J., Gao, X., Zhang, X., Jaffrey, S.R. and Qian, S.-B. (2015) Dynamic m(6)A mRNA methylation directs translational control of heat shock response. *Nature*, **526**, 591–594.
10. Yang, Y., Fan, X., Mao, M., Song, X., Wu, P., Zhang, Y., Jin, Y., Yang, Y., Chen, L.-L., Wang, Y. *et al.* (2017) Extensive translation of circular RNAs driven by N6-methyladenosine. *Cell Res.*, **27**, 626–641.
11. Fustin, J.-M., Doi, M., Yamaguchi, Y., Hida, H., Nishimura, S., Yoshida, M., Isagawa, T., Morioka, M.S., Kakeya, H., Manabe, I. *et al.* (2013) RNA-methylation-dependent RNA processing controls the speed of the circadian clock. *Cell*, **155**, 793–806.
12. Slobodin, B., Han, R., Calderone, V., Vrieling, J.A.F.O., Loayza-Puch, F., Elkon, R. and Agami, R. (2017) Transcription impacts the efficiency of mRNA translation via co-transcriptional N6-adenosine methylation. *Cell*, **169**, 326–337.
13. Alarcon, C.R., Lee, H., Goodarzi, H., Halberg, N. and Tavazoie, S.F. (2015) N6-methyladenosine marks primary microRNAs for processing. *Nature*, **519**, 482–485.
14. Chen, T., Hao, Y.-J., Zhang, Y., Li, M.-M., Wang, M., Han, W., Wu, Y., Lv, Y., Hao, J. and Wang, L. (2015) m6A RNA methylation is regulated by microRNAs and promotes reprogramming to pluripotency. *Cell Stem Cell*, **16**, 289–301.
15. Hess, M.E., Hess, S., Meyer, K.D., Verhagen, L.A.W., Koch, L., Bronneke, H.S., Dietrich, M.O., Jordan, S.D., Saletore, Y., Elemento, O. *et al.* (2013) The fat mass and obesity associated gene (Fto) regulates activity of the dopaminergic midbrain circuitry. *Nat. Neurosci.*, **16**, 1042–1048.
16. Haussmann, I.U., Bodi, Z., Sanchez-Moran, E., Mongan, N.P., Archer, N., Fray, R.G. and Soller, M. (2016) m6A potentiates Sxl alternative pre-mRNA splicing for robust *Drosophila* sex determination. *Nature*, **540**, 301–304.
17. Lence, T., Akhtar, J., Bayer, M., Schmid, K., Spindler, L., Ho, C.H., Kreim, N., Andrade-Navarro, M.A., Poeck, B., Helm, M. *et al.* (2016) m6A modulates neuronal functions and sex determination in *Drosophila*. *Nature*, **540**, 242–247.
18. Wang, Y., Li, Y., Toth, J.I., Petroski, M.D., Zhang, Z. and Zhao, J.C. (2014) N6-methyladenosine modification destabilizes developmental regulators in embryonic stem cells. *Nat. Cell Biol.*, **16**, 191–198.
19. Batista, P.J., Molinie, B., Wang, J., Qu, K., Zhang, J., Li, L., Bouley, D.M., Lujan, E., Haddad, B., Daneshvar, K. *et al.* (2014) m(6)A RNA modification controls cell fate transition in mammalian embryonic stem cells. *Cell Stem Cell*, **15**, 707–719.
20. Geula, S., Moshitch-Moshkovitz, S., Dominissini, D., Mansour, A.A., Kol, N., Salmon-Divon, M., Hershkovitz, V., Peer, E., Mor, N., Manor, Y.S. *et al.* (2015) m6A mRNA methylation facilitates resolution of naive pluripotency toward differentiation. *Science*, **347**, 1002–1006.
21. Schwartz, S., Mumbach, M.R., Jovanovic, M., Wang, T., Maciag, K., Bushkin, G.G., Mertins, P., Ter-Ovanesyan, D., Habib, N., Cacchiarelli, D. *et al.* (2014) Perturbation of m6A writers reveals two distinct classes of mRNA methylation at internal and 5' sites. *Cell Rep.*, **8**, 284–296.
22. Liu, H., Flores, M.A., Meng, J., Zhang, L., Zhao, X., Rao, M.K., Chen, Y. and Huang, Y. (2015) MeT-DB: a database of transcriptome methylation in mammalian cells. *Nucleic Acids Res.*, **43**, D197–D203.
23. Meng, J., Cui, X., Rao, M.K., Chen, Y. and Huang, Y. (2013) Exome-based analysis for RNA epigenome sequencing data. *Bioinformatics*, **29**, 1565–1567.
24. Cui, X., Meng, J., Zhang, S., Chen, Y. and Huang, Y. (2016) A novel algorithm for calling mRNA m6A peaks by modeling biological variances in MeRIP-seq data. *Bioinformatics*, **32**, i378–i385.
25. Cui, X., Zhang, L., Meng, J., Rao, M., Chen, Y. and Huang, Y. (2015) MeTDiff: a novel differential RNA methylation analysis for MeRIP-seq data. *IEEE/ACM Trans. Comput. Biol. Bioinformatics*, **99**, 1.
26. Cui, X., Wei, Z., Zhang, L., Liu, H., Sun, L., Zhang, S.-W., Huang, Y. and Meng, J. (2016) Guitar: an R/bioconductor package for gene annotation guided Transcriptomic analysis of RNA-related genomic features. *BioMed. Res. Int.*, **2016**, 8367534.
27. Zhang, S.-Y., Zhang, S.-W., Liu, L., Meng, J. and Huang, Y. (2016) m6A-Driver: identifying context-specific mRNA m6A methylation-driven gene interaction networks. *PLoS Comput. Biol.*, **12**, e1005287.
28. Kim, D., Pertea, G., Trapnell, C., Pimentel, H., Kelley, R. and Salzberg, S.L. (2013) TopHat2: accurate alignment of transcriptomes in the presence of insertions, deletions and gene fusions. *Genome Biol.*, **14**, R36.
29. Bailey, T.L., Boden, M., Buske, F.A., Frith, M., Grant, C.E., Clementi, L., Ren, J., Li, W.W. and Noble, W.S. (2009) MEME SUITE: tools for motif discovery and searching. *Nucleic Acids Res.*, **37**, W202–W208.
30. Roberts, A., Trapnell, C., Donaghey, J., Rinn, J.L. and Pachter, L. (2011) Improving RNA-seq expression estimates by correcting for fragment bias. *Genome Biol.*, **12**, R22.
31. Anders, S., Pyl, P.T. and Huber, W. (2015) HTSeq—a Python framework to work with high-throughput sequencing data. *Bioinformatics*, **31**, 166–169.
32. Liu, L., Zhang, S.-W., Huang, Y. and Meng, J. (2017) QNB: differential RNA methylation analysis for count-based small-sample sequencing data with a quad-negative binomial model. *BMC Bioinformatics*, **18**, 387.
33. Berulava, T., Rahmann, S., Rademacher, K., Klein-Hitpass, L. and Horsthemke, B. (2015) N6-adenosine methylation in MiRNAs. *PLoS One*, **10**, e0118438.
34. Gokhale, N.S., McIntyre, A.B.R., McFadden, M.J., Roder, A.E., Kennedy, E.M., Gandara, J.A., Hopcraft, S.E., Quicke, K.M., Vazquez, C., Willer, J. *et al.* (2016) N6-methyladenosine in Flaviviridae viral RNA genomes regulates infection. *Cell Host Microbe*, **20**, 654–665.
35. He, S., Wang, H., Liu, R., He, M., Che, T., Jin, L., Deng, L., Tian, S., Li, Y., Lu, H. *et al.* (2017) mRNA N6-methyladenosine methylation of postnatal liver development in pig. *PLoS One*, **12**, e0173421.
36. Li, Z., Weng, H., Su, R., Weng, X., Zuo, Z., Li, C., Huang, H., Nachtergaele, S., Dong, L., Hu, C. *et al.* (2017) FTO plays an oncogenic role in acute myeloid leukemia as a N6-methyladenosine RNA demethylase. *Cancer Cell*, **31**, 127–141.
37. Lichinchi, G., Gao, S., Saletore, Y., Gonzalez, G.M., Bansal, V., Wang, Y., Mason, C.E. and Rana, T.M. (2016) Dynamics of the human and viral m(6)A RNA methylomes during HIV-1 infection of T cells. *Nat. Microbiol.*, **1**, 16011.
38. Lichinchi, G., Zhao, B.S., Wu, Y., Lu, Z., Qin, Y., He, C. and Rana, T.M. (2016) Dynamics of human and viral RNA methylation during zika virus infection. *Cell Host Microbe*, **20**, 666–673.
39. Lin, S., Choe, J., Du, P., Triboulet, R. and Gregory, R.I. (2016) The m(6)A methyltransferase METTL3 promotes translation in human cancer cells. *Mol. Cell*, **62**, 335–345.
40. Luo, G.-Z., MacQueen, A., Zheng, G., Duan, H., Dore, L.C., Lu, Z., Liu, J., Chen, K., Jia, G., Bergelson, J. *et al.* (2014) Unique features of the m6A methylome in *Arabidopsis thaliana*. *Nat. Commun.*, **5**, 5630.
41. Schwartz, S., Agarwala, S.D., Mumbach, M.R., Jovanovic, M., Mertins, P., Shishkin, A., Tabach, Y., Mikkelsen, T.S., Satija, R., Ruvkun, G. *et al.* (2013) High-resolution mapping reveals a conserved, widespread, dynamic mRNA methylation program in yeast meiosis. *Cell*, **155**, 1409–1421.
42. Shen, L., Liang, Z., Gu, X., Chen, Y., Teo, Z.W.N., Hou, X., Cai, W.M., Dedon, P.C., Liu, L. and Yu, H. (2016) N(6)-methyladenosine RNA modification regulates shoot stem cell fate in *Arabidopsis*. *Dev. Cell*, **38**, 186–200.
43. Tirumuru, N., Zhao, B.S., Lu, W., Lu, Z., He, C. and Wu, L.-G. (2016) N(6)-methyladenosine of HIV-1 RNA regulates viral infection and HIV-1 Gag protein expression. *Elife*, **5**, e15528.
44. Wan, Y., Tang, K., Zhang, D., Xie, S., Zhu, X., Wang, Z. and Lang, Z. (2015) Transcriptome-wide high-throughput deep m(6)A-seq reveals unique differential m(6)A methylation patterns between three organs in *Arabidopsis thaliana*. *Genome Biol.*, **16**, 272.
45. Wang, X., Lu, Z., Gomez, A., Hon, G.C., Yue, Y., Han, D., Fu, Y., Parisien, M., Dai, Q., Jia, G. *et al.* (2013) N6-methyladenosine-dependent regulation of messenger RNA stability. *Nature*, **505**, 117–120.
46. Zhao, B.S., Wang, X., Beadell, A.V., Lu, Z., Shi, H., Kuuspalu, A., Ho, R.K. and He, C. (2017) m6A-dependent maternal mRNA

- clearance facilitates zebrafish maternal-to-zygotic transition. *Nature*, **542**, 475–478.
47. Zhao, X., Yang, Y., Sun, B.-F., Shi, Y., Yang, X., Xiao, W., Hao, Y.-J., Ping, X.-L., Chen, Y.-S., Wang, W.-J. *et al.* (2014) FTO-dependent demethylation of N6-methyladenosine regulates mRNA splicing and is required for adipogenesis. *Cell Res.*, **24**, 1403–1419.
 48. Liu, J., Yue, Y., Han, D., Wang, X., Fu, Y., Zhang, L., Jia, G., Yu, M., Lu, Z., Deng, X. *et al.* (2014) A METTL3-METTL14 complex mediates mammalian nuclear RNA N6-adenosine methylation. *Nat. Chem. Biol.*, **10**, 93–95.
 49. Liu, N., Dai, Q., Zheng, G., He, C., Parisien, M. and Pan, T. (2015) N(6)-methyladenosine-dependent RNA structural switches regulate RNA-protein interactions. *Nature*, **518**, 560–564.
 50. Xiang, W., Jing, F., Yuan, X., Guan, Z., Zhang, D., Zhu, L., Zhou, G., Qiang, W., Huang, J. and Tang, C. (2016) Structural basis of N6-adenosine methylation by the METTL3–METTL14 complex. *Nature*, **534**, 575–578.
 51. Tyner, C., Barber, G.P., Casper, J., Clawson, H., Diekhans, M., Eisenhart, C., Fischer, C.M., Gibson, D., Gonzalez, J.N. and Guruvadoo, L. (2016) The UCSC Genome Browser database: 2017 update. *Nucleic Acids Res.*, **45**, D626–D634.
 52. Lewis, B.P., Burge, C.B. and Bartel, D.P. (2005) Conserved seed pairing, often flanked by adenosines, indicates that thousands of human genes are microRNA targets. *Cell*, **120**, 15–20.
 53. Betel, D., Koppal, A., Agius, P., Sander, C. and Leslie, C. (2010) Comprehensive modeling of microRNA targets predicts functional non-conserved and non-canonical sites. *Genome Biol.*, **11**, R90.
 54. Chou, C.-H., Chang, N.-W., Shrestha, S., Hsu, S.-D., Lin, Y.-L., Lee, W.-H., Yang, C.-D., Hong, H.-C., Wei, T.-Y. and Tu, S.-J. (2015) miRTarBase 2016: updates to the experimentally validated miRNA-target interactions database. *Nucleic Acids Res.*, **44**, D239–D247.
 55. Giulietti, M., Piva, F., D’Antonio, M., D’Onorio De Meo, P., Paoletti, D., Castrignano, T., D’Erchia, A.M., Picardi, E., Zambelli, F., Principato, G. *et al.* (2013) SpliceAid-F: a database of human splicing factors and their RNA-binding sites. *Nucleic Acids Res.*, **41**, D125–D131.
 56. MacArthur, J., Bowler, E., Cerezo, M., Gil, L., Hall, P., Hastings, E., Junkins, H., McMahon, A., Milano, A., Morales, J. *et al.* (2017) The new NHGRI-EBI Catalog of published genome-wide association studies (GWAS Catalog). *Nucleic Acids Res.*, **45**, D896–D901.
 57. Li, J.-H., Liu, S., Zhou, H., Qu, L.-H. and Yang, J.-H. (2014) starBase v2.0: decoding miRNA-ceRNA, miRNA-ncRNA and protein–RNA interaction networks from large-scale CLIP-Seq data. *Nucleic Acids Res.*, **42**, D92–D97.
 58. Zhao, M., Kim, P., Mitra, R., Zhao, J. and Zhao, Z. (2016) TSGene 2.0: an updated literature-based knowledgebase for tumor suppressor genes. *Nucleic Acids Res.*, **44**, D1023–D1031.
 59. Forbes, S.A., Beare, D., Boutselakis, H., Bamford, S., Bindal, N., Tate, J., Cole, C.G., Ward, S., Dawson, E., Ponting, L. *et al.* (2017) COSMIC: somatic cancer genetics at high-resolution. *Nucleic Acids Res.*, **45**, D777–D783.
 60. Skinner, M.E., Uzilov, A.V., Stein, L.D., Mungall, C.J. and Holmes, I.H. (2009) JBrowse: a next-generation genome browser. *Genome Res.*, **19**, 1630–1638.
 61. Sun, W.-J., Li, J.-H., Liu, S., Wu, J., Zhou, H., Qu, L.-H. and Yang, J.-H. (2015) RMBase: a resource for decoding the landscape of RNA modifications from high-throughput sequencing data. *Nucleic Acids Res.*, **44**, D259–D265.