



Erratum to “Sensor-Assisted Total Knee Arthroplasty: A Narrative Review”

Cheol Hee Park, MD, Sang Jun Song, MD

Department of Orthopaedic Surgery, Kyung Hee University College of Medicine, Seoul, Korea

Clinics in Orthopedic Surgery 2021;13:1-9
<https://doi.org/10.4055/cios20034>

In the article entitled “Sensor-Assisted Total Knee Arthroplasty: A Narrative Review,”¹⁾ the data in Table 1 were incorrectly indicated. The revised data are shown in bold in the table below.

Table 1. Ideal Target Loads in Sensor-Assisted Total Knee Arthroplasty

Variable	Gustke et al. ²⁰⁾	Risitano et al. ²²⁾	Song et al. ¹²⁾
Maximum load (lb)	40	70	55
Maximum mediolateral difference (lb)	15	15 ± 5	15
Medial (lb)	0–40	50 ± 20 (30–70)	10– 55
Lateral (lb)	0–40	35 ± 20 (15– 55)	10– 40
Other factor	< 10 mm excursion	Medial pivoting	Extension > flexion Medial > lateral

Values are presented as mean ± standard deviation, range, or mean ± standard deviation (range).

REFERENCE

1. Park CH, Song SJ. Sensor-assisted total knee arthroplasty: a narrative review. Clin Orthop Surg. 2021;13(1):1-9.