



Correction to: Impact of pandemic COVID-19 outbreak on oral mucositis preventive and treatment protocols: new perspectives for extraoral photobiomodulation therapy

Karina Morais Faria¹ · Wagner Gomes-Silva^{1,2} · Elisa Kauark-Fontes³ · Carolina Guimarães Bonfim-Alves^{1,3} · Luiz Paulo Kowalski⁴ · Ana Carolina Prado-Ribeiro^{1,3} · Aljomar José Vechiato-Filho¹ · Marcio Ajudarte Lopes³ · Gustavo Nader Marta^{5,6} · Gilberto de Castro Jr⁷ · Adriana Franco Paes Leme⁸ · Cesar Augusto Migliorati⁹ · Alan Roger Santos-Silva³ · Thaís Bianca Brandão¹

Published online: 29 April 2021

© Springer-Verlag GmbH Germany, part of Springer Nature 2021

Correction to: Supportive Care in Cancer (2020) 28:4545–4548

<https://doi.org/10.1007/s00520-020-05636-1>

The reason for this errata is a typing error in the photobiomodulation probe specifications, there was an extra 0 (zero) in the wavelength, where you read 6060-nm, it should be 660-nm (page 2, paragraph 5, line 4). We rewrote the sentence with the corrected wavelength specifications for replacement.

Original sentence:

The probe contains 34×6060-nm LED with the following specifications: 6060-nm central wavelength; spectral width of 20 nm at 50% intensity, average power of 10 mW, active area of 0.2 cm²; power density (irradiance) of 51 mW/cm²; and beam divergence of 20° half angle associated with 35×850-nm LED with the following specifications, 850-nm wavelength; spectral width of 45 nm at 50% intensity, average power of 30 mW, active area of 0.2 cm²; power density (irradiance) of 150 mW/cm²; and beam divergence of 22° half angle leading to 1390 mW of total

power, an outer diameter probe of 70 mm, 63 mm of diameter of active area, and an average power density of 44.6 mW/cm².

Corrected sentence:

The probe contains the following specifications: 34×660-nm central wavelength LED, with spectral width of 20 nm at 50% intensity, average power of 10 mW, active area of 0.2 cm²; power density (irradiance) of 51 mW/cm²; and beam divergence of 20° half angle; associated with 35×850-nm wavelength LED, with spectral width of 45 nm at 50% intensity, average power of 30 mW, active area of 0.2 cm²; power density (irradiance) of 150 mW/cm²; and beam divergence of 22° half angle leading to 1390 mW of total power, an outer diameter probe of 70 mm, 63 mm of diameter of active area, and an average power density of 44.6 mW/cm².

Publisher's note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The original article can be found online at <https://doi.org/10.1007/s00520-020-05636-1>.

✉ Alan Roger Santos-Silva
alanroger@fop.unicamp.br

¹ Dental Oncology Service, Instituto Do Câncer Do Estado de São Paulo (ICESP), São Paulo, Brazil

² Medical School, Nove de Julho University, UNINOVE, São Paulo, Brazil

³ Oral Diagnosis Department, Piracicaba Dental School, University of Campinas (UNICAMP), Piracicaba, Brazil

⁴ Head and Neck Surgery Department, University of Sao Paulo, Medical School and Department of Head and Neck Surgery and Otorhinolaryngology A C Camargo Cancer Center, São Paulo, Brazil

⁵ Division of Radiation Oncology, Instituto Do Câncer Do Estado de São Paulo (ICESP), São Paulo, Brazil

⁶ Department of Radiation Oncology, Hospital Sírio-Libanês, São Paulo, Brazil

⁷ Department of Medical Oncology, Instituto Do Câncer Do Estado de São Paulo (ICESP), São Paulo, Brazil

⁸ Brazilian Biosciences National Laboratory, CNPEM, Campinas, São Paulo, LNBio, Brazil

⁹ College of Dentistry, University of Florida, Gainesville, FL, USA